

SANDVIK INC WELDING AND WIRING DIVISION -- SANDVIK -- 3439-01-164-5274

=====
Product Identification
=====

Product ID:SANDVIK

MSDS Date:04/01/1991

FSC:3439

NIIN:01-164-5274

MSDS Number: BYDKK

=== Responsible Party ===

Company Name:SANDVIK INC WELDING AND WIRING DIVISION

Address:INTERSTATE 81 EXT 59

Box:1220

City:SCRANTON

State:PA

ZIP:18501-1220

Country:US

Info Phone Num:717-587-5191 FAX:717-586-81

83

Emergency Phone Num:717-587-5191

CAGE:61005

=== Contractor Identification ===

Company Name:SANDVIK INC WELDING AND WIRING DIVISION

Address:INTERSTATE 81 EXT 59

Box:1220

City:SCRANTON

State:PA

ZIP:18501

Country:US

Phone:717-587-5191

CAGE:61005

=====
Composition/Information on Ingredients
=====

Ingred Name:CHROMIUM (SARA 313) (CERCLA)

CAS:7440-47-3

RTECS #:GB4200000

Fraction by Wt: 0 - 25%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:1 MG/M3

ACGIH TLV:0.5 MG/M3; 9495

EPA Rpt Q

ty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:COPPER (SARA 313) (CERCLA)
CAS:7440-50-8
RTECS #:GL5325000
Fraction by Wt: 30 - 65%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.1MG/M3 FUME/1 DUST
ACGIH TLV:0.2 MG/M3 FUME; 9495
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:IRON
CAS:7439-89-6
RTECS #:NO4565500
Fraction by Wt: 1 - 5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:10 MG/M3 (TDUST)
ACGIH TLV:5 MG/M3 (OXIDE FUME)

Ingred Name:MANGANESE (SARA 313)
CAS:7439-96-5
RTECS #:OO9275000
Fraction by
Wt: 1 - 5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:C 5 MG/M3 DUST
ACGIH TLV:5 MG/M3 DUST 9495

Ingred Name:MOLYBDENUM
CAS:7439-98-7
RTECS #:QA4680000
Fraction by Wt: 1 - 10%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:10 PPM.
ACGIH TLV:10 PPM.

Ingred Name:NICKEL (SARA 313) (CERCLA)
CAS:7440-02-0
RTECS #:QR5950000
Fraction by Wt: 30 - 65%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1 MG/M3
ACGIH TLV:1 MG/M3; 9495

Ingred Name:NIOBIUM (ALSO CALLED COLUMBIUM)
CAS:7440-03-1
Fraction by Wt: 0 - 5%

Other REC Limits:NONE RECOMMENDED

Ingred Name:TITANIUM,

CAS:7440-32-6

RTECS #:XR1700000

Fraction by Wt: 1 - 5%

Other REC Limits:NONE RECOMMENDED

===== Fire Fighting Measures =====

Flash Point:NONFLAMMABLE

Extinguishing Media:USE CHEMICAL OR SAND FOR MOLTEN METALS. COOL
FIRE-EXPOSED CONTAINERS WITH WATER SPRAY.

Fire Fighting Procedures:WEAR FULL PROTECTIVE CLOTHING AND
NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS WITH FULL
FACEPIECE OPERATED

IN THE POSITIVE PRESSURE MODE.

Unusual Fire/Explosion Hazard:THIS PRODUCT IS NONREACTIVE,
NONFLAMMABLE, NONEXPLOSIVE AND NONHAZARDOUS UNTIL WELDED. WELDING
ARC AND SPARKS CAN IGNITE COMBUSTIBLE AND FLAMMABLE MATERIALS.

===== Exposure Controls/Personal Protection =====

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:N1

NRC/State Lic Num:NOT RELEVANT

Viscosity:NOT RELEVANT

Evaporation Rate & Reference:NOT REL
EVENT

Solubility in Water:INSOLUBLE

Appearance and Odor:WELDING WIRE OR STRIP - ODORLESS

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS

Stability Condition to Avoid:NONE

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this inf

ormation to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.