View NSN Online: https://aerobasegroup.kr/nsn/6505-00-023-6481

3M PHARMACEUTICAL, SUB OF MINNESOTA MINING AND MFG -- MEDIHALER-ISO (PRESCRIPTION DRUG),NDC 00089-0785-21 -- 6505-00-023-6481

Product ID:MEDIHALER-ISO (PRESCRIPTION DRUG),NDC 00089-0785-21 MSDS Date:02/17/1995 FSC:6505 NIIN:00-023-6481 **MSDS Number: BYFFP** === Responsible Party === Company Name: 3M PHARMACEUTICAL, SUB OF MINNESOTA MINING AND MFG Address:19901 NORDHO FF ST City:NORTHRIDGE State:CA ZIP:91328-0001 Country:US Info Phone Num:818-709-3076/612-733-1110 Emergency Phone Num:818-709-3076/612-733-1110 CAGE:04515 === Contractor Identification === Company Name: MINNESOTA MINING AND MFG CO 3M PHARMACEUTICAL Address:19901 NORDHOFF ST Box:City:NORTHRIDGE State:CA ZIP:91324-3298 Country:US Phone:818-709-3076 CAGE:04515 Ingred Name: DICHLORODIFLUOROMETHANE (SARA 313) (CERCLA) CAS:75-71-8 RT ECS #:PA8200000 Fraction by Wt: 50.0% Other REC Limits:NONE RECOMMENDED OSHA PEL:1000 PPM ACGIH TLV:1000 PPM; 9495 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS **Ozone Depleting Chemical:1** Ingred Name:TRICHLOROFLUOROMETHANE (CFC-11) (SARA 313) (CERCLA) CAS:75-69-4 RTECS #:PB6125000 Fraction by Wt: 24.8% Other REC Limits:NONE RECOMMENDED OSHA PEL:1000 PPM ACGIH TLV:C, 1000 PPM; 9495 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS **Ozone Depleting Chemical:1** 

Ingred Name: DICHLOROTETRAFLUOROETHANE (SARA 313)

/PROPELLANT 114 CAS:76-14-2 RTECS #:KI1101000 Fraction by Wt: 24.8% Other REC Limits:NONE RECOMMENDED OSHA PEL:1000 PPM ACGIH TLV:1000 PPM; 9495 Ozone Depleting Chemical:1

Ingred Name:ISOPROTERENOL SULFATE CAS:299-95-6 RTECS #:DO2273000 Fraction by Wt: 0.2% Other REC Limits:NONE RECOMMENDED

LD50 LC50 Mixture:TLV 1000 PPM Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA: NO

Health Hazards Acute and Chronic:TARGET ORGANS:EYES, SKIN, CNS, RESPIRATORY TRACT. ACUTE- EYE:MAY CAUSE IRRITATION. FROSTBITE MAY RESULT IF SPRAYED AT CLOSE RANGE. SKIN:MAY CAUSE IRRITATION, FROSTBITE. INHALE:MAY HAVE CNS & CARDIAC E FFECTS, CAUSING DIZZINESS. ORAL:MAY CAUSE DIGESTIVE SYSTEM IRRITATION & CNS IMPAIRMENT. CHRONIC- UNKNOWN.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:EYE AND/OR SKIN FROSTBITE, SKIN IRRITATION, DIZZINESS, NERVOUSNESS, HEADA

CHE, DEPRESSION, ANXIETY, DRY MOUTH, CONFUSION, WEAKNESS, FAINTING, HYPERTENSION OR HYPOTENSION, PALPITATIONS, CARDIAC ARRHYTHM IAS, ABDOMINAL CRAMPS/PAIN, LOSS OF APPETITE, DIARRHEA, NAUSEA, VOMITING

Medical Cond Aggravated by Exposure:INDIVIDUALS WITH CARDIAC ARRHYTHMIA OR RESPIRATORY DISORDERS MAY BE AT INCREASED RISK IN SEVERE EXPOSURES.

First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED:REMOVE TO

FRESH

AIR. PROVIDE CPR/OXYGEN IF NEEDED. CALL A PHYSICIAN. EYES:FLUSH WITH WATER FOR 15 MINUTES, HOLDING EYELIDS OPEN. CALL A PHYSICIAN. SKIN:WA SH WITH SOAP & WATER. ORAL:DO NOT INDUCEVOMITING. IF CONSCIOUS, RINSE MOUTH WITH WATER. SEEK IMMEDIATE MEDICAL ATTENTION. IF SPONTANEOUS VOMITING OCCURS, MONITOR FOR BREATHING DIFFICULTY.

Flash Point:NONE

Extinguishing Media:WATER SPRAY, CARBON DIOXIDE, FOAM OR DRY CHEMICAL

FOR SURROUNDING FIRE. USE WATER SPRAY TO COOL FIRE EXPOSED CYLINDERS.

Fire Fighting Procedures:WEAR PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:MAY FORM CORROSIVE AND TOXIC HYDROGEN FLUORIDE, HYDROGEN CHLORIDE AND/OR PHOSGENE. AEROSOL CAN MAY EXPLODE.

Spill Release Procedures: IF AEROSOL CANS ARE RUPTURED, EXTINGUISH ALL IGNITIO

N SOURCES. WEAR PROTECTIVE EQUIPMENT. VENTILATE AREA. CONTAIN SPILL AND COVER WITH ABSORBENT MATERIAL SUCH AS SAND. COLLECT SPILLED MATERIAL AND PLA CE IN AN APPROVED CLOSED CONTAINER AND SEAL.

Neutralizing Agent:NOT RELEVANT

Handling and Storage Precautions:STORE IN WELL-VENTILATED, DRY, COOL (BELOW 125F) PLACE AWAY FROM OPEN FLAMES AND HOT SURFACES. KEEP OUT OF REACH OF CHILDREN.

Other Precautions: AVOID I

NHALATION EXCEPT FOR THERAPEUTIC APPLICATION.

AVOID EYE OR SKIN CONTACT. WASH WITH SOAP AND WATER AFTER HANDLING AND BEFORE EATING OR DRINKING. USE WITH ADEQUATE VENTILATION TO AVOID VAPOR BUIL UP.

Respiratory Protection:NONE NORMALLY REQUIRED. IF TLV EXCEEDED, WEAR NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS OR SUPPLIED-AIR RESPIRATOR, OPERATED IN POSITIVE PRESSURE MODE. Ventilation:USE GENERAL OR LO CAL EXHAUST VENTILATION TO MEET TLV REQUIREMENTS. Protective Gloves:CLOTH-LINED RUBBER GLOVES Eye Protection:SAFETY GOGGLES/FACE SHIELD Other Protective Equipment:EYEBATH, SAFETY SHOWER, PROTECTIVE CLOTHING Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. Supplemental Safety and Health

HCC:V2 NRC/State Lic Num:NOT RELEVANT Boiling Pt:=-30.C, -22.F Vapor Pres:4379 @ 70F Vapor Density:6.3 Viscosity:NOT RELEVANT Solubility in Water:LIMITED Appearance and Odor:WHITE AEROSOL SUSPENSION IN PRESSURIZED CONTAINERS Percent Volatiles by Volume:98

Stability Indicator/Materials to Avoid:YES Stability Condition to Avoid:OPEN FLAME, EXTREMELY HOT/GLOWING METAL SURFACES, HIGH TEMPERATURES

Hazardous Decomposition Products:MAY FORM HYDROGEN FLUORIDE, HYDROGEN CHLORIDE AND POSSIBLY CARBONYLFLUORIDE.

=====

Waste Disposal Methods:INCINERATE ABSORBED AND PARTIALLY FULL CANS AFTER MIXING WITH FLAMMABLE MATERIAL IN AN APPROVED FACILITY. FOR DISCHARGE OR DISPOSING OF MATERIAL, CONSULT LOCAL, STATE AND FEDERAL AUTHORITIES. DO NOT W ENT TO ATMOSPHERE. RECYLCE PRODUCT IF POSSIBLE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of De fense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.