View NSN Online: https://aerobasegroup.kr/nsn/6850-01-282-9908

## 3M - ENGINEERING SYSTEMS DIV. -- 3M BRAND TYPE 148 TONER

\_\_\_\_\_

MSDS Safety Information

\_\_\_\_\_

FSC: 6850

NIIN: 01-282-9908 MSDS Date: 02/20/1995 MSDS Num: BYHKS

Product ID: 3M BRAND TYPE 148 TONER

MFN: 03

Responsible Party Cage: 1BY21

Name: 3M CO - ENGINEERING SYSTEMS DIV.

Address: 3M CENTER City: ST PAUL MN 5514

4-1000

Info Phone Number: 612-733-1110

Emergency Phone Number: 612-733-1110

Review Ind: Y Published: Y

\_\_\_\_\_\_

Contractor Summary

\_\_\_\_\_\_

Cage: 1BY21

Name: MINNESOTA MINING AND MFG CO ENGINEERING DOCUMENT SYSTEMS DIV

Address: 3M CTR

City: SAINT PAUL MN 55144-1000

Phone: 612-737-4114

Cage: 9X866

Name: SUMMIT ASSOCIATES

Address: 10910-H SOUTHLAKE COURT

City: RICHMOND VA 23236-3914

Phone: 804-794-1434

=

\_\_\_\_\_\_

Item Description Information

\_\_\_\_\_

Item Manager: S9G

Item Name: TONER, DIRECT ELECTROSTATIC PROCESS

Specification Number: NONE Type/Grade/Class: NONE

Unit of Issue: BX

Quantitative Expression: 00000000004EA

UI Container Qty: 4
Type of Container: BOX

\_\_\_\_\_

Ingredients

\_\_\_\_\_\_

Cas: 25213-39-2

Name

: STYRENE ACRYLIC RESIN (MIXTURE WITH CAS# 58353-09-6)

% Wt: 60-100

Other REC Limits: NONE RECOMMENDED

OSHA PEL: NOT ESTABLISHED ACGIH TLV: NOT ESTABLISHED

-----

Cas: 58353-09-6

Name: STYRENE ACRYLIC RESIN (MIXTURE WITH CAS# 25213-39-2)

% Wt: 60-100

Other REC Limits: NONE RECOMMENDED

OSHA PEL: NOT ESTABLISHED ACGIH TLV: NOT ESTABLISHED

-----

Cas: 39382-25-7

Name: BISPHENOL A PROPYLENE OXIDE FUMARATE

% Wt: 10-30

Other REC Limits: NONE RECOMMENDED

OSHA PEL: NOT ESTABLISHED ACGIH TLV: NOT ESTABLISHED

-----

Cas: 9003-07-0

RTECS #: TR5000000 Name: POLYPROPYLENE

% Wt: 5-10

Other REC Limits: NONE RECOMMENDED

OSHA PEL: NOT ESTABLISHED ACGIH TLV: NOT ESTABLISHED

-----

Cas: 8005-02-5

Name: SOLVENT BLACK 7

% Wt: 3-7

Other REC Limits: NONE RECOMMENDED

OSHA PEL: NOT ESTABLISHED ACGIH TLV: NOT ESTABLISHED

-----

Cas: 1333-86-4

RTECS #: FF5800000 Name: CARBON BLACK

% Wt: 3-7

Oth

er REC Limits: NONE RECOMMENDED

OSHA PEL: NOT ESTABLISHED ACGIH TLV: NOT ESTABLISHED

-----

Cas: 112945-52-5 RTECS #: VV7310000

Name: SILICA % Wt: 0.1-1

Other REC Limits: NONE RECOMMENDED

OSHA PEL: 6 MG/M3 ACGIH TLV: 10 MG/M3

\_\_\_\_\_\_

Health Hazards Data

\_\_\_\_\_\_

LD50 LC50 Mixture: ORAL LD50 (RAT) IS UNKNOWN

Route Of Entry Inds - Inhalation: YES

Skin: YES Ingestion: YES Carcinog

enicity Inds - NTP: NO

IARC: NO OSHA: NO

Effects of Exposure: EYES: MECHANICAL EYE IRRITATION. SKIN: MECHANICAL SKIN

IRRITATION. INHALATION: IRRITATION (UPPER RESPIRATORY). INGESTION: IRRITATION

OF GASTROINTESTINAL TISSUES. Explanation Of Carcinogenicity: NONE

Signs And Symptions Of Overexposure: EYE-REDNESS, SCRATCHING OF THE CORNEA AND TEARING. SKIN-ITCHING AND REDNESS. INHALATION-SORENESS OF THE NOSE AND THROAT, COUGHING AND SNEEZING. SWALLOWED-PAIN, VOMITING, ABDOMINAL TENDERNESS,

NAUSEA, BLOOD IN VOMITUS, AND BLOOD IN FECES.

Medical Cond Aggravated By Exposure: NONE SPECIFIED BY MANUFACTURER.

First Aid: EYES: IMMEDIATELY FLUSH WITH LARGE AMOUNTS OF WATER. GET IMMEDIATE MEDICAL ATTENTION. SKIN: WASH AFFECTED AREA WITH SOAP AND WATER. INHALATION: IF SIGNS/SYMPTOMS OCCUR, REMOVE PERSON TO FRESH AIR. IF SIGNS/SYMPTOMS CONTINUE, CALL A PHYSICIAN. SWALLOWED: DRINK 2 GLASSES OF WATER. CALL A PHYSICIAN.

\_\_\_\_\_\_

Handling and Disposal

\_\_\_\_\_\_

Spill Release Procedures: OBSERVE PRECAUTIONS FROM OTHER SECTIONS. VACUUM TO AVOID DUSTING. CAUTION! A VACUUM CLEANER COULD BE AN IGNITION SOURCE. CLEAN UP RESIDUE WITH WATER. PLACE IN CLOSED CONTAINER. CAUTION: POWDER SPILL O N FLOOR MAY CREATE A SLIP HAZARD.

Waste Disposal Methods: INCINERATE IN A INDUSTRIAL OR COMMERCIAL FACILITY.

DISPOSE OF WASTE PRODUCT IN A SANITARY LANDFILL.

Handling And Storage Precautions: STOR

E AWAY FROM HEAT, SPARKS, OPEN FLAMES, AND OTHER SOURCES OF IGNITION. Other Precautions: KEEP AWAY FROM HEAT, SPARKS, OPEN FLAME & amp; OTHER IGNITION SOURCES. \_\_\_\_\_ Fire and Explosion Hazard Information \_\_\_\_\_ Extinguishing Media: WATER SPRAY, CARBON DIOXIDE, DRY CHEMICAL. Fire Fighting Procedures: NOT DETERMINED. Unusual Fire/Explosion Hazard: DUST CLOUDS OF THIS MATERIAL IN COMBINATION WITH AN IGNITION SOURCE MAY BE EXPLOSIVE. \_\_\_\_\_\_ **Control Measures** \_\_\_\_\_\_ Respiratory Protection: AVOID PROLONGED BREATHING OF DUST. Ventilation: USE IN WELL-VENTILATED AREA. Protective Gloves: AVOID PROLONGED OR REPEATED SKIN CONTAC Eye Protection: AVOID EYE CONTACT. Other Protective Equipment: NONE SPECIFIED BY MANUFACTURER. Work Hygienic Practices: WASH HANDS AFTER HANDLING AND BEFORE EATING. Supple mental Safety and Health: NONE \_\_\_\_\_ Physical/Chemical Properties \_\_\_\_\_ HCC: V7 Spec Gravity: 0.30-0.50 Solubility in Water: NIL Appearance and Odor: FINE BLACK POWDER, ESSENTIALLY ODORLESS. \_\_\_\_\_\_ Reactivity Data \_\_\_\_\_\_ Stability Indicator: YES Stability Condition To Avoid: ELEVATED TEMPERATURE STO RAGE MAY CAUSE CLUMPING OF TONER OWDER. Materials To Avoid: NONE SPECIFIED BY MANUFACTURER. Hazardous Decomposition Products: CARBON MONOXIDE, CARBON DIOXIDE,

HYDROCARBONS, STYRENE MONOMER AND CARBON PARTICULATES.

Hazardous Polymerization Indicator: NO Conditions To Avoid Polymerization: NONE

\_\_\_\_\_

Toxicological Information

\_\_\_\_\_\_

\_\_\_\_\_\_

Ecologi

cal Information
======================================
======================================
======================================
Transportation Information
Responsible Party Cage: 1BY21 Trans ID NO: 121864 Product ID: 3M BRAND TYPE 148 TONER MSDS Prepared Date: 02/20/1995 Review Date: 03/27/1996 MFN: 3 Net Unit Weight: 2.8 LBS AF MMAC Code: NR Multiple KIT Number: 0 Review IND: Y Unit Of Issue: BX Container QTY: 4 Type Of Container: BOX
Detail DOT Information ====================================
DOT PSN Code: ZZZ  DOT Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION
Detail IMO Information
Detail IATA Information

IATA PS

N Code: ZZZ

IATA Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

\_\_\_\_\_

**Detail AFI Information** 

\_\_\_\_\_

AFI PSN Code: ZZZ

AFI Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

HAZCOM Label

\_\_\_\_\_\_

Product ID: 3M BRAND TYPE 148 TONER

Cage: 1BY21

Company Name: MIN

NESOTA MINING AND MFG CO ENGINEERING DOCUMENT SYSTEMS DIV

Street: 3M CTR

City: SAINT PAUL MN Zipcode: 55144-1000

Health Emergency Phone: 612-733-1110

Label Required IND: Y

Date Of Label Review: 03/27/1996

Status Code: C

Label Date: 03/27/1996 Origination Code: F Chronic Hazard IND: Y Signal Word: CAUTION Health Hazard: Slight Contact Hazard: Slight Fire Hazard: None

Reactivity Hazard: None

Hazard And Precautions: STORE AWAY FROM HEAT, SPARKS, OPEN FLAMES, AND OTHER

SOURCES OF IGNITION. IN CASE

OF SPILL: OBSERVE PRECAUTIONS FROM OTHER

SECTIONS. VACUUM TO AVOID DUSTING. CAUTION! A VACUUM CLEANER COULD BE AN IGNI TION SOURCE. CLEAN UP RESIDUE WITH WATER. PLACE IN CLOSED CONTAINER. CAUTION: POWDER SPILL ON FLOOR MAY CREATE A SLIP HAZARD. FIRST AID: EYES: IMMEDIATELY FLUSH WITH LARGE AMOUNTS OF WATER. GET IMMEDI ATE MEDICAL ATTENTION. SKIN: WASH AFFECTED AREA WITH SOAP AND WATER. INHALATION: IF SIGNS/SYMPTOMS OCCUR, REMOVE PERSON TO FRESH AIR. IF SIGNS/SYMPTOMS CONTINUE, CALL A PHYSICIAN.

SWALLOWED: DRINK 2 G LASSES OF WATER. CALL A PHYSICIAN.

\_\_\_\_\_

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Departme

## nt of Defense

nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.