

FISKE BROTHERS REFINING CO -- LUBRIPLATE MAG-1, MAG-00 -- 9150-01-095-5512

=====
Product Identification
=====

Product ID:LUBRIPLATE MAG-1, MAG-00

MSDS Date:01/01/1999

FSC:9150

NIIN:01-095-5512

MSDS Number: BYRTX

=== Responsible Party ===

Company Name:FISKE BROTHERS REFINING CO

Address:129 LOCKWOOD ST

City:NEWARK

State:NJ

ZIP:07105-4720

Country:US

Info Phone Num:201-589-9150 / FAX 201-589-4432

Eme

Agency Phone Num:800-255-3924 CHEM-TEL

Preparer's Name:JAMES R. KONTAK

CAGE:9N579

=== Contractor Identification ===

Company Name:FISKE BROS REFINING CO

Address:129 LOCKWOOD ST

Box:City:NEWARK

State:NJ

ZIP:07105-4720

Country:US

Phone:201-589-9150

CAGE:73219

Company Name:FISKE BROTHERS REFINING CO

Address:1500 OAKDALE AVE

Box:City:TOLEDO

State:OH

ZIP:43605

Country:US

Phone:419-691-2491

CAGE:9N579

Company Name:INDUSTRIAL SUPPLY CORP

Address:1905 WESTWOOD AVE

Box:6356

City:RICHMOND

State:VA

ZIP:2323

0

Country:US

Phone:804-355-8041

Contract Num:SPO450-01-M-D653

CAGE:6A908

=====
Composition/Information on Ingredients
=====

Ingred Name:NON-HAZARDOUS INGREDIENT(S)

= Wt:100.

Other REC Limits:NOT PROVIDED

OSHA PEL:0.5 MG/M3 (SB COMPD)

ACGIH TLV:5 MG/M3 (OIL MIST)

=====
Hazards Identification
=====

LD50 LC50 Mixture:NOT PROVIDED

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EFFECTS OF OVEREXPOSURE: PROLONGED OR

REPEATED SKIN CONTACT MAY CAUSE SKIN IRRITATION. PRODUCT CONTACTING EYES MAY CAUSE IRRITATION. HUMAN HEALTH RISKS VARY FROM PERSON TO PERSON. AS A PRECAUTION, EXPOSURE TO LIQUIDS, VAPORS, MISTS AND FUMES SHOULD BE MINIMIZED. THIS PRODUCT HAS A LOW ORDER OF ACUTE ORAL TOXICITY, BUT MINUTE AMOUNTS ASPIRATED INTO THE LUNGS DURING INGESTION MAY CAUSE MILD TO SEVERE PULMONARY INJURY.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE

SKIN IRRITATION. PRODUCT CONTACTING EYES MAY CAUSE IRRITATION.

Medical Cond Aggravated by Exposure:NOT PROVIDED

=====
First Aid Measures
=====

First Aid:EYE CONTACT: FLUSH WITH CLEAR WATER FOR 15 MINUTES OR UNTIL IRRITATION SUBSIDES. IF IRRITATION PERSISTS, CONSULT A PHYSICIAN.

SKIN CONTACT: REMOVE ANY CONTAMINATED CLOTHING AND WASH WITH SOAP AND WATER. IF INJECTED BY HIGH PRESSURE UNDER SKIN, REGARDLESS OF APPEARANCE OR ITS SIZE, CONTACT A PHYSICIAN IMMEDIATELY. DELAY MAY

CAUSE LOSS OF AFFECTED PART OF THE BODY. INHALATION: VAPOR PRESSURE IS VERY LOW AND INHALATION AT ROOM TEMPERATURE IS NOT A PROBLEM. IF OVERCOME BY VAPOR FROM HOT PRODUCT, IMMEDIATELY REMOVE FROM EXPOSURE AND CALL A PHYSICIAN. INGESTION: IF INGESTED, CALL A PHYSICIAN IMMEDIATELY. DO NOT INDUCE VOMITING.

=====
Fire Fighting Measures
=====

Flash Point Method:COC

Flash Point:168.3C

, 335.F

Lower Limits:0.9%

Upper Limits:7.0%

Extinguishing Media:FOAM, DRY CHEMICAL, CARBON DIOXIDE, WATER SPRAY (FOG).

Fire Fighting Procedures:COOL EXPOSED CONTAINERS WITH WATER. USE AIR-SUPPLIED BREATHING EQUIPMENT FOR ENCLOSED OR CONFINED SPACES.

Unusual Fire/Explosion Hazard:DO NOT STORE OR MIX WITH STRONG OXIDANTS. EMPTY CONTAINERS RETAIN RESIDUE. DO NOT CUT, DRILL, GRIND OR WELD, AS THEY MAY EXPLODE.

===== Accidental Release Measures =====

Spil

I Release Procedures:SCRAPE UP GREASE, WASH REMAINDER WITH SUITABLE PETROLEUM SOLVENT OR ADD ABSORBENT. KEEP PETROLEUM PRODUCTS OUT OF SEWERS AND WATER COURSES. ADVISE AUTHORITIES IF PRODUCT HAS ENTERED OR MAY ENTER SEWER S AND WATER COURSES.

Neutralizing Agent:NOT PROVIDED

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED WHEN NOT IN USE. DO NOT HANDLE OR STORE NEAR HEAT, SPARKS, FLAME, OR STRONG OXIDANTS.

Other Precautions:REMOVE OIL-SOAKED CLOTHING AND LAUNDRER BEFORE REUSE. CLEANSE SKIN THOROUGHLY AFTER CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NORMALLY NOT NEEDED.

Ventilation:USE LOCAL EXHAUST TO CAPTURE FUMES AND VAPORS.

Protective Gloves:USE OIL-RESISTANT GLOVES IF NEEDED.

Eye Protection:WEAR GOGGLES.

Other Protective Equipment:USE OIL RESISTANT APRON IF NEEDED.

Work Hygienic Practices:REMOVE OIL SOAKED CLOTHING AND LAUNDRER BEFORE

REUSE. CLEANSE SKIN THOROUGHLY AFTER CONTACT.

Supplemental Safety and Health

CONTRACTOR'S (INDUSTRIAL SUPPLY CORPORATION) PART NUMBER: L0189.001.

ABBREVIATION: N/A = NOT APPLICABLE. N/AV = NOT AVAILABLE. N/K =

UNKNOWN. N/P = NOT PROVIDED. N/R = NOT RELEVANT. N/D = NOT DETERMINED. N/E = NOT ESTABLISHED.

===== Physical/Chemical Properties =====

HCC:V6

NRC/State Lic Num:NOT RELEVANT

Boiling Pt:>287.8C, 550.F

Melt/Freeze Pt:M.P/F.P Text:SEMI-

SOLID

Decomp Temp:Decomp Text:NOT PROVIDED

Vapor Pres:5

Spec Gravity:0.87-0.89

pH:NOT PROVIDED

Viscosity:NOT PROVIDED

Evaporation Rate & Reference: