

SHERWIN-WILLIAMS CO THE SPECIALTY DIV. -- G2W10 KRYLON 1501 GLOSSY WHITE --
8010-00-079-3762

===== Product Identification =====

Product ID:G2W10 KRYLON 1501 GLOSSY WHITE

MSDS Date:04/10/1989

FSC:8010

NIIN:00-079-3762

MSDS Number: BYSYN

=== Responsible Party ===

Company Name:SHERWIN-WILLIAMS CO THE SPECIALTY DIV.

Address:31500 SOLON RD

City:SOLON

State:OH

ZIP:44146-5000

Country:US

Info Phone Num:8

00-777-2966

Emergency Phone Num:800-777-2966/216-292-700

CAGE:DO642

=== Contractor Identification ===

Company Name:BLICK DICK CO

Address:P O BOX 1267

Box:City:GALESBURG

State:IL

ZIP:61401

Country:US

Phone:309-343-6181

CAGE:06608

Company Name:SAX ARTS & CRAFTS SUB OF BEATRICE COMPANIES INC

Address:2405 S CALHOUN RD

Box:City:NEW BERLIN

State:WI

ZIP:53151

Country:US

Phone:262-784-6880

CAGE:26290

Company Name:SHERWIN-WILLIAMS CO THE SPECIALTY DIV.

Address:6830 COCHRAN RD.

Box:6709

City:SOLON

State:O

TECS #:SA9275000
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM
ACGIH TLV:50 PPM/75 STEL; 9495
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE
CAS:108-65-6
RTECS #:AI8295000
Fraction by Wt: 5-10%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:NOT ESTABLISHED.
ACGIH TLV:NOT ESTABLISHED.

Ingred Name:TOLUENE (SARA 313) (CERCLA)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:200 PPM
; Z-2
ACGIH TLV:S, 50 PPM; 9495
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA 313) (CERCLA)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 10-30%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM
ACGIH TLV:100 PPM/150STEL;9495
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:TITANIUM DIOXIDE
CAS:13463-67-7
RTECS #:XR2275000
Fraction by Wt: 5-10%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9495

=====

==== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: INGESTION NOT EXPECTED TO HARMFUL UNDER NORMAL CONDITIONS OF USE. INHALATION OF VAPORS/MISTS MAY CAUSE RESPIRATORY IRRITATION, CNS DEPRESSION, ASPHYXIATION, LIVER/KIDNEY DAMAGE. CONTACT MAY CAUSE SKIN AND EYE IRRITATION. CHRONIC:NONE SPECIFIED BY MANUFACTURER.

Explanation of C

arcinogenicity:NO INGREDIENT OF A CONCENTRATION OF 0.1% OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN.

Effects of Overexposure:INHALED-HEADACHE, DIZZINESS, NAUSEA, VOMITING, UNCONSCIOUSNESS, CYANOSIS. SKIN-IRRITATION. EYES-IRRITATION. INGESTED-NONE SPECIFIED BY MANUFACTURER.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

==== First Aid Measures =====

First Aid:IN ALL CASES GET MEDICAL ATTENTION. EYES-IMMEDIATELY FLUSH

WITH WATER FOR 15 MINUTES, LIFT LIDS. SKIN-REMOVE CONTAMINATED CLOTHES. FLUSH WITH LOTS OF WATER. INHALED-REMOVE TO FRESH AIR. ADMINISTER OXYGEN OR ARTIFICIAL RESPIRATION AS NEEDED. INGESTED-IF CONSCIOUS, GIVE LOTS OF WATER AND CONTACT POISON CONTROL CENTER OR EMERGENCY ROOM.

==== Fire Fighting Measures =====

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM. WATER MAY BE INEFFECTIVE BUT SHOULD BE USED TO COOL FIRE EXPOSED CONTAINERS.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE GEAR.

Unusual Fire/Explosion Hazard:EXTREMELY FLAMMABLE. VAPOR MAY IGNITE EXPLOSIVELY. VAPORS MAY TRAVEL TO DISTANT IGNITION SOURCE AND FLASHBACK.

==== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. SOAK UP WITH INERT ABSORBENT MATERIAL AND REMOVE TO A CHEMICAL DISPOSAL AREA. PREVENT ENTRY INTO BODI

ES OF WATER.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN A COOL, DRY PLACE BELOW 120F AND AWAY FROM SOURCES OF IGNITION AND STRONG OXIDIZING AGENTS.

Other Precautions:AVOID CONTACT WITH SKIN AND EYES. AVOID BEATHING VAPOR OR MIST.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:IF ENGINEERING CONTROLS FAIL OR NON-ROUTINE USE

OR AN EMERGENCY OCCURS; WEAR AN MSHA/NIOSH APPROVED RESPIRATOR WITH ORGANIC VAPOR CARTRIDGE OR AN AIR-SUPPLIED RESPIRATOR OR SCBA, AS REQUIRED. USE IAW 29 CFR 1910.134.

Ventilation:USE EXPLOSION-PROOF ADEQUATE MECHANICAL VENTILATION OR LOCAL EXHAUST TO MAINTAIN EXPOSURE BELOW TLV(S).

Protective Gloves:BUTYL, PVA.

Eye Protection:SAFETY GLASSES/CHEMICAL SPLASH GOGGLES.

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER. DLA-HMIS: EYE WASH STATION & SAFETY SHOWER.

Work Hy

gienic Practices:WASH HANDS AFTER HANDLING AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDRER CONTAMINATED CLOTHES BEFORE REUSE.

Supplemental Safety and Health

SAX ARTS & CRAFTS PART NUMBER: 317-0016. CONTRACT NUMBER SP0420-95-PA057.

=====
Physical/Chemical Properties
=====

HCC:V3

Vapor Pres:60 PSIG

Spec Gravity:1 (N-BUTYL ACETATE=1)

Solubility in Water:SLIGHT

Appearance and Odor:WHITE LIQUID IN AEROSOL CAN WITH GAS PROPELLANT.

Percent Volatiles by Volume:89

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES

NONE SPECIFIED BY MANUFACTURER. DLA-HMIS: STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER. DLA-HMIS:

AVOID EXPOSURE TO HIGH TEMPERATURES AND STRONG OXIDIZING AGENTS.

Hazardous Decomposition Products:OXIDES OF CARBON.

Conditions to Avoid Polymerization:WILL NOT OCCUR.

=====
Disposal Considerations
=====

Waste Dis

posal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND
FEDERAL ENVIRONMENTAL REGULATIONS. EMPTY CONTAINER MAY CONTAIN
EXPLSOIVE VAPORS. DO NOT CUT, PUNCTURE OR WELD ON OR NEARBY.
INCINERATION WILL CAUSE CONTA INER TO BURST VIOLENTLY.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this
information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.