

AMERICAN GAS AND CHEMICAL COMPANY,LTD -- FLAW FINDER AG-DN DEVELOPER --
6850-01-264-8680

===== Product Identification =====

Product ID:FLAW FINDER AG-DN DEVELOPER

MSDS Date:06/06/1996

FSC:6850

NIIN:01-264-8680

MSDS Number: BYVXM

=== Responsible Party ===

Company Name:AMERICAN GAS AND CHEMICAL COMPANY,LTD

Address:220 PEGASUS AVENUE,

City:NORTHVALE

State:NJ

ZIP:07647-1904

Country:US

Info Phone Num:8

00-526-1008

Emergency Phone Num:800-526-1008/201-767-7300

Preparer's Name:ELENA FROST

CAGE:03530

=== Contractor Identification ===

Company Name:AMERICAN GAS AND CHEMICAL COMPANY,LTD

Address:220 PEGASUS AVENUE,

City:NORTHVALE

State:NJ

ZIP:07647-1904

Country:US

Phone:201-767-7300

CAGE:03530

Company Name:SOLVENTS AND CHEMICALS, INC.

Address:4704 SHANK ROAD

Box:City:PEARLAND

State:TX

ZIP:77588-0490

Country:US

Phone:281-485-5377

CAGE:4W432

===== Composition/Information on Ingredients =====

=====

Ingred Name:ISOPROPYL ALCOHOL (SARA 313)
CAS:67-63-0
RTECS #:NT8050000
Fraction by Wt: 84%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:400 PPM
ACGIH TLV:400 PPM/500STEL;9495

Ingred Name:NON-HAZARDOUS INGREDIENTS
Fraction by Wt: 16%
Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL, RAT) IS UNKNOWN.
Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:
NO
Health Hazards Acute and Chronic:TARGET ORGANS:EYE, SKIN, CNS,
RESPIRATORY & GI TRACTS. ACUTE- HARMFUL IF INHALED/INGESTED. MAY
CAUSE CNS DEPRESSION, HEADACHE. MAY CAUSE EYE IRRITATION.
PROLONGED/REPEATED SKIN CONTACT MAY CAUSE DEFAT TING, IRRITATION.
CHRONIC- UNKNOWN.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:IRRITATION, HEADACHE, DIZZINESS, NAUSEA,
VOMITING, TEARING, DEFATTING OF SKIN AND DRYNESS, IN EXTREME CASES,
UNCONSCIOUSNESS, RESPIRATORY DEPRE
SSION AND DEATH
Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING SKIN
DISORDERS, EYE PROBLEMS OR IMPAIRED RESPIRATORY FUNCTION MAY BE
MORE SUSCEPTIBLE TO THE EFFECTS OF THIS PRODUCT.

===== First Aid Measures =====

First Aid:CALL PHYSICIAN IF SYMPTOMS PERSIST. EYE:IMMEDIATELY FLUSH
WITH WATER FOR 15 MINUTES. HOLD EYELIDS OPEN. SKIN:FLUSH WITH
WATER. INHALED:REMOVE TO FRESH AIR. PROVIDE CPR/OXYGEN IF NEEDED.
ORAL:IF CONSCI OU

S, DRINK NO MORE THAN 2 GLASSES OF WATER & INDUCE VOMITING. CALL A PHYSICIAN/POISON CONTROL CENTER IMMEDIATELY. NEVER GIVE FLUID OR INDUCE VOMITING IF PATIENT IS UNCONSCIOUS OR HAS CONVULSIONS.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:53.0F,11.7C

Lower Limits:2.0

Upper Limits:12.0

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, "ALCOHOL" FOAM, OR DRY CHEMICAL. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Fire F

ighting Procedures:DO NOT ENTER ANY ENCLOSED OR CONFINED AREA WITHOUT PROPER PROTECTIVE EQUIPMENT AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:VAPOR IS HEAVIER THAN AIR AND CAN TRAVEL CONSIDERABLE DISTANCE TO A SOURCE OF IGNITION AND FLASH BACK. CONTAINERS MAY RUPTURE DUE TO VAPOR PRESSURE BUILDUP.

===== Accidental Release Measures =====

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENT. ELIMINATE SOURCES

OF IGNITION. VENTILATE AREA. REMOVE SPILL WITH PUMP(EXPLOSION PROOF)/WITH NON-FLAMMABLE ABSORBENT SUCH AS SAND. PLACE IN CONTAINER FOR DISPOSAL. PREVENT LI QUID FROM ENTERING SEWERS, WATERWAYS ORLOW AREAS.

Neutralizing Agent:DILUTE WITH WATER

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN TIGHTLY CLOSED CONTAINERS IN FLAMMABLE LIQUID STORAGE ROOM/CABINET. AVOID EXCESSIVE HEAT. KEEP AWAY FROM INCOMPATIBLE MATERIA

LS.

Other Precautions:AVOID BREATHING VAPORS. DO NOT GET IN EYES, ON SKIN OR ON CLOTHING. WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING OR DRINKING. KEEP OUT OF REACH OF CHILDREN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF TLV IS EXCEEDED OR FOR SYMPTOMS OF OVER EXPOSURE, WEAR NIOSH-APPROVED ORGANIC VAPOR RESPIRATOR OR SUPPLIED AIR RESPIRATOR. IN EMERGENCY, WEAR A NIOSH-APPROVED POSITIVE-PRESSURE SELF-CONTAINED BREAT HIN

G APPARATUS.

Ventilation:MECHANICAL (GENERAL AND/OR LOCAL EXHAUST, EXPLOSION-PROOF)
VENTILATION TO MAINTAIN EXPOSURE BELOW TLV(S).

Protective Gloves:RUBBER, NEOPRENE FOR REPEATED CONTACT

Eye Protection:SAFETY GLASSES/CHEMICAL SPLASH GOGGLES

Other Protective Equipment:EYE WASH STATION & SAFETY SHOWERS SHOULD BE
AVAILABLE IN THE IMMEDIATE VICINITY OF ANY POTENTIAL EXPOSURE.

Work Hygienic Practices:WASH HANDS BEFORE EATING, DRINKING, SMOKING, OR
USING TOILET FACILITIES. WASH CONTAMINATE
D CLOTHING BEFORE REUSE.

Supplemental Safety and Health

NOTE TO PHYSICIAN: IF VICTIM IS A CHILD, GIVE NO MORE THAN 1 GLASS OF
WATER AND 15CC (1 TABLESPOON) SYRUP OF IPECAC. IF SYMPTOMS SUCH AS
LOSS OF GAG REFLEX, CONVULSIONS OR UNCONSCIOUSNESS OCCUR BEFORE
EMESIS, GASTRIC LAVAGE SHOULD BE CONSIDERED FOLLOWING INTUBATION
WITH A CUFFED ENDOTRACHEAL TUBE.

===== Physical/Chemical Properties =====

HCC:F2

NRC/State Lic Num:NOT RELEVANT

Boiling Pt:=82.C, 1

79.6F

Melt/Freeze Pt:=-88.C, -126.4F

Vapor Pres:32 @ 68F

Vapor Density:2.1

Spec Gravity:0.789

Evaporation Rate & Reference:1.4 (N-BUTYL ACETATE=1)

Solubility in Water:COMPLETE

Appearance and Odor:COLORLESS, MOBILE LIQUID - MILD ODOR

Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, ALUMINUM EQUIPMENT AT TEMPERATURES ABOVE 120F

Stability Condition to Avoid:HIGH HEAT, SPARKS,

OPEN FLAMES AND OTHER

SOURCES OF IGNITION

Hazardous Decomposition Products:MAY EMIT CARBON MONOXIDE, CARBON
DIOXIDE AND OTHER UNIDENTIFIED ORGANIC COMPOUNDS.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN AN APPROVED INCINERATOR OR CONTRACT
WITH LICENSED CHEMICAL WASTE DISPOSAL SERVICE. DISCHARGE, TREATMENT
OR DISPOSAL IS SUBJECT TO FEDERAL, STATE OR LOCAL LAWS. WHEN EMPTY,
THOROUGHLY RINSE C ONTAINER WITH WATER BEFORE

DISPOSAL.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.