View NSN Online: https://aerobasegroup.kr/nsn/1420-00-627-2131

CHEMTECH INDUSTRIES,INC. -- LIQUID CAUSTIC POTASH,PART A,(ONE OF FOUR ITEMS)

1420-00-627-2131

Product ID:LIQUID CAUSTIC POTASH, PART A, (ONE OF FOUR ITEMS)

MSDS Date:11/01/1983

FSC:1420

NIIN:00-627-2131

MSDS Number: BYXKD === Responsible Party ===

Company Name: CHEMTECH INDUSTRIES, INC.

Address:1655 BES PERES RD

Box:31000

City:SAINT LOUIS

State:MO ZIP:63131 Countr v:US

Info Phone Num:314-966-9900

Emergency Phone Num:314-966-9900

Preparer's Name: NONE

CAGE:56894

=== Contractor Identification ===

Company Name: CHEMTECH INDUSTRIES INC MANUFACTURED PRODUCTS DIV

Address:1655 DES PERES RD

Box:31000 City:ST. LOUIS State:MO

ZIP:63131-1821 Country:US

Phone:314-966-9934

CAGE:56894

Company Name: EAGLE-PICHER INDUSTRIES, INC.

Address: C AND PORTER STS

Box:47 City:JOPLIN State:MO ZIP:64801 Country:US

Phone:417-623-8000

CAGE:81855

Company Name: HUGHES AIRCRAFT CO RADAR SYST


EMS GROUP Address:BLDG C1 MS A142 Box:92426 City:LOS ANGELES State:CA ZIP:90009 Country:US Phone:213-568-7200 CAGE:82577 ======= Composition/Information on Ingredients ========= Ingred Name:POTASSIUM HYDROXIDE (CERCLA), (ESTIMATED KOH=7 OZ/BATTERY) CAS:1310-58-3 RTECS #:TT2100000 Fraction by Wt: 48%(VOL) Other REC Limits: NONE RECOMMENDED OSHA PEL:C 2 MG/M3 ACGIH TLV:C 2 MG/M3; 9495 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS ====== Hazards Identification ======== LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: ACUTE: EYES: SEVERE BURNS. SKIN: SEVERE BURNS. INHALATION: DUST AND MISTS CORROSIVE TO RESPIRATORY SYSTEM. INGESTION: CORROSIVE TO MOUTH, THROAT, AND DIGESTIVE TRACT. CHRONIC: NONE SPECIFIED BY MANUFA CTURER. **Explanation of Carcinogenicity:NONE** Effects of Overexposure: EYES: IRRITATI ON, CHEMICAL BURNS. SKIN:

IRRITATION, CHEMICAL BURNS. INHALATION: SEVERE IRRITATION.

INGESTION. SEVERE IRRITATION AND CHEMICAL BURNS.

Medical Cond Aggravated by Exposure: NONE SPECIFIED BY MANUFACTURER.

First Aid:EYES/SKIN: FLUSH WITH LARGE AMOUNTS OF WATER. DO NOT NEUTRALIZE. GET MEDICAL ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING. INHALATION: MOVE TO FRESH AIR. SUPPORT BREATHING AS NEEDED. GET MEDICAL A



============ Fire Fighting Measures ===============

Flash Point: NON-FLAMMABLE

Extinguishing Media:NON-FLAMMABLE. USE MEDIA APPROPRIATE FOR SURROUNDING FIRE.

Fire Fighting Procedures: NONE SPECIFIED BY MANUFACTURER.

Unusual Fire/Explosion Hazard:HOT OR MOLTEN MATERIAL WILL REACT VIOLENTLY WITH WATER LIBER

ATING HEAT AND CAUSING SPLASHING.

======== Accidental Release Measures ===========

Spill Release Procedures:SHOVEL UP AND CONTAINERIZE MATERIAL, FOLLOWED BY FLUSHING WITH LARGE AMOUNTS OF WATER AND DILUTE ACID. AN APPLICATION OF SODIUM BICARBONATE WILL NEUTRALIZE FINAL TRACES OF CAUSTIC SODA.

Neutralizing Agent: SODIUM BICARBONATE.

========== Handling and Storage ==============

Handling and Storage Precautions: DO NOT GET IN EYES, ON SKIN, OR ON

CLOTHING. AVOID BREATHING DUST OR MIST. DO NOT TAKE INTERNALLY. Other Precautions:WHEN HANDLING, WEAR GOGGLES, FACE SHIELD, RUBBER GLOVES, APRON, AND PROTECTIVE CLOTHING. WHEN DILUTING CAUSTIC POTASH, ADD IT TO WATER WITH AGITATION TO AVOID SPLATTERING AND EXCESSIVE HEAT GENERATION.

====== Exposure Controls/Personal Protection ========

Respiratory Protection:WEAR NIOSH APPROVED RESPIRATOR FOR DUST AND MIST.

Ventilation:PROVIDE SUFFICIENT LOCAL EXHAUST TO

MAINTAIN AIR

CONCENTRATION BELOW 2 MG/M3.

Protective Gloves: RUBBER, PVC, OR NEOPRENE RECOMMENDED.

Eye Protection: CHEMICAL SAFETY GOGGLES RECOMMENDED.

Other Protective Equipment: RUBBER BOOTS AND APRONS. PROVIDE EYE WASH STATION AND SAFETY SHOWER IN AREAS WHERE CAUSTIC SODA IS BEING HANDLED.

Work Hygienic Practices:WASH AFTER HANDLING AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. Supplemental Safety and Health

THIS ITEM IS NOT PART OF A KIT. T

HIS ENTRY DESCRIBES ONE OF THE FOUR
ITEMS THAT MAKE-UP THE "BATTERY, EXPLOSIVE" SPECIFIED IN NSN
1420-00-627-2131. SEE THIS SAME NSN, P/N IND'S C, D, AND E, FOR
DATA ON THE OTHER THREE ITEMS. ESTIMATED CALCULATED HAZARDOUS
MATERIAL (TOTAL FOR ALL FOUR ITEMS, P/N A,B,C,D) IN BATTERY=5 LBS.

======== Physical/Chemical Properties ===========

HCC:B1

Boiling Pt:=133.C, 271.4F

Vapor Pres:39 Spec Gravity:1.45 pH:BASIC

Solubility in Water: COMPLETE

Appearance and Odor:P
RACTICALLY ODORLESS.

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES

ALUMINUM, TIN, LEAD, ZINC, AND THEIR ALLOYS. ALL ACIDS, LEATHER, AND WOOL.

Stability Condition to Avoid: NONE.

Hazardous Decomposition Products: NONE.

Conditions to Avoid Polymerization: WILL NOT OCCUR.

======= Disposal Considerations ===========

Waste Disposal Methods:DISPOSE OF WASTE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGU

LATIONS REGARDING HEALTH AND POLLUTION.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.