View NSN Online: https://aerobasegroup.com/nsn/8030-01-196-1958

COURTAULDS AEROSPACE, INC -- PRO-SEAL 870 B-2 (0870B11) ACCELERATOR 8030-01-196-1958

============= Product Identification ========================

Product ID:PRO-SEAL 870 B-2 (0870B11) ACCELERATOR

MSDS Date:06/03/1994

FSC:8030

NIIN:01-196-1958

Kit Part:Y

MSDS Number: BYXXS === Responsible Party ===

Company Name: COURTAULDS AEROSPACE, INC

Address:5430 SAN FERNANDO RD.

Box:1800

City:GLENDALE

State:CA ZIP:91209 Country:US

nfo Phone Num:818-240-2060

Emergency Phone Num:800-424-9300 (CHEMTREC)

CAGE:83574

=== Contractor Identification ===

Company Name: PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA ZIP:91209 Country:US

Phone:818-240-2060

CAGE:83574

======= Composition/Information on Ingredients ========

Ingred Name: MAGNESIUM CHROMATE (SARA 313)

CAS:13423-61-5 Fraction by Wt: 25%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:0.1 MG/M3 (A

S CR) ACGIH TLV:0.05 MG/M3

Ingred Name: 1,3 DIPHENYL GUANIDINE

CAS:102-06-7 Fraction by Wt: 5%

Other REC Limits: NONE RECOMMENDED

Ingred Name: MANGANESE DIOXIDE (SARA 313)

CAS:1313-13-9

RTECS #:OP0350000 Fraction by Wt: 40%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:5 MG/M3 (CEILING)

ACGIH TLV:5 MG/M3

Ingred Name: HYDROGENATED TERPHENYLS (VP = 1 MMHG

CAS:61788-32-7 RTECS #:WZ6535000 Fraction by Wt: 35%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:0.5 PPM ACGIH TLV:0.5 PPM

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES: SEVERE IRRITANT. POSSIBLE EYE

DAMAGE. SKIN: IRRITATION. MAY CAUSE ALLERGIC SKIN RASH IN

SENSITIZED PEOPLE. INHALATION/INGESTION: ALTHOUGH MAIN HAZARD OF MANGANESE COMPOUNDS IS BREATHING DUST, IN GESTION SHOULD BE AVOIDED

AS PRECAUTIONAGAINST MANGANESE POISONING.

Effects of Overexposure:SKI

N: PROLONGED EXPOSURE TO HEXAVALENT CHROMIUM COMPOUNDS OVER PEL MAY CAUSE PAINLESS PENETRATING SKIN ULCERS. INHALATION/INGESTION: PROLONGED EXPOSURE TO HEXAVALENT CHROMIUM COMPOUNDS OVER PEL MAY CA USE PENETRATING ULCERS OF MUCOUS MEMBRANES OF NOSE & PERFORATION OF CARTILAGINOUS NASAL SEPTUM.

First Aid:EYES: FLUSH W/LUKE WARM WATER 15 MINUTES. IF SYMPTOMS PERSIST, CONSULT DR. SKIN: WASH W/SOAP & WATER. IF

| PERSIST, CONSULT DR. INHALATION: GET FRESH AIR. GET MEDICAL AID. INGESTION: CONSULT DR . |
|--|
| ====================================== |
| Flash Point:>200F,>93C Extinguishing Media:CO2, DRY CHEMICAL, FOAM, WATER. Fire Fighting Procedures:USE AIR-SUPPLIED RESPIRATOR. USE WATER TO COOL HEAT EXPOSED CONTAINERS. Unusual Fire/Explosion Hazard:EXCESSIVE HEAT MAY CAUSE DECOMPOSITION OF MANGANESE DIOXIDES RESULTING IN OXIDATION & POSSIBLE IGNITION OF HY |
| DROCARBON VEHICLE. |
| ============ Accidental Release Measures ============= |
| Spill Release Procedures:SCOOP INTO CONTAINERS. CLEAN UP RESIDUE W/SUITABLE SOLVENT. |
| ====================================== |
| Handling and Storage Precautions:WASH THOROUGHLY AFTER HANDLING & BEFORE SMOKING OR EATING. AVOID INGESTION. |
| ====== Exposure Controls/Personal Protection ======== |
| Ventilation:GENERAL Protective Gloves:SOLVENT RESISTANT Eye Protectio n:SAFETY GLASSES Supplemental Safety and Health NK |
| ========= Physical/Chemical Properties ========== |
| Boiling Pt:B.P. Text:644F,340C Vapor Density:NONVOL. Spec Gravity:1.801 Evaporation Rate & Description Rate |
| ========= Stability and Reactivity Data ========== |
| Stability Indicator/Materials to Avoid:YES EASILY OXIDIZABLE MATERIALS. |

Hazardous Decomposition Product

SYMPTOMS

s:OXIDES OF CARBON & NITROGEN, CHROMIUM & MANGANESE COMPOUNDS.

======= Disposal Considerations ==========

Waste Disposal Methods: EPA WASTE #D-007. DISPOSE IN ACCORDANCE W/FEDERAL, STATE, LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.