

DOW CORNING CORP -- DOW CORNING 3-7132 RTV ADHESIVE SEALANT -- 8040-01-331-7468

=====
Product Identification
=====

Product ID:DOW CORNING 3-7132 RTV ADHESIVE SEALANT

MSDS Date:07/11/1994

FSC:8040

NIIN:01-331-7468

MSDS Number: BYYJL

=== Responsible Party ===

Company Name:DOW CORNING CORP

Address:SOUTH SAGINAW ROAD

City:MIDLAND

State:MI

ZIP:48686

Country:US

Info Phone Num:517-496-5900

Emergency Pho

ne Num:517-496-5900

CAGE:5D028

=== Contractor Identification ===

Company Name:DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

Company Name:DOW CORNING CORP

Address:2200 W SALZBURG RD

Box:City:AUBURN

State:MI

ZIP:48611

Country:US

Phone:517-496-4388

CAGE:71984

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYLTRACETOXYSILANE

CAS:4253-34-3

RTECS #:VV4500000

Fraction

by Wt: 2.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:10 PPM
ACGIH TLV:10 PPM/STEL 15 PPM

Ingred Name:ETHYLTRIACETOXYSILANE
CAS:17689-77-9
Fraction by Wt: 2.0%
Other REC Limits:NONE RECOMMENDED

Ingred Name:SILICA AMORPHOUS
CAS:112945-52-5
Fraction by Wt: 10.0%
Other REC Limits:*5 MG/M3 RESP FRACTN
OSHA PEL:15 MG/M3, T DUST*
ACGIH TLV:10 MG/M3, T DUST

===== Fire Fighting Measures =====

Flash Point Method:CC
Flash Point:NA - SOLID
Extinguishing Media:WATER, WA
TER FOG OR SPRAY, CO2, DRY CHEMICAL, FOAM.
Fire Fighting Procedures:SCBA & PROTECTIVE CLOTHING SHOULD BE WORN IN
FIRES INVOLVING CHEMICALS. IF LARGE AMOUNT CHEMICALS INVOLVED,
EVACUATE AREA.
Unusual Fire/Explosion Hazard:NONE

===== Exposure Controls/Personal Protection =====

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V7
Boiling Pt:B.P. Text:NA
Vapor Pres:NA
Vapor Density:NA
Spec Gravity:1.03
pH:NA
Solubili

ty in Water:NONE

Appearance and Odor:RED PASTE, ACETIC ACID ODOR

Percent Volatiles by Volume:NA

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZING MATERIAL. AIR OR MOISTURE CAUSES CURING, ACETIC VAPORS FORM.

Stability Condition to Avoid:EXPOSURE TO MOISTURE OR HUMID AIR UNTIL
READY TO USE.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.