

MAINTEX INC. -- SHOWER, TUB & TILE (HARD WATER/SCUM REMOVER) -- 7930-01-398-0856

=====  
Product Identification  
=====

Product ID:SHOWER, TUB & TILE (HARD WATER/SCUM REMOVER)

MSDS Date:06/11/1994

FSC:7930

NIIN:01-398-0856

MSDS Number: BYZBR

=== Responsible Party ===

Company Name:MAINTEX INC.

Address:13300 NELSON AVE.

City:CITY OF INDUSTRY

State:CA

ZIP:91746

Country:US

Info Phone Num:818-961-1988

Emer

gency Phone Num:800-255-3924 (CHEMTEL)

Preparer's Name:ALI ABYANE

CAGE:NO277

=== Contractor Identification ===

Company Name:MAINTEX INC

Address:13300 NELSON AVE

Box:City:CITY OF INDUSTRY

State:CA

ZIP:91746

Country:US

Phone:818-961-1988

CAGE:0PWJ2

Company Name:MAINTEX INC.

Address:3614 EL MONTE AVE

Box:City:EL MONTE

State:CA

ZIP:91731

Phone:213-283-7380

CAGE:NO277

=====  
Composition/Information on Ingredients  
=====

Ingred Name:GLYCOLIC ACID

CAS:79-14-1

Fraction by Wt: 15-20%

Ot

her REC Limits:NONE RECOMMENDED  
OSHA PEL:NOT EST.  
ACGIH TLV:NOT EST.

Ingred Name:VOC = 4%  
RTECS #:9999999VO  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:NOT EST.  
ACGIH TLV:NOT EST.

=====  
Hazards Identification  
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:EYES: IRRIT. DAMAGE W/BRIEF CONTACT  
LIQUIDS/MISTS. POS PERM INJURY W/EXTENDED CONTACT. SKIN: IRRIT BY

VAPORS. VAPOR/LIQ/MISTS CORROSIVE. INHAL: IRRIT/BURNS W/EXTENDED  
CONTACT. INGEST: BURNS TISSUES. C HRONIC-SKIN: ALLERGIC REACTIONS  
W/OVEREXPOSURE.

Effects of Overexposure:INGEST: ABDOMINAL PAIN, NAUSEA, VOMITING. EYES:  
STINGING, WATERING.

Medical Cond Aggravated by Exposure:INHALATION/INGESTION: POSSIBLE  
AGGRAVATION OF PREEXISTING LUNG DISEASE.

=====  
First Aid Measures  
=====

First Aid:EYES: REMOVE CONTACTS. IMMEDIATELY FLUSH W/LOTS WATER  
>15  
MINUTES. CALL DR. SKIN: WASH W/SOAP & WATER. INHALATION: IF  
DISCOMFORT, GET FRESH AIR. IF BREATHING DIFFICULT, IMMEDIATELY GET  
MEDICAL AID. IN GESTION: GET PLENTY WATER. DO NOT INDUCE VOMITING.  
WASH OUT MOUTH AREA. CALL DR.

=====  
Fire Fighting Measures  
=====

Flash Point:>250F,>121C  
Extinguishing Media:WATER SPRAY, FOAM, CO2, DRY CHEMICAL.  
Fire Fighting Procedures:POSITIVE PRESSURE SCBA W/FULL FACEPIECE FOR  
FIREFIGHTERS.  
Unusual Fire/Ex

Evaporation Hazard:USE WATER FOG/SPRAY TO COOL/LOWER  
PRESSURE OF FIRE-EXPOSED CONTAINERS, TO FLUSH VAPORS AWAY.

===== Accidental Release Measures =====

Spill Release Procedures:SMALL: MOP/RINSE AREA. LG, >55 GL: WEAR RUBBER  
BOOTS, GLOVES, APPROPRIATE PROTECTIVE CLOTHES. SHUT OFF LEAK IF  
SAFE. DIKE/CONTAIN. TRANSFER LIQ TO PLASTIC DRUMS/CONTAINERS FOR  
RECOVERY/DISPOSAL.

===== Handling and Storage =====

Handling and Storage

Precautions:KEEP AWAY FROM CHILDREN. DO NOT GET  
IN/ON EYES, SKIN, CLOTHES. DO NOT TAKE INTERNALLY.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT REQUIRED IF PROPERLY DILUTED.

Protective Gloves:RUBBER - DECREASES DRYNESS OF SKIN.

Eye Protection:CHEM SPLASH GLASSES/FACE SHIELD ADVISED\*

Other Protective Equipment:\*ESPECIALLY W/CONCENTRATE.

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

==

Boiling Pt:B.P. Text:212F,100C

Melt/Freeze Pt:M.P/F.P Text:>32F,>0C

Vapor Pres:1

Spec Gravity:1.08

pH:1-2

Evaporation Rate & Reference: