View NSN Online: https://aerobasegroup.kr/nsn/7930-01-412-1020

MAINTEX INC. -- DOUBLE DUTY (CLEANER & NEUTRALIZER) -- 7930-01-412-1020

Product ID:DOUBLE DUTY (CLEANER & NEUTRALIZER) MSDS Date:05/16/1994 FSC:7930 NIIN:01-412-1020 MSDS Number: BYZCY === Responsible Party === Company Name: MAINTEX INC. Address:13300 NELSON AVE. City:CITY OF INDUSTRY State:CA ZIP:91746 Country:US Info Phone Num:818-961-1988 **Emergency Phone Num:80** 0-255-3924 (CHEMTEL) Preparer's Name: ALI ABYANE CAGE:NO277 === Contractor Identification === **Company Name: MAINTEX INC** Address:13300 NELSON AVE Box:City:CITY OF INDUSTRY State:CA ZIP:91746 Country:US Phone:818-961-1988 CAGE:0PWJ2 Company Name: MAINTEX INC. Address:3614 EL MONTE AVE Box:City:EL MONTE State:CA ZIP:91731 Phone:213-283-7380 CAGE:NO277

Ingred Name:CITRIC ACID, CAS:77-92-9 RTECS #:GE7350000 Fraction by Wt: 1-3% Other Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES: DIRECT CONTACT W/CONCENTRATED PROD. MAY CAUSE MODERATE IRRITATION, TEARING, REDNESS. SKIN: MILD IRRITANT. REPEATED/PROLONGED CONTACT MAY IRRITATE OR DRY. INHALATION: NOT EXPECTED TO BE A PROBLEM, UNLESS CONCENTRATED PRODUCT HEATED & I

NHALED. INGESTION: MAY IRRITATE GASTROINTESTINAL TRACT, CAUSING NAUSEA/DIARRHEA. Effects of Overexposure:OVEREXPOSURE MAY RESULT IN ALLERGIC SKIN

REACTIONS. EYES: STINGING, WATERING. SKIN: IRRITATION, INFLAMMATION.

First Aid:EYES: GENTLY IRRIGATE W/LARGE AMOUNTS COOL WATER 15 MINUTES. SEEK MEDICAL ATTN. SKIN: WASH W/WATER. INHALATION: IF DISCOMFORT EXPERIENCED, REMOVE TO FRESH AIR. IF BREATHING DIFFICULT, GIVE

OXYGEN, CAL L PHYSICIAN. INGESTION: WASH MOUTH AREA. GIVE MODERATE AMOUNTS FLUID (WATER/MILK) TO DILUTE. DO NOT INDUCE VOMITING. SEEK MEDICAL ATTN.

Flash Point Method:TCC Flash Point:>212F,>100C Extinguishing Media:WATER SPRAY, FOAM, CO2, DRY CHEMICAL. Fire Fighting Procedures:FIRE FIGHTERS SHOULD WEAR POSITIVE PRESSURE SCBA W/FULL FACE PIECE. Unusual Fire/Explosion Hazard:USE WATER FOG/SPRAY TO COOL & LO WER

PRESSURE OF FIRE-EXPOSED CONTAINERS, TO FLUSH VAPORS AWAY.

Spill Release Procedures:LARGE (>55 GL): WEAR RUBBER BOOTS, GLOVES & APPROPRIATE PROTECTIVE CLOTHING. SHUT OFF LEAK SOURCE IF SAFE. DIKE/CONTAIN SPILL. SMALL: MOP & RINSE AREA.

Handling and Storage Precautions: KEEP OUT OF REACH OF CHILDREN. DO NOT GET IN EYES, ON SKIN OR CLOTHING.

DO NOT TAKE INTERNALLY. KEEP PRODUCT FROM SPLASHING INTO EYES. Other Precautions:WARNING: FLOORS MAY BE SLIPPERY. USE CARE WALKING, WORKING, STANDING IN SPILL.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:FOR MISTS/SPRAYED MATERIAL USE NIOSH APPROVED RESPIRATOR. Ventilation:IN CONFINED AREAS PROVIDE ADEQUATE LOCAL EXHAUST VENTILATION. Protective Gloves:RUBBER: DECREASES DRYNESS/IRRITATION. Eye Protection:CHEMICAL SPLASH GOGGLES. Su pplemental Safety and Health NK

Boiling Pt:B.P. Text:>212F,>100C Melt/Freeze Pt:M.P/F.P Text:>32F,>0C Vapor Pres:>17 @ 68F Vapor Density:>1 Spec Gravity:1.01 pH:3-5 Evaporation Rate & amp; Reference: