

MOBIL OIL CORP -- AVREX S TURBO 256 -- 9150-01-414-5926

===== Product Identification =====

Product ID:AVREX S TURBO 256

MSDS Date:01/01/1995

FSC:9150

NIIN:01-414-5926

MSDS Number: BZBGD

=== Responsible Party ===

Company Name:MOBIL OIL CORP

Address:3225 GALLONS ROAD

City:FAIRFAX

State:VA

ZIP:22037-0001

Country:US

Info Phone Num:800-662-4525/800-227-0707 X3265

Emergency Phone Num:609-737-4411/CHEMTR

EC 800-424-9300

Preparer's Name:EH & S DEPT

CAGE:3U728

=== Contractor Identification ===

Company Name:MOBIL OIL CORP, NORTH AMERICAS MARKETING AND REFINING

Address:3225 GALLOWS ROAD

Box:City:FAIRFAX

State:VA

ZIP:22037

Country:US

Phone:800-662-4525/ 856-224-4644

CAGE:3U728

Company Name:SALATHE OIL CO INC

Address:2226 PETERS RD

Box:City:HARVEY

State:LA

ZIP:70058

Country:US

Phone:504-366-4542

CAGE:0T5C6

===== Composition/Information on Ingredients =====

Ingred Name:HYDROCARBONS

Other REC Limits:5 MG/M3 (OIL MIST)

Ingred Name:ADDITIVES

Other REC Limits:NONE RECOMMENDED

Ingred Name:PHOSPHORIC ACID, TRIS(METHYLPHENYL) ESTER OR  
TRICRESYLPHOSPHATE

CAS:1330-78-5

RTECS #:TD0175000

Fraction by Wt: 0.5%

Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

LD50 LC50 Mixture:ORAL LD50 (RAT) IS >2000 MG/KG

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazard

s Acute and Chronic:NO SIGNIFIGANT EFFECTS EXPECTED.

Explanation of Carcinogenicity:NO INGREDIENT OF A CONCENTRATION OF 0.1%  
OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN.

Effects of Overexposure:NONE SPECIFIED BY MANUFACTURER.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:EYES-FLUSH WITH WATER. GET MEDICAL ATTENTION IF  
IRRITATIONOCCURS. SKIN-WASH WITH SOAP & WATER. INHAL  
ED-REMOVE FROM

EXPOSURE. IF SYMPTOMS OCCUR, SEEK IMMEDIATE MEDICAL ATTENTION.  
RESTORE BREATHING IF N EEEDED. INGESTED-DO NOT INDUCE VOMITING!!IF  
CONSCIOUS, GIVE 1-2 GLASSES WATER. GET MEDICAL ASSISTANCE.

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:410F,210C

Extinguishing Media:WATER FOG, CARBON DIOXIDE, DRY CHEMICAL, FOAM.  
WATER OR FOAM MAY CAUSE FROTHING.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS

AND

FULL PROTECTIVE GEAR. COOL FIRE EXPOSED CONTAINERS WITH WATER.  
PREVENT RUNOFF FROM ENTERING WATERWAYS & STREAMS.

Unusual Fire/Explosion Hazard:NEUROTOXIC FUMES MAY BE GENERATED DURING  
A FIRE. CAUTION-THERMALLY DECOMPOSED RESIDUES MAY BE NEUROTOXIC.

===== Accidental Release Measures =====

Spill Release Procedures:ABSORB WITH INERT MATERIAL AND PLACE IN A  
CONTAINER FOR LATER DISPOSAL. KEEP OUT OF WATERWAYS, DRAINS, SEWERS  
AND FROM CONTACTING SO

IL. NOTIFY USCG AT 800-424-8802 IF SPILL  
AFFECTS WATERWAYS.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE IN OPEN OR UNLABELLED  
CONTAINERS. STORE IN A COOL, DRY PLACE AWAY FROM STRONG OXIDIZING  
AGENTS AND COMBUSTIBLE MATERIAL.

Other Precautions:NONE SPECIFIED BY MANUFACTURER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED.

Ventilation:USE IN A WELL-VENTILATED AREA.

Protective Gloves:NONE NORMALLY REQUIRED.

Eye Protection:SAFETY GLASSES W/SIDE SHIELDS.

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:WASH HANDS AFTER HANDLING AND BEFORE EATING,  
DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOTHES BEFORE REUSE.

Supplemental Safety and Health

MSDS PRESENTED BY CAGE 0T5C6 FOR CONTRACT NUMBER SP0451-96-MP855.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:600F,316C

Melt/Freeze Pt:M.P/F.P Text:-80F,-62C

Vapor Pres: