

DEVOE COATINGS CO DIV OF GROW GROUP INC -- 860F0592 F-150 TYPE 4, COMPONENT A, GREEN -- 8010-01-380-2389

===== Product Identification =====

Product ID:860F0592 F-150 TYPE 4, COMPONENT A, GREEN  
MSDS Date:06/01/1995  
FSC:8010  
NIIN:01-380-2389  
Kit Part:Y  
MSDS Number: BZLPC  
=== Responsible Party ===  
Company Name:DEVOE COATINGS CO DIV OF GROW GROUP INC  
Address:4000 DUPONT CIR  
Box:7600  
City:LOUISVILLE  
S  
tate:KY  
ZIP:40207-4802  
Country:US  
Info Phone Num:502-897-9861  
Emergency Phone Num:800-424-9300  
Preparer's Name:LOUIS F. HOLZKNECHT  
CAGE:1HK86

=== Contractor Identification ===

Company Name:DEVOE COATINGS CO  
Address:4000 DUPONT CIRCLE  
Box:7600  
City:LOUISVILLE  
State:KY  
ZIP:40207-4802  
Country:US  
Phone:502-897-9861  
CAGE:1HK86

===== Composition/Information on Ingredients =====

Ingred Name:IRON OXIDE  
CAS:51274-00-1  
Fraction by Wt: 15 MIN. GET MED AID. SKIN:  
WASH W/SOAP & WATER.

REMOVE CONTAM CLOTHES. GET MED AID IF IRRIT PERSISTS. INGESTION: CALL DR. IMMED. DON'T INDUCE VOMITING. CHEM PNEUMONITIS W/ASPIRATION OF VOMITUS, POSSIBLY FATAL. INHAL: GET FRESH AIR IF TROUBLE BREATHING. IF CONTINUED TROUBLE BREATHING GET IMMED MED AID. BREATHING STOPPED, RESTORE BREATHING W/CPR. GET IMMED MED AID.

===== Fire Fighting Measures =====

Flash Point:99.0F,37.2C

Lower Limits:1.4

Extinguishing Media:CO2, DRY CHEMICAL, FOAM (CLASS B FIRE).

Fire Fighting Procedures:FULL PROTECT EQUIP W/SCBA. WATER SPRAY MAY BE INEFFECTIVE, FOG NOZZLES PREFERRED. COOL FIRE-HEAT EXPOSED CONTAINERS. PREVENT PRESSURE BUILD-UP/AUTOIGNITION.

Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED. KEEP FROM HEAT/ELECTRICAL EQUIP/SPARKS/FLAME. CLOSED CONTAINERS MAY EXPLODE IN EXTREME HEAT. DON'T CUT/WELD ON/NEAR CONTAINER AS MAY IGNITE.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ILLUSTRATED SOURCES. AVOID BREATHING VAPORS.

VENTILATE AREA. BEFORE CLEAN-UP REFER TO HAZ CAUTION INFO. CONTAIN SPILL/REMOVE W/INERT ABSORBENT/NONSPARKING TOOLS. STORE IN CLOSED CONTAINER UNTIL PROPERLY DISPOSED OF.

===== Handling and Storage =====

Handling and Storage Precautions:ISOLATE FROM HEAT/SPARKS/FLAMES. DON'T SMOKE. PREVENT VAPOR BUILD-UP W/CONTINUOUS FLOW FRESH AIR. DON'T STORE >120F, NEAR FIRE/OPEN FLAME. STORE LG\*

Other Precautions:

AMTS IN BUILDINGS TO COMPLY W/OSHA 1910.106. KEEP CONTAINER CLOSED WHEN NOT USING. DON'T TRANSFER TO BOTTLES/UNLABELED CONTAINERS. DON'T REUSE EMPTY CONTAINERS. IF MATERIAL PART OF 2 COMPONENT PRODUCT, MIXTURE WILL HAVE HAZARDS OF BOTH COMPONENTS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:DON'T BREATHE VAPORS/SPRAY MIST/SANDING DUST.NIOSH/MSHA APPROVED MECHANICAL FILTER RESPIRATOR IN RESTRICTED VENTILATION, NIOSH/MSHA APPROVED CHEM/MECHANICAL FILTER F

OR

PARTICULATES/VAPOR.CONFINED AREAS, NIOS H/MSHA APPROVED AIR-SUPPLY  
RESPRTR/HOODS

Ventilation:GEN DILUTION/LOCAL EXHAUST VENT. TO KEEP AIR CONTAM CONC