

DEVOE COATINGS CO DIV OF GROW GROUP INC -- #138C0922 HEAVY DUTY EPOXY CLEAR CONVERTER -- 8010-01-397-3804

===== Product Identification =====

Product ID:#138C0922 HEAVY DUTY EPOXY CLEAR CONVERTER

MSDS Date:07/28/1995

FSC:8010

NIIN:01-397-3804

Kit Part:Y

MSDS Number: BZLRN

=== Responsible Party ===

Company Name:DEVOE COATINGS CO DIV OF GROW GROUP INC

Address:4000 DUPONT CIR

Box:7600

City:LOUISVILLE

State:KY

ZIP:40207-4802

Country:US

Info Phone Num:502-897-9861

Emergency Phone Num:800-424-9300

Preparer's Name:LOUIS F. HOLZKNECHT

CAGE:1HK86

=== Contractor Identification ===

Company Name:DEVOE COATINGS CO

Address:4000 DUPONT CIRCLE

Box:7600

City:LOUISVILLE

State:KY

ZIP:40207-4802

Country:US

Phone:502-897-9861

CAGE:1HK86

===== Composition/Information on Ingredients =====

Ingred Name:ALIPHATIC AMINE ADDUCT (SARA 313) (LD50 ORAL RAT >1600  
MG/KG)

Fraction by Wt: 30.0%

Oth

er REC Limits:NONE RECOMMENDED

OSHA PEL:5 PPM (SKIN)

ACGIH TLV:5 PPM (SKIN)

Ingred Name:AMINE COMPOUND (LD50 ORAL RAT 5 MG/KG)

Fraction by Wt: 50.0%

Other REC Limits:NONE RECOMMENDED

Ingred Name:AMORPHOUS SILICA

CAS:63231-67-4

RTECS #:VV7322000

Fraction by Wt: 5.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:15 MG/M3 TOTAL DUST

ACGIH TLV:NOT EST.

Ingred Name:HIGH FLASH AROMATIC NAPHTHA (VP = 10)(LD50 >5 GM/KG ORAL  
RAT, LC50 RAT 8 HRS >3670 PPM)

CAS:64742-95-6

Fraction by Wt: 10.0%

Other RE

C Limits:NONE RECOMMENDED

OSHA PEL:NOT EST.

ACGIH TLV:100 PPM

Ingred Name:METHYL ALCOHOL (METHANOL) (SARA 313) (CERCLA)(VP =  
100)(LD50 ORAL RAT 7.5 GM/KG, LC50 64000 PPM RAT 4 HRS)

CAS:67-56-1

RTECS #:PC1400000

Fraction by Wt: 15 MIN. GET MED AID. SKIN:

WASH W/SOAP & WATER. REMOVE CONTAM CLOTHES. GET MED AID IF IRRIT  
PERSISTS. INGESTION: CALL DR. IMMEDIATE. DON'T INDUCE VOMITING. CHEM  
PNEUMONITIS W/ASPIRATION OF VOMITUS, POSSIBLY FATAL. INHAL: GET  
FRESH AIR IF TROUBLE BREATHING

. IF CONTINUED TROUBLE BREATHING GET

IMMEDIATE MED AID. BREATHING STOPPED, RESTORE BREATHING W/CPR. GET  
IMMEDIATE MED AID.

=====  
===== Fire Fighting Measures =====

Flash Point:132F,56C

Lower Limits:1.0

Extinguishing Media:CO2, DRY CHEMICAL, FOAM (CLASS B FIRE).

Fire Fighting Procedures:FULL PROTEC EQUIP W/SCBA. WATER SPRAY MAY BE  
INEFFECTIVE, FOG NOZZLES PREFERRED. COOL FIRE-HEAT EXPOSED CLSD  
CNTNRS. PREVENT PRESSURE BUILD-UP/AUTOIGNITION.

Unusual Fire/Explo

sion Hazard:KEEP CNTNRS TIGHTLY CLSD. KEEP FROM HEAT/ELECTRICAL EQUIP/SPARKS/FLAME. CLSD CNTNRS MAY EXPLODE IN EXTREME HEAT. DON'T CUT/WELD ON/NEAR CNTNR AS MAY IGNITE.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNIT SOURCES. AVOID BREATHING VAPORS. VENTILATE AREA. BEFORE CLEAN-UP REFER TO HAZ CAUTION INFO. CONTAIN SPILL/REMOVE W/INERT ABSORBENT/NONSPARKING TOOLS. STORE IN CLOSED CONTAINER UNTIL PROPE RLY DISPOSED OF

===== Handling and Storage =====

Handling and Storage Precautions:ISOLATE FROM HEAT/SPARKS/FLAMES. DON'T SMOKE. PREVENT VAPOR BUILD-UP W/CONTINUOUS FLOW FRESH AIR. DON'T STORE >120F, NEAR FIRE/OPEN FLAME. STORE LG\*

Other Precautions:AMTS IN BUILDINGS TO COMPLY W/OSHA 1910.106. KEEP CNTNR CLSD WHEN NOT USING. DON'T TRANSFER TO BOTTLES/UNLABELED CNTNRS. DON'T REUSE EMPTY CNTNRS. IF MAT'L PART OF 2 COMPONENT PROD, MIXTURE WILL HAVE HAZARDS OF BOTH COMPONENTS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:DON'T BREATHE VAPORS/SPRAY MIST/SANDING DUST.NIOSH/MSHA APPROVED MECHANCL FILTER RESPRTR.IN RESTRICTED VENTILATION, NIOSH/MSHA APPROVED CHEM/MECHANCL FILTER FOR PARTICULATES/VAPOR.CONFINED AREAS, NIOS H/MSHA APPROVED AIR-SUPPLY RESPRTR/HOODS

Ventilation:GEN DILUTION/LOCAL EXHAUST VENT. TO KEEP AIR CONTAM CONC