

3M -- STELLAR BRAND ULTRA HIGH SPEED FLOOR FINISH 6

=====

MSDS Safety Information

=====

FSC: 7930
NIIN: 01-418-1182
MSDS Date: 02/14/1992
MSDS Num: BZLVB
Product ID: STELLAR BRAND ULTRA HIGH SPEED FLOOR FINISH 61-5000-3752-0
MFN: 01
Responsible Party
Cage: 0F0U5
Name: 3M
Address: 3M CENTER
City: ST. PAUL M
N 55144-1000
Info Phone Number: 612-733-1110
Emergency Phone Number: 612-733-1110
Review Ind: Y
Published: Y

=====

Contractor Summary

=====

Cage: 0WJ98
Name: MINNESOTA MINING AND MFG CO INFUSION THERAPY DIV
Address: 3M CTR
City: SAINT PAUL MN 55144-1000
Phone: 800-237-8033
Cage: 0F0U5
Name: PACEBROOK LTD
Address: 15 GOSDITCH ST
City: CIRENCESTER GLOS GL7 2AG NK 00000
Country: UK
Phone: NONE

=====

=====

Item Description Information

=====

Item Manager: GSA
Item Name: FINISH,FLOOR,NONBUFFING
Unit of Issue: BX
Quantitative Expression: 00000000002EA
UI Container Qty: 1

=====

Ingredients

=====

Cas: 7732-18-5
RTECS #: ZC0110000
Name: WATER
% Wt: 75-85
Other REC Limits: NONE RECOMMENDED
OSHA PEL: NOT E

STABLISHED
ACGIH TLV: NOT ESTABLISHED

Name: MODIFIED ACRYLIC POLYMER
% Wt: 12-16
Other REC Limits: NONE RECOMMENDED
OSHA PEL: NOT ESTABLISHED
ACGIH TLV: NOT ESTABLISHED

Cas: 111-77-3
RTECS #: KL6125000
Name: DIETHYLENE GLYCOL MONOMETHYL ETHER
% Wt: 2-3
Other REC Limits: NONE RECOMMENDED
OSHA PEL: NOT ESTABLISHED
ACGIH TLV: 30 PPM

Cas: 9010-77-9
Name: ETHYLENE-ACRYLIC ACID POLYMER
% Wt: 1-3
Other REC Limit
s: NONE RECOMMENDED
OSHA PEL: NOT ESTABLISHED
ACGIH TLV: 30 PPM

Cas: 68441-17-8
Name: OXIDIZED POLYETHYLENE
% Wt: 1-3
Other REC Limits: NONE RECOMMENDED
OSHA PEL: NOT ESTABLISHED
ACGIH TLV: NOT ESTABLISHED

Cas: 78-51-3
RTECS #: KJ9800000
Name: TRIBUTOXYETHYL PHOSPHATE
% Wt: 1-3
Other REC Limits: NONE RECOMMENDED
OSHA PEL: NOT ESTABLISHED
ACGIH TLV: NOT ESTABLISHED

Cas: 84-74-2
RTECS #: TI0875000
Name: DI

BUTYL PHTHALATE (SARA 313) (CERCLA)
% Wt: 1-2
Other REC Limits: NONE RECOMMENDED
OSHA PEL: 5 MG/M3
ACGIH TLV: 5 MG/M3
EPA Rpt Qty: 10 LBS
DOT Rpt Qty: 10 LBS

Health Hazards Data

Route Of Entry Inds - Inhalation: YES
Skin: YES
Ingestion: YES
Carcinogenicity Inds - NTP: NO
IARC: NO
OSHA: NO
Effects of Exposure: EYES: MINIMAL IRRIT FROM LIQ BASED ON ANIMAL STUDIES.
SKIN: NOT IRRIT BASE
D ON ANIMAL STUDIES. INHAL: CHRONIC EXPOSURE TO VAPORS IN
POORLY VENTILATED AREAS MAY IRRIT RESP SYSTEM, GIVE SYMPTOMS OF HEAD
ACHE/NAUSEA. INGEST: LIQ MAY IRRIT DIGESTIVE SYSTEM. FOUND TO BE PRACTICALLY
NON-TOXIC BASED ON ANIMAL STUDIES.
Signs And Symptions Of Overexposure: HEADACHE/NAUSEA FROM OVEREXPOSURE.
First Aid: EYES: IMMEDIATELY FLUSH W/WATER 10 MINUTES HOLDING LIDS OPEN. CALL
DR. SKIN: WASH AFFECTED AREA W/SOAP & WATER. INHALATION: REMOVE PERSON TO
FRESH AIR. INGESTION: D
O NOT INDUCE VOMITING. IMMEDIATELY C ALL DR.

Handling and Disposal

Spill Release Procedures: OBSERVE PRECAUTIONS FROM OTHER SECTIONS. FLUSH SPILLS
<5 GL TO WASTE WATER TREATMENT SYSTEM. IF BULK QUANTITY SPILL, COLLECT
MATERIAL USING ABSORBENT MAT'L AS NECESSARY & FLUSH RESIDUE TO WASTE
WATER TREATMENT SYSTEM. CLEAN UP RESIDUE W/WATER.
Waste Disposal Methods: FLUSH SPENT P
RODUCT/SOLUTIONS TO WASTE WATER TREATMENT
SYSTEM. IF FOAMING REDUCE DISCHARGE RATE. MIX ABSORBED/BULK & INCINERATE
IN INDUSTRIAL/COMMERCIAL/MUNICIPAL FACILITY. EMPTY CNTNR MAY BE SANITARY
LANDFILLED. CONSULT APPLIC REGS BEFORE DISPOSAL.
Handling And Storage Precautions: AVOID CONTACT W/EYES. USE IN VENTILATED AREA.
KEEP CONTAINER CLOSED WHEN NOT IN USE. KEEP AWAY FROM CHILDREN.

Fire and Explosion Hazard Information

Flash Point Text: NA
Lower Limits: NA
Upper Limits: NA
Extinguishing Media: WATER, CO2, FOAM, DRY CHEMICAL.
Fire Fighting Procedures: NONE
Unusual Fire/Explosion Hazard: NONE

Control Measures

Physical/Chemical Properties

B.P. Text
: 212F,100C
M.P/F.P Text: NOT EST.
Vapor Pres: NOT EST.
Vapor Density: NOT EST.
Spec Gravity: 1.0 (WATER=1)
PH: 8.50
Evaporation Rate & Reference: NOT EST.
Solubility in Water: COMPLETE
Appearance and Odor: LIQUID, OPAQUE WHITE
Percent Volatiles by Volume: 80.0

Reactivity Data

Stability Indicator: YES
Hazardous Decomposition Products: CO, CO2, SMOKE PARTICLES.
Hazardous Polymerization Indicator: YES

Toxicological Information

Ecological Information

MSDS Transport Information

Regulator

y Information
=====

Other Information
=====

Transportation Information
=====

Responsible Party Cage: 0F0U5
Trans ID NO: 135321
Product ID: STELLAR BRAND ULTRA HIGH SPEED FLOOR FINISH 61-5000-3752-0
MSDS Prepared Date: 02/14/1992
Review
 Date: 05/17/1996
MFN: 1
Multiple KIT Number: 0
Review IND: Y
Unit Of Issue: BX
Container QTY: 1

Detail DOT Information
=====

DOT PSN Code: ZZZ
DOT Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

Detail IMO Information
=====

IMO PSN Code: ZZZ
IMO Proper Shipping Name
: NOT REGULATED FOR THIS MODE OF TRANSPORTATION

Detail IATA Information
=====

IATA PSN Code: ZZZ
IATA Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

Detail AFI Information
=====

AFI PSN Code: ZZZ
AFI Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

=====

HAZCOM Label

=====

Product ID: STELLAR BRAND ULTRA HIGH SPEED FLOOR FINISH 61-5000-3752-0

Cage: 0F0U5

Company Name: PACEBROOK LTD

Street: 15 GOSDITCH ST

City: CIRENCESTER GLOS GL7 2AG NK

Zipcode: 00000

Country: UK

Health Emergency Phone: 612-733-1110

Label Required IND: Y

Date Of Label Review: 12/16/1998

Status Code: C

Label Date: 12/16/1998

Origination Code: G

Hazard And Precautions: EYES

: MINIMAL IRRIT FROM LIQ BASED ON ANIMAL STUDIES.

SKIN: NOT IRRIT BASED ON ANIMAL STUDIES. INHAL: CHRONIC EXPOSURE TO VAPORS IN POORLY VENTILATED AREAS MAY IRRIT RESP SYSTEM, GIVE SYMPTOMS OF HEAD ACHE/NAUSEA. INGEST: LIQ MAY IRRIT DIGESTIVE SYSTEM. FOUND TO BE PRACTICALLY NON-TOXIC BASED ON ANIMAL STUDIES. HEADACHE/NAUSEA FROM OVEREXPOSURE.

=====

Disclaimer (provided with this information by the compiling agencies): This informati

on is formulated for use by elements of the Department of Defense.

The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a milita

ry or civilian employee of the

United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.