View NSN Online: https://aerobasegroup.kr/nsn/6840-00-116-9364

PENETONE CORP SUB OF WEST CHEMICAL PRODUCTS INC -- PC-6 -- 6840-00-116-9364

======== Product Identification ============

Product ID:PC-6

MSDS Date:01/06/1994

FSC:6840

NIIN:00-116-9364

MSDS Number: BZPDS === Responsible Party ===

Company Name: PENETONE CORP SUB OF WEST CHEMICAL PRODUCTS INC

Address:74 HUDSON AVENUE

City:TONAFLY

State:NJ

ZIP:07670-1017 Country:US

Info Phone Num:201-567-3000

Emergency Phone Num

:201-567-3000/800-424-9300(CHEMTREC)

CAGE:56883

=== Contractor Identification ===
Company Name:PENETONE CORP

Address:74 HUDSON AVE

Box:City:TENAFLY

State:NJ ZIP:07670 Country:US

Phone:201-567-3000

CAGE:56883

====== Composition/Information on Ingredients ========

Ingred Name: HEXYLENE GLYCOL

CAS:107-41-5

RTECS #:SA0810000

Other REC Limits: NONE RECOMMENDED

OSHA PEL:C 25 PPM

ACGIH TLV:C 25 PPM; 9596

Ingred Name:ISOPROPYL ALCOHOL (SARA 313)

CAS:67-63-0

RTECS #:NT8050000

Other REC Lim

its:NONE RECOMMENDED OSHA PEL:400 PPM ACGIH TLV:400 PPM/500STEL;9596

Ingred Name:WATER CAS:7732-18-5

RTECS #:ZC0110000

Other REC Limits: NONE RECOMMENDED

Ingred Name: TETRAPOTASSIUM PYROPHOSPHATE

CAS:7320-34-5 RTECS #:JL6735000

Other REC Limits: NONE RECOMMENDED

Ingred Name: O-BENZYL-P-CHLOROPHENOL; (POTASSIUM

O-BENZYL-P-CHLOROPHENOLALE)

CAS:120-32-1

RTECS #:GO7175000

Other REC Limits: NONE RECOMMENDED

Ingred Name: POTASSIUM DODECYLBENZENE SULFONATE

CAS:27177-77-1 RTECS #:DB6820000

Other REC L

imits:NONE RECOMMENDED

========== Hazards Identification ================

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYE:IRRIT ON CONTACT ONLY.

SKIN:FREQ/PROL CONTACT MAY IRRIT OR DRY SKIN, CAUSE DERM. INHAL:HIGH VAP/AEROSOL CONCEN(>TLV)IRRIT TO RESP TRACT, MAY CAUSE

HEAD, DIZZ, ANESTHESIA, DROWS, UNCONSC, OTHER CNS EFFECT S

. INGEST:MAY

CAUSE IRRIT TO DIGESTIVE TRACT, DIARRHEA.

Effects of Overexposure:EYE IRRIT. SKIN IRRIT, DRY SKIN, DERMATITIS.
RESPIRATORY TRACT IRRIT, HEADACHES, DIZZINESS, ANESTHESIA,
DROWSINESS, UNCONSCIOUSNESS, OTHER CNS EFFECTS. IRRIT DIGESTIVE
TRACT, DIARRHEA.

Medical Cond Aggravated by Exposure: SKIN CONTACT MAY AGGRAVATE AN EXISTING DERMATITIS CONDITION.

First Aid:EYE:FLUSH W/LG AMTS OF WATER.SEE PHYSIC

IAN IMMED. SKIN:FLUSH W/LG ATMS OF WATER.REMOVE CONTAMIN CLOTH.IRRIT DEVELOPS/PERSISTS CONSULT PHYSICIAN. INHAL: REMOVE TO FRESH AIR. ADMINISTER OXY OR ARTIFICIAL RESPIRATION AS NEEDED. CALL PHYSICIAN IMMED. INGEST: GIVE PLENTY OF WATER OR MILK.CALL PHYSICIAN IMMED. Flash Point Method:TCC Flash Point: 105F,41C Autoignition Temp: Autoignition Temp Text: ND Lower Limits:ND **Upper Limits:ND** Extinguishing Media:WATER, FOA M, DRY CHEMMICAL. Fire Fighting Procedures: EITHER ALLOW FIRE TO BURN OUT UNDER CONTROLLED CONDITIONS OR EXTINGUISH W/WATER, FOAM, DRY CHEMICAL. COOL EXPO CNTNR W/WATER SPRAY. Unusual Fire/Explosion Hazard:FLAMM LIQ.CAN FORM FLAMM MIXTURES @/>FLASH PT.CNTNR CAN RUPTURE & EXPLO UNDER FIRE CONDITIONS DUE TO PRESSURE & VAP BUILDUP. ======== Accidental Release Measures ============ Spill Release Procedures:LAND:USE ABSORBENT AMTL(TOWELS, ABSORBENT POWDERS).PUT ALL MATL INTO PROPER WASTE DISPO CNTN W/LID TIGHTLY COVER.DIKE LG SPILLS, RECOVER, USE ABSORBENT MATL TO DRY.RINSE W/WATER.WATER:WATER BASED/DILUTAB LE.SURFACTNATS BIODEGRADABLE.LOC HI CONCEN (SUPPL) Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER. ============= Handling and Storage ========================== >120F.KEEP FROM FREEZING.DO NOT STORE NEAR STRONG ACIDS.

Handling and Storage Precautions: STORAGE TEMP: AMBIENT. DO NOT STORE

Other Precautions: NONE SPECIFIED BY MANUFACTU RER.

====== Exposure Controls/Personal Protection ========

Respiratory Protection: AN ORGANIC VAPOR MASK SHOULD BE USED IF TLV IS EXCEEDED & PARTICLE MASK IF PRODUCT IS SPRAYED.

Ventilation: NONE NEEDED UNDER NORMAL USE CONDITIONS. ENCLSD AREA/LG AMTS BEING USED USE FANS/MECHANICAL VENTILATION.

Protective Gloves: RUBBER GLOVES.

Eve Protection: SAF GLASSES FOR ALL WORKPLACE CONDITIONS

Other Protective Equipment: WHEN SPRAYING PROD SPLASH PROOF GOGG, RUBB BOOTS, APRONS, GAUNTLET

S,RAIN GEAR SHOULD BE WORN DEPENDING ON OPERATIONS.
Work Hygienic Practices:LAUNDER CONTAMIN CLOTH BEF REUSE.
Supplemental Safety and Health SPILL:MAY CAUSE FISH KILLS BUT NO PERSISTANT/LONG TERM EFFECTS
RESULT.CHECK W/LOC ENVIRO REG AGENCIES FOR REPORTING REQMTS.
========= Physical/Chemical Properties ==========
HCC:F6 Boiling Pt:B.P. Text:212F,100C Melt/Freeze Pt:M.P/F.P Text:NP Decomp Temp:Decomp Text:NP Vapor Pres:=WATER
Vapor Density:=WATER Spec Gravity:1.06 @75 F
pH:10-11 Viscosity:NP
Evaporation Rate & Evaporation R
Appearance and Odor:CLEAR BROWN LIQUID WITH PERFUME ODOR. Percent Volatiles by Volume:4 Corrosion Rate:NP
========= Stability and Reactivity Data ==========
Stability Indicator/Materials to Avoid:YES STRONG ACIDS.
Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.
Hazardous Decomposition Products:SMOKE, FUMES, & OXIDES OF CARBON & NITROGEN.
===== Disposal Considerations ============
·
Waste Disposal Methods:RCRA HAZ CLASS:D001,IGN WASTE.PROD CONTAINS NO REPORTABLE CERCLA MATLS.CONTACT LOCAL AUTHORITIES TO DETERMINE II THERE MAY BE OTHER LOC REPORTING REQMTS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to

be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.