View NSN Online: https://aerobasegroup.kr/nsn/3439-00-238-5667

Product ID:8N12 MISCELLANEOUS ARCALOY HIGH ALLOY COVERED ELECTRODES MSDS Date:02/15/1988 FSC:3439 NIIN:00-238-5667 MSDS Number: BZPFS === Responsible Party === Company Name: ALLOY RODS CORPORATION Address:WILSON AVENUE Box:517 **City:HANOVER** State:PA ZIP:17331 Coun try:US Info Phone Num:717-637-8911 Emergency Phone Num:717-637-8911 CAGE:84021 === Contractor Identification === Company Name: ESAB GROUP INC Address:801 WILSON AVENUE Box:517 City:HANOVER State:PA ZIP:17331 Country:US Phone:717-637-8911 OR 800-933-7070 CAGE:84021

Ingred Name:TITANIUM CAS:7440-32-6 RTECS #:XR1700000 Other REC Limits:NONE RECOMMENDED

Ingred Name:NIOBIUM (ALSO CALLED COLUMBIUM) CAS:7440-03-1 Other REC Limits:NO

NE RECOMMENDED

Ingred Name:FELDSPAR; (POTASSIUM FELDSPAR) CAS:68476-25-5 Other REC Limits:NONE RECOMMENDED

Ingred Name:SODIUM METASILICATE CAS:6834-92-0 RTECS #:VV9275000 Other REC Limits:NONE RECOMMENDED

Ingred Name:POTASSIUM TITANATE CAS:12030-97-6 Other REC Limits:NONE RECOMMENDED

Ingred Name:IRON CAS:7439-89-6 RTECS #:NO4565500 Other REC Limits:NONE RECOMMENDED

Ingred Name:CALCIUM CARBONATE (MARBLE) (LIMESTONE) CAS:1317-65-3 RTECS #:EV9580000 Other REC Limits:NONE RECOMMENDED OSHA PEL:1 5 MG/M3 TDUST ACGIH TLV:10 MG/M3 TDUST; 9596

Ingred Name:CRYOLITE (SODIUM ALUMINUM FLUORIDE) CAS:15096-52-3 RTECS #:WA9625000 Other REC Limits:NONE RECOMMENDED

Ingred Name:TITANIUM DIOXIDE CAS:13463-67-7 RTECS #:XR2275000 Other REC Limits:NONE RECOMMENDED OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3 TDUST; 9596

Ingred Name:SODIUM TITANATE CAS:12034-34-3 Other REC Limits:NONE RECOMMENDED

LD50 LC50 Mixture:WELDING FUME 5MG/M3

(ACGIH). Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES Health Hazards Acute and Chronic: FUMES/GASES CAN BE DANGEROUS TO HEALTH.ARC RAYS CAN INJURE EYES/BURN SKIN.ELECTRIC SHOCK CAN KILL.ACUTE OVEREXPO TO WELDING FUMES:DISCOMFORT,DIZZ,NAU,DRYNESS,IRRIT OF NOSE/THROAT/EYES.CHRONIC OVEREXPO MAY LEAD TO SIDEROSIS(IRON DEPOSITS INLUNT), BELIEVED BY SOME INVETIGATORS TO AFFECT PULM FUNCTION. Explanation of Carcinoge nicity:PER MSDS:CARCINOGENICITY:NTP-NI,CR. IARC-NI, CR. OSHA-CR. (IF INGREDS CONTAIN THESE MATLS). Effects of Overexposure: INJURY TO EYES, BURN TO SKIN. DEATH FROM ELECTRIC SHOCK. DISCOMFORT, DIZZINESS, NAUSEA, DRYNESS, IRRITATION OF NOSE/THROAT/EYES. SIDEROSIS. Medical Cond Aggravated by Exposure: AGGRAVATION OF PRE-EXISTING RESPIRATORY OR ALLERGIC CONDITIONS MAY OCCUR IN SOME WORKERS. First Aid:CALL FOR MEDICA L AID. EMPLOY FIRST AID TECHNIQUES RECOMMENDED BY THE AMERICAN RED CROSS. Flash Point:NP Autoignition Temp:Autoignition Temp Text:NP Lower Limits:NP Upper Limits:NP Extinguishing Media:NON-FLAMMABLE. Fire Fighting Procedures:NONE SPECIFIED BY MANUFACTURER. Unusual Fire/Explosion Hazard:WELDING ARC & SPARKS CAN IGNITE COMBUSTIBLES. SEE Z-49.1 Handlin g and Storage Precautions: MONITOR FUMES OF CR VI/NI/CU WHEN PRESENT IN INGRED.READ/UNDERSTAND MFG INSTRUCTIONS/PRECAUT LABEL ON PROD.REF:Z-49.1/OSHA 29CFR1910. Other Precautions: ONE RECOMMENDED WAY TO DETERMINE COMP/QUANT OF FUMES/GASES WORKERS EXPO:TAKE AIR SMPL INSIDE WELDER'S

HELMET/BREATH ZONE.SEE ANSI/AWS F1.1 FROM AMER WELDER'S SOC,POB351040,MIA,FL33135.TRAIN WELDER NOT TOU CH LIVE ELECT PARTS/INSULATE FRM WORK/GR

======= Exposure Controls/Personal Protection =

Respiratory Protection: USE RESPIRABLE FUME RESPIRATOR OR AIR SUPPLIED RESPIRATOR WHEN WELDING IN CONFINED SPACE OR WHERE LOCAL EXHASUT OR VNETILATION DOES NOT KEEP EXPOSURE BELOW TLV. Ventilation: USE ENOUGH VENT/LOC EXHA @ARC/BOTH TO KEEP FUME/GAS BEL TLV IN WORKER BREATH ZONE/GEN AREA.TRAIN WELD KEEP HEAD OUT FUME Protective Gloves:WELDERS GLOVES Eye Protection: FCSHIELD W/FILT LEN, FLASH/SCREEN GOGG. Other Protective Equipment: WEAR HELMET/HEAD/HAND/BODY PROT FRM RAD IATION/SPARKS/ELECT SHOCK.ARM/SHOULD PROT, APRONS, HATS, DARK SUBSTANTIAL CLOTH. Work Hygienic Practices: NONE SPECIFIED BY MANUFACTURER. Supplemental Safety and Health DECOMPO: USED, COAT ON METAL, #OF WELDERS/VOL IN WORKAREA, QUAL/AMT OF VENTI, POSITION FO WLEDER HEAD W/RESPECT TO FUME PLUME, PRESENCE OF CONTAMIN IN ATM.ELECTRODE CONSUMED FUNE/GAS DECOMPO PROD DIFFERENT IN %/FORM FROM INGREDS.REASONABLY EXPECT:FLUORIDES,COMPLEX OXIDES OF METALS IN PRODUCT, CO/CO2, OZONE, NITROGEN OXIDE S.

HCC:N1 Boiling Pt:B.P. Text:NP Melt/Freeze Pt:M.P/F.P Text:NP Decomp Temp:Decomp Text:NP Vapor Pres:NP Vapor Density:NP Spec Gravity:NP pH:NP Viscosity:NP Evaporation Rate & amp; Reference:NP Solubility in Water:NP Appearance and Odor:NP Percent Volatiles by Volume:NP Corrosion Rate:NP

NONE SPECIFIED BY MANUFACTURER. Stability Condition to Avoid:NONE SPEC

IFIED BY MANUFACTURER. Hazardous Decomposition Products:WELDING FUMES CAN'T BE CLASSIFIED SIMPLY.COPO/QUANT DEPENDENT UPON METAL BEING WELDED/PROCESS/PROCEDURES/ELECTRODES(SUP)

Waste Disposal Methods:PREVENT WASTE FROM CONTAMINATING SURROUNDING ENVIRO.DISCARD ANY PRODUCT RESIDUE/DISPOSABLE CNTNR/LINER IN ENVIRO ACCEPTABLE MANNER IN FULL COMPLIANCE W/FED/STATE/LOC REGULATIONS.

Disclaimer (provided with this in

formation by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.