

CASTROL INDUSTRIAL INC. -- STICK WAX -- 9160-00-868-4003

===== Product Identification =====

Product ID:STICK WAX

MSDS Date:08/30/1993

FSC:9160

NIIN:00-868-4003

MSDS Number: BZPHS

=== Responsible Party ===

Company Name:CASTROL INDUSTRIAL INC.

Address:1001 WEST 31ST STREET

City:DOWNERS GROVE

State:IL

ZIP:60515-1280

Country:US

Info Phone Num:708-241-4000

Emergency Phone Num:708-241-4000

Preparer's N

ame:DAVE BELL

CAGE:CASTI

=== Contractor Identification ===

Company Name:AV DISTRIBUTING CO INC

Address:3277 SAWTOOTH CT

Box:City:THOUSAND OAKS

State:CA

ZIP:91362

Country:US

Phone:818-204-3890

CAGE:03BK1

Company Name:CASTROL INDUSTRIAL INC

Address:1001 W 31ST

City:DOWNERS GROVE

State:IL

ZIP:60515-1280

Country:US

Phone:708-241-4000

CAGE:CASTI

===== Composition/Information on Ingredients =====

Ingred Name:NON-HAZARDOUS INGREDIENTS

Fraction by Wt: 100%

Other REC Limits:NONE RECOM

MENDED

=====  
===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL, RAT) IS NOT KNOWN.  
Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:TARGET ORGANS:EYE, SKIN, RESPIRATORY &  
GI TRACTS. ACUTE- VAPORS OF MOLTEN WAX MAY CAUSE IRRITATION OF EYES  
& RESPIRATORY TRACT. CONTACT WITH MOLTEN MATERIAL CAN CAUSE THERMAL  
BURNS. MAY CAUSE GASTROIN TESTINAL IRRITATION I  
F INGESTED. CHRONIC-  
NONE.  
Explanation of Carcinogenicity:NONE  
Effects of Overexposure:IRRITATION

=====  
===== First Aid Measures =====

First Aid:GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. SKIN:REMOVE  
CONTAMINATED CLOTHING. WASH SKIN WITH SOAP & WATER. EYE:FLUSH WITH  
WATER FOR 15 MINUTES. HOLD EYELIDS OPEN. INHALED:REMOVE TO FRESH  
AIR. PROVIDE OXYGEN/CPR IF NEEDED. ORAL:IF CONSCIOUS, INDUCE  
VOMITING IMMEDIATELY AS DIRECTED BY MEDICAL PERSONNE  
L. CALL A  
PHYSICIAN/POISON CONTROL CENTER IMMEDIATELY. NEVER GIVE ANYTHING TO  
AN UNCONSCIOUS PERSON.

=====  
===== Fire Fighting Measures =====

Flash Point Method:COC  
Flash Point:470F,243C  
Extinguishing Media:USE CARBON DIOXIDE, DRY CHEMICAL, FOAM, SAND. WATER  
OR FOAM MAY CAUSE FROTHING.  
Fire Fighting Procedures:WEAR PROTECTIVE CLOTHING AND NIOSH-APPROVED  
SELF-CONTAINED BREATHING APPARATUS. COOL FIRE-EXPOSED CONTAINERS  
WITH WATER SPRAY.  
Unusual Fir  
e/Explosion Hazard:NONE

=====  
===== Accidental Release Measures =====

Spill Release Procedures:SWEEP UP AND PLACE IN SUITABLE CONTAINER FOR  
DISPOSAL. ABSORB MOLTEN PRODUCT WITH SAND. AVOID CONTACT WITH  
MOLTEN PRODUCT.  
Neutralizing Agent:NOT RELEVANT

=====  
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, DRY PLACE AWAY FROM  
HEAT AND STRONG OXIDIZING AGENTS. KEEP OUT OF REACH OF SMALL  
CHILDREN.

O

ther Precautions:WASH THOROUGHLY AFTER HANDLING. DO NOT GET IN EYES.  
DO NOT INHALE FUMES. DO NOT INGEST.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED. FOR FUMES FROM MOLTEN PRODUCTS, WEAR NIOSH-APPROVED RESPIRATOR.  
Ventilation:NONE NORMALLY REQUIRED. LOCAL EXHAUST FOR MOLTEN PRODUCTS  
Protective Gloves:HEAT RESISTANT FOR MOLTEN PRODUCTS  
Eye Protection:SAFETY GLASSES/GOGGLES FOR HOT PRODUCTS  
Other Protective Equipment:S  
AFETY SHOWER AND EYE WASH FOUNTAIN SHOULD BE LOCATED NEARBY.  
Work Hygienic Practices:OBSERVE GOOD INDUSTRIAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. WASH THOROUGHLY BEFORE EATING, DRINKING/SMOKING.  
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:N1  
NRC/State Lic Num:NOT RELEVANT  
Boiling Pt:B.P. Text:480F,249C  
Melt/Freeze Pt:M.P/F.P Text:150F,66C  
Spec Gravity:0.90  
Viscosity:NOT RELEVANT  
Evaporation Rate & Reference: