

EASTMAN KODAK COMPANY -- KODAK RAPID FIXER, CAT# 146 4114, TO MAKE 5 GAL, PART B --
6525-00-935-4105

===== Product Identification =====

Product ID:KODAK RAPID FIXER, CAT# 146 4114, TO MAKE 5 GAL, PART B

MSDS Date:11/08/1995

FSC:6525

NIIN:00-935-4105

Kit Part:Y

MSDS Number: BZPHY

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone Num:716-477-3194 MSDS :800- 242-2424

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name:EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD

Box:City:ROCHESTER

State:NY

ZIP:14650-3129

Country:US

Phone:800-828-6203

CAGE:5K871

=====

Composition/Information on Ingredients =====

Ingred Name:WATER
CAS:7732-18-5
RTECS #:ZC0110000
Fraction by Wt: 70-75% %
Other REC Limits:NONE RECOMMENDED

Ingred Name:ALUMINUM SULFATE (SARA III)
CAS:10043-01-3
RTECS #:BD1700000
Fraction by Wt: 15-20% %
Other REC Limits:NONE RECOMMENDED
OSHA PEL:2 MG/M3
ACGIH TLV:2 MG/M3; 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:SULFURIC ACID (SARA III)
CAS:7664-93-9
RTECS #:WS5600000
Fraction by Wt: 10-15% %
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1 MG/M3
ACGIH TLV:1 MG/M3; 9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

===== Hazards Identification =====

LD50 LC50 Mixture:ORAL LD50 (RAT): 0.5-5.0 G/KG
Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EXPECTED TO BE A LOW INHALATION HAZARD
FOR RECOMMENDED HANDLING. CAUSES EYE IRRITATION. CAUSES SKIN
IRRITATION. HARMFUL IF SWALLOWED. MAY
CAUSE BURNS OF THE
GASTROINTESTINAL TRACT IF SWALLOWED.
Explanation of Carcinogenicity:IARC HAS DETERMINED THAT OCCUPATIONAL
EXPOSURE TO STRONG ACIDS MAY BE CARCINOGENIC TO HUMANS.
Effects of Overexposure:EYE IRRITATION, SKIN IRRITATION, GI TRACT
IRRITATION, GASTROINTESTINAL BURNS.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:INHALATION: IF SYMPTOMATIC, MOVE TO FRESH AIR. GET MEDIC

AL

ATTENTION IF SYMPTOMS PERSIST. EYES: IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL ATTENTION. SKIN: IMMEDIATELY REMOVE CONTAMINATED CLOTHING AND WASH WITH SOAP AND WATER. GET MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITING. GIVE VICTIM A GLASS OF WATER. SEEK MEDICAL ATTENTION. NEVER GIVE ANYTHING BY MOUTH IF UNCONSCIOUS.

===== Fire Fighting Measures =====

Flash Point:NONFLAMMABLE

Lower Limits:NOT GIVEN

Upper Limits:N

OT GIVEN

Extinguishing Media:USE APPROPRIATE AGENT FOR ADJACENT FIRE.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING.

Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS.

===== Accidental Release Measures =====

Spill Release Procedures:MAY REQUIRE NEUTRALIZATION. FLUSH TO SEWER IF ALLOWABLE WITH LARGE AMOUNTS OF WATER. OTHERWISE, ABSORB SPILL WITH VERMICULITE OR OTHER

INERT MATERIAL, THEN PLACE IN A CONTAINER FOR CHEMICAL WASTE. CLEAN SURFACE TO REMOVE RESIDUAL CONTAMINATION.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT BREATHE MIST OR VAPOR. AVOID CONTACT WITH EYES, SKIN AND CLOTHING. USE WITH ADEQUATE VENTILATION. KEEP CONTAINER TIGHTLY CLOSED.

Other Precautions:KEEP AWAY FROM INCOMPATIBLE MATERIALS. WASH CONTAMINATED CLOTHING AFTER USE. DESTROY OR THOROUGHLY CLEAN CONTAMINATED SHOES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SHOULD BE NEEDED.

Ventilation:GOOD GENERAL VENTILATION, TYPICALLY 10 AIR CHANGES PER HOUR, SHOULD BE USED. RATES SHOULD MATCH CONDITIONS.

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY GLASSES W/SIDE SHIELDS OR GOGGLES

Other Protective Equipment:CHEMICAL RESISTANT CLOTHING AS NECESSARY TO PREVENT SKIN CONTACT. AN EMERGENCY

CY EYEWASH AND SHOWER SHOULD BE AVAILABLE.

Work Hygienic Practices:WASH HANDS THOROUGHLY WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES.

Supplemental Safety and Health

REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE. KEEP AWAY FROM CHILDREN.

===== Physical/Chemical Properties =====

HCC:C1

Boiling Pt:B.P. Text:>212F,>100C

Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN

Vapor Pres:18

Vapor Density:0.6

Spec Gravity:1.30

pH:1.0

Evap

Evaporation Rate & Reference:NOT GIVEN

Solubility in Water:COMPLETE

Appearance and Odor:COLORLESS LIQUID, SLIGHT SULFUR DIOXIDE ODOR

Percent Volatiles by Volume:70-75%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

BASES

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:SULFUR DIOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:DISCHARGE,

TREATMENT OR DISPOSAL MAY BE SUBJECT

TO NATIONAL, STATE OR LOCAL LAWS. MAY REQUIRE NEUTRALIZATION IF PH < 2.0 OR PH > 12.5. DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.