

LHB INDUSTRIES -- ECO-SURE BROWN #30277 (0674-395)

=====  
MSDS Safety Information  
=====

FSC: 8010  
NIIN: 01-337-3969  
MSDS Date: 04/28/1995  
MSDS Num: BZSZC  
Product ID: ECO-SURE BROWN #30277 (0674-395)  
MFN: 03  
Responsible Party  
Cage: 0FTT5  
Name: LHB INDUSTRIES  
Address: 8833 FLEISCHER PLACE  
City: SAINT LOUIS M  
O 63134  
Info Phone Number: 314-522-3141  
Emergency Phone Number: 314-522-3141 OR 800-424-9300  
Preparer's Name: RUDOLF OPPENHEIM  
Review Ind: Y  
Published: Y

=====  
Preparer Co. when other than Responsible Party Co.  
=====

Cage: 0FTT5  
Name: LHB INDUSTRIES  
Address: 8833 FLEISCHER PLACE  
City: ST. LOUIS MO 63134

=====  
Contractor Summary  
=====

Cage: 0FTT5  
Name: LHB INDUSTRIES  
Address: 8833 FLEISCHER PLACE  
City: ST. LOUIS MO 63134  
Phone: 314-522-3141

=====  
Item Description Information  
=====

Item Manager: GSA  
Item Name: ENAMEL  
Specification Number: A-A-2787  
Type/Grade/Class: TYPE 1  
Unit of Issue: PT  
UI Container Qty: 0

=====  
Ingredients  
=====

=====  
Cas: 1330-20-7  
RTECS #: ZE2100000  
Name: XYLENE (SARA III)  
% Wt: &lt;3.26  
Other REC Limits: NONE RECOMME  
OSHA PEL: NOT ESTABLISHED  
ACGIH TLV: 100 PPM  
EPA Rpt Qty: 1000 LBS  
DOT Rpt Qty: 1000 LBS  
-----

Cas: 108-88-3  
RTECS #: XS5250000  
Name: TOLUENE (SARA III)  
% Wt: 14.92  
Other REC Limits: NONE RECOMME  
OSHA PEL: 200 PPM  
ACGIH TLV: 100 PPM  
EPA Rpt Qty: 1000 LBS  
DOT Rpt Qty: 1000 LBS  
-----

Cas: 110-12-3  
RTECS  
#: MP3850000  
Name: 5-METHYL 2-HEXANONE  
% Wt: 6.53  
Other REC Limits: NONE RECOMME  
OSHA PEL: 50 PPM  
ACGIH TLV: 50 PPM  
-----

Cas: 64742-95-6  
RTECS #: SE7546500  
Name: AROMATIC 150  
% Wt: &lt;3.26  
Other REC Limits: NONE RECOMME  
OSHA PEL: 5 PPM  
ACGIH TLV: 5 PPM  
-----

Cas: 64742-95-6  
RTECS #: SE7546500  
Name: AROMATIC 100  
% Wt: 6.53  
Other REC Limits: NONE RECOMME  
OSHA PEL: 50 PPM  
ACGIH TLV: 50 PPM  
-----

Cas: 108-10-1  
RTECS #: SA9

275000

Name: 4-METHYL 2-PENTANONE (SARA III)

% Wt: &lt;3.26

Other REC Limits: NONE RECOMME

OSHA PEL: 100 PPM

ACGIH TLV: 50 PPM

EPA Rpt Qty: 5000 LBS

DOT Rpt Qty: 5000 LBS

-----  
Cas: 107-87-9

RTECS #: SA7875000

Name: 2- PENTANONE

% Wt: &lt;3.26

Other REC Limits: NONE RECOMME

OSHA PEL: 200 PPM

ACGIH TLV: 200 PPM

-----  
Cas: 95-63-6

RTECS #: DC3325000

Name: 1,2,4-TRIMETHYLBENZENE (SARA III)

% Wt: &lt;3.26

Other REC Limits: NONE RECOMME

OSHA PEL: 25 P

PM

ACGIH TLV: 25 PPM

-----  
Cas: 71-36-3

RTECS #: EO1400000

Name: N-BUTANOL (SARA III)

% Wt: &lt;3.26

Other REC Limits: NONE RECOMME

OSHA PEL: 50 PPM

ACGIH TLV: 100 PPM

EPA Rpt Qty: 5000 LBS

DOT Rpt Qty: 5000 LBS

-----  
Cas: 115-10-6

RTECS #: PM4780000

Name: DIMETHYL ETHER

% Wt: 7.08

Other REC Limits: NONE RECOMME

OSHA PEL: NOT ESTABLISHED

ACGIH TLV: NOT ESTABLISHED

-----  
Cas: 74-98-6

RTECS #: TX2275000

Name: PROPANE

% Wt:

12.74  
Other REC Limits: NONE RECOMME  
OSHA PEL: 1000 PPM  
ACGIH TLV: 1000 PPM

-----  
RTECS #: 9999999VO  
Name: VOC: 60%, 584 G/L  
Other REC Limits: NONE RECOMME

=====  
Health Hazards Data  
=====

Route Of Entry Inds - Inhalation: YES  
Skin: YES  
Ingestion: YES  
Carcinogenicity Inds - NTP: NO  
IARC: NO  
OSHA: NO  
Effects of Exposure: CONCENTRATING & INHALING CONTENTS MAY BE  
HARMFU  
L/FATAL. REPORTS ASSOCIATE REPEATED & PROLONGED OVEREXPOSURE W/  
PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE. HIGH CONCENTRATING ANESTHETIC.  
SKIN & RESPIRATORY TRACT IRRITATION. LIGHT HEADEDNESS, STAGGERING,  
GIDDINESS, NAUSEA. HARMFUL IF SWALLOWED. SEVERE EYE IRRITATION.  
Signs And Symptions Of Overexposure: IRRITATION TO EYES, THROAT, AND  
RESPIRATORY TRACT. MAY CAUSE HEADACHES, NAUSEA, AND VOMITING.  
Medical Cond Aggravated By Exposure: RESPIRATORY AILMENTS  
First Aid: FOR CONTACT  
WITH SKIN OR CLOTHES WASH WITH SOAP & WATER. WASH  
CLOTHES BEFORE REUSE. FOR CONTACT WITH EYES, FLUSH WITH WATER FOR 15 MINTUES.  
CONTACT A PHYSICIAN/OPHTHALMOLOGIST IMMEDIATELY. IF SWALLOWE D, DO NOT INDUCE  
VOMITING. GET IMMEDIATE MEDICAL AID. IF INHALED, GET FRESH AIR & GET  
ARTIFICIAL REAPIRATION IF NECESSARY. GET MED AID. NEVER GIVE ANYTHING BY  
MOUTH TO UNCONSCIOUS PERSON.

=====  
Handling and Disposal  
=====

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION AND VENTILATE AREA.  
MOP SPILLS WITH INERT ABSORBENT. AVOID BREATHING VAPORS.  
Waste Disposal Methods: DISPOSE IN ACCORD WITH FEDERAL, STATE, LOCAL  
REGULATIONS. DO NOT PUNCTURE, INCINERATE, OR STORE ABOVE 120F. EXPOSURE TO  
HEAT OR PROLONGED EXPOSURE TO SUN MAY CAUSE CAN TO BURST. DISCARD EMPTY CAN  
IN T RASH PICK-UP. DON'T PLACE IN HOME TRASHCOMPACTOR.  
Handling And Storage Precautions: KEEP OUT OF REACH O

KEEP FROM CHILDREN. CONTENTS UNDER  
PRESSURE. DO NOT STORE WHERE TEMPERATURES MAY EXCEED 120F. AVOID BREATHING  
SPRAY, MIST, OR VAPOR.

Other Precautions: AVOID CONTACT WITH EYES AND SKIN. USE WITH GOOD VENTILATION.  
READ ENTIRE LABEL DIRECTIONS. INTENTIONAL MISUSE BY DELIBERATELY  
CONCENTRATING & INHALING OR SWALLOWING CONTENTS MAY BE HARMFUL OR FATAL.

=====  
Fire and Explosion Hazard Information  
=====

=====  
Flash Point Text: NR

Lower Limits: 2.2

Upper Limits: 18.0

Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, FOAM, SAND, WATER SPRAY.  
AVOID SPREADING ANY BURNING LIQUID WITH WATER SPRAY.

Fire Fighting Procedures: WATER MAY BE INEFFECTIVE, USE TO COOL FIRE EXPOSED  
CONTAINER. WEAR SCBA. USE SHIELDING TO PROTECT PERSONNEL AGAINST BURSTING,  
RUPTURING OR VENTING OF CONTAINER.

Unusual Fire/Explosion Hazard: DO NOT SPRAY NEAR OPEN FLAME. AT ELEVATED  
TEMPERATURE (>120F) CONTAINER MAY VE  
NT, RUPTURE, OR BURST. AEROSOL  
CONTAINER; DO NOT EXPOSE TO TEMPERATURE ABOVE 120F.

=====  
Control Measures  
=====

Respiratory Protection: NONE BELOW TLV. USE NIOSH/MSHA APPROVED MASK ABOVE TLV.

Ventilation: LOCAL EXHAUST: PREFERRED. MECHANICAL (GENERAL): ACCEPTABLE AT  
POINT OF MIST OR SPRAY RELEASE.

Protective Gloves: TO PROTECT SKIN

Eye Protection: CHEMICAL SPLASH GOGGLES

Other Protective Equi

PMENT: IMPERVIOUS CLOTHES TO PROTECT SKIN. EYE WASH  
STATION.

Work Hygienic Practices: USE GOOD PERSONAL HYGIENE. DO NOT EAT, DRINK, OR SMOKE  
WHILE USING PRODUCT.

=====  
Physical/Chemical Properties  
=====

HCC: V3

Vapor Pres: 70 @ 68F

Vapor Density: >1.522

Spec Gravity: 1.189 (WATER=1)

Solubility in Water: INSOLUBLE

Appearance and Odor: BROWN / PAINT  
=====

=====

Reactivity Data

Stability Indicator: YES  
Stability Condition To Avoid: EXTREME HEAT  
Hazardous Decomposition Products: CARBON MONOXIDE  
Hazardous Polymerization Indicator: NO

=====  
Toxicological Information  
=====

=====  
Ecological Information  
=====

=====  
MSDS Transport Information  
=====

=====  
Regulatory Information  
=====

=====  
Other Information  
=====

=====  
Transportation Information  
=====

Responsible Party Code: 0FTT5  
Trans ID NO: 126996  
Product ID: ECO-SURE BROWN #30277 (0674-395)  
MSDS Prepared Date: 04/28/1995  
Review Date: 07/08/1996  
MFN: 3  
Multiple KIT Number: 0  
Review IND: Y  
Unit Of Issue: PT  
Container QTY: 0

=====  
Detail DOT Information  
=====

DOT PSN Code: DTJ  
Symbols: D  
DOT Proper Shipping Name: CONSUMER COMMO

DITY  
Hazard Class: ORM-D  
Label: NONE  
Non Bulk Pack: 156,306  
Bulk Pack: NONE  
Max Qty Pass: 30KGGROSS  
Max Qty Cargo: 30KGGROSS  
Vessel Stow Req: A

=====  
Detail IMO Information  
=====

IMO PSN Code: AKH  
IMO Proper Shipping Name: AEROSOLS/AEROSOL PRODUCT ?  
IMDG Page Number: SEE 9022  
UN Number: 1950  
UN Hazard Class: 9?  
IMO Packaging Group: -  
Subsidiary Risk Label: -  
EMS Number: 2-13  
=====

=====  
Detail IATA Information  
=====

IATA PSN Code: ALS  
IATA UN ID Num: 1950  
IATA Proper Shipping Name: AEROSOLS, FLAMMABLE  
IATA PSN Modifier: (EACH NOT EXCEEDING 1 L CAPACITY)  
IATA UN Class: 2.1  
IATA Label: FLAMMABLE GAS  
Packing Note Passenger: 203  
Max Quant Pass: 75KG  
Max Quant Cargo: 150KG  
Packaging Note Cargo: 203  
=====

=====  
Detail AFI Information  
=====

AFI PSN Code: ALR  
AFI Symbols: \*  
AFI Proper Shipping Name: AEROSOLS, FLAMMABLE, N.O.S.  
AFI PSN Modifier: (EACH NOT EXCEEDING 1L CAPACITY)  
AFI Hazard Class: 2.1  
AFI UN ID NUM: UN1950  
Special Provisions: P4  
Back Pack Reference: A6.3  
=====

=====  
HAZCOM Label  
=====

Product ID: ECO-SURE BROWN #30277 (0674-395)  
Cage: 0FTT5  
Company Name: LHB INDUSTRIES  
Street: 8833 FLEISCHER

PLACE

City: ST. LOUIS MO

Zipcode: 63134

Health Emergency Phone: 800-424-9300 CHEMTREC/ 314-522-3141

Label Required IND: Y

Date Of Label Review: 12/16/1998

Status Code: C

Label Date: 12/16/1998

Origination Code: G

Hazard And Precautions: CONCENTRATING & INHALING CONTENTS MAY BE HARMFUL/FATAL. REPORTS ASSOCIATE REPEATED & PROLONGED OVEREXPOSURE W/ PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE. HIGH CONCENTRATIONS ANESTHETIC. SKIN & RESPIRATORY TRACT IRRITATION. LIGHT HEADEDNESS, STAGGERING, GIDDINESS, NAUSEA. HARMFUL IF SWALLOWED. SEVERE EYE IRRITATION. IRRITATION TO EYES, THROAT, AND RESPIRATORY TRACT. MAY CAUSE HEADACHES, NAUSEA, AND VOMITING.

=====  
Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends to provide information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.