

FISKE BROTHERS REFINING CO -- LUBRIPLATE RG-62-A -- 9150-00-754-0063

=====
Product Identification
=====

Product ID:LUBRIPLATE RG-62-A

MSDS Date:03/01/1996

FSC:9150

NIIN:00-754-0063

MSDS Number: CBQLF

=== Responsible Party ===

Company Name:FISKE BROTHERS REFINING CO

Address:1500 OAKDALE AVE, STATION A.

Box:8038

City:TOLEDO

State:OH

ZIP:43605-3843

Country:US

Info Phone Num:419-691-2491

Emergency Ph

one Num:800-255-3924 CHEMTEL

Preparer's Name:JAMES R. KONTAK

CAGE:9N579

=== Contractor Identification ===

Company Name:FISKE BROS REFINING CO

Address:129 LOCKWOOD ST

Box:City:NEWARK

State:NJ

ZIP:07105-4720

Country:US

Phone:201-589-9150

CAGE:73219

Company Name:FISKE BROTHERS REFINING CO

Address:1500 OAKDALE AVE

Box:City:TOLEDO

State:OH

ZIP:43605

Country:US

Phone:419-691-2491

CAGE:9N579

Company Name:INDUSTRIAL SUPPLY CORP

Address:1905 WESTWOOD AVE

Box:6356

City:RICHMOND

State:VA

ZIP:23230

Country:

US
Phone:804-355-8041
CAGE:6A908

=====
Composition/Information on Ingredients
=====

Ingred Name:NON-HAZARDOUS INGREDIENTS
Fraction by Wt: 100%
Other REC Limits:NONE RECOMMENDED

=====
Hazards Identification
=====

LD50 LC50 Mixture:TLV=5 MG/M3 (OIL MIST)
Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYE CONTACT MAY CAUSE IRRITATION.
PROLONGED SKI
N CONTACT MAY CAUSE IRRITATION. HUMAN HEALTH RISKS
VARY FROM PERSON TO PERSON. AS A PRECAUTION, EXPOSURE TO LIQUIDS,
VAPORS, MISTS & FUMES SHOULD BE MINI MIZED. PRODUCT HAS A LOW ORDER
OF ORAL TOXICITY, BUT MINUTES AMOUNTS ASPIRATED INTO LUNGS MAY
CAUSE PULMONARY INJURY.
Explanation of Carcinogenicity:NO INGREDIENT OF A CONCENTRATION OF 0.1%
OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN.
Effects of Overexposure:EYES-IRRITATION. SKIN-IRRITATION.
INHALED/INGE
STED-ASPIRATION, LUNG INJURY.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
First Aid Measures
=====

First Aid:EYES-FLUSH WITH CLEAR WATER FOR 15 MINUTES OR UNTIL
IRRITATION SUBSIDES. CONSULT A PHYSICIAN IF IRRITATION PERSISTS.
SKIN-REMOVE CONTAMINATED CLOTHES. WASH WOTH SOAP & WATER. IF
INJECTED UNDER HIGH PR ESSURE, SEE A PHYSICIAN IMMEDIATELY.
INHALED-REMOVE FROM EXPOSURE & CALL PHYSICIAN. INGESTED-DO NOT
INDUCE VOMITING! CALL PHYSICIAN IMMEDIATELY.

=====
Fire Fighting Measures
=====

Flash Point Method:COC
Flash Point:410F,210C
Lower Limits:0.9
Upper Limits:7.0
Extinguishing Media:WATER SPRAY OR FOG, CARBON DIOXIDE, DRY CHEMICAL,
FOAM.
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND
FULL FIRE FIGHTER'S PROTECTIVE GEAR. USE WATER TO COOL FIRE EXPOSED
CONTAINERS.
Unusual Fire/Explosion Hazard:DO NOT STORE OR MIX WITH STRONG OXIDAN

TS.

EMPTY CONTAINERS RETAIN RESIDUE. DO NOT CUT, DRILL, GRIND OR WELD AS THEY EXPLODE.

===== Accidental Release Measures =====

Spill Release Procedures:SCRAPE UP GREASE. WASH REMAINDER WITH SUITABLE PETROLEUM SOLVENT OR ADD ABSORBENT. KEEP PETROLEUM PRODUCTS OUT OF SEWERS AND WATER COURSES. ADVISE AUTHORITIES IF PRODUCT HAS ENTERED OR MAY ENTER SEWER S OR WATER COURSES (USCG 800-424-8802).

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY PLACE AWAY FROM HEAT, SPARKS, FLAME OR STRONG OXIDIZING AGENTS. KEEP CONTAINERS CLOSED WHEN NOT IN USE.

Other Precautions:REMOVE OIL-SOAKED CLOTHING AND LAUNDER BEFORE REUSE. CLEANSE THOROUGHLY AFTER CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED.

Ventilation:USE LOCAL EXHAUST TO MAINTAIN EXPOSURE BELOW TLV(S).

Protective Gloves:OIL-RESISTANT: NITRILE.

Eye Protection:GOGGLES.

Other Protective Equipment:OIL-RESISTANT APRON. DLA-HMIS: EYE WASH STATION.

Work Hygienic Practices:WASH HANDS AFTER HANDLING AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOTHES BEFORE REUSE.

Supplemental Safety and Health

MSDS PRESNETED BY CAGE 6A908 FOR CONTRACT NUMBER SP0451-96-M-Q407.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text

t:>550F,>288C

Melt/Freeze Pt:M.P/F.P Text:SEMI-SOLID

Vapor Pres:5

Spec Gravity:0.96

Evaporation Rate & Reference: