

BAROID DRILLING FLUIDS,INC. -- EZ MUD -- 9390-01-241-7430

=====
===== Product Identification =====

Product ID:EZ MUD

MSDS Date:06/30/1996

FSC:9390

NIIN:01-241-7430

MSDS Number: CBQTZ

=== Responsible Party ===

Company Name:BAROID DRILLING FLUIDS,INC.

Address:3000 N SAM HOUSTON PKY E

Box:1675

City:HOUSTON

State:TX

ZIP:77251

Country:US

Info Phone Num:713-987-5900

Emergency Phone Num:800-424-5900 OR 713-987-5900

CAGE:HO821

=== Contractor Identification ===

Company Name:BAROID DRILLING FLUIDS

Address:A PRODUCT SVC LINE OF HALLIBURTON ENERGY SVC, INC

Box:1675

City:HOUSTON

State:TX

ZIP:77251

Country:US

Phone:(281) 871-4000

CAGE:HO821

Company Name:BAROID DRILLING FLUIDS,INC.

Address:3000 N SAM HOUSTON PKY E

Box:1675

City:HOUSTON

State:TX

ZIP:77251

Country:US

Phone:713-987-4000/713-987-5900

CAGE:20064

=====
===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM HYDROCARB

ON,
CAS:64742-47-8
RTECS #:OA5504000
Fraction by Wt: 24%
Other REC Limits:400 PPM OSHA PER MFR
OSHA PEL:5 MG/M3 (OIL MIST)
ACGIH TLV:5 MG/M3 (OIL MIST)

=====
===== Hazards Identification =====

LD50 LC50 Mixture:PRODUCT'S LD50 (ORAL RAT) WAS NOT STATED
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYE:MAY CAUSE IRRITATION. SKIN:ON
DIRECT CONTACT, MAY PRODUCE SEVERE SK
IN IRRITATION. INGESTION:LARGE
AMOUNTS MAY CAUSE INJURY. INHALATION:PROLONGED REPEATED EXPOSURE TO
VAPOR MAY CAUSE CNS DAMAGE AND /OR CNS DEPRESSION AS WELL AS HEART
& BLOOD DISORDERS. ASPIRATION MAY CAUSE CHEMICAL PNEUMONITIS.
Explanation of Carcinogenicity:NOT ON NTP, IARC OR OSHA LISTS.
Effects of Overexposure:EYE:IRRITATION. SKIN:SEVERE IRRITATION.
INGESTION:LARGE AMOUNTS MAY CAUSE INJURY. INHALATION:PROLONGED
REPEATED EXPOSURE TO VAPOR;CNS DAMAGE AND/OR CNS DEPRESSION, H
EART
& BLOOD DISORDERS. ASPIRATION MAY CAUSE CHEMICAL PNEUMONITIS.
Medical Cond Aggravated by Exposure:MFR GAVE NO INFORMATION OF MSDS.

=====
===== First Aid Measures =====

First Aid:IF ANY IRRITATION PERSISTS OR SEVERE, GET MEDICAL ATTENTION.
EYE:FLUSH W/WATER FOR 15 MIN. SKIN:WASH W/SOAP & WATER. REMOVE
CONTAMINATED CLOTHING & LAUNDER BEFORE REUSE. INHALED:REMOVE FROM
CONTAMINATED AREA IF AFFECTED. CONSULT A PHYSICIAN.

=====
===== Fire Fighting Measures =====

Flash Point:>200F,>93C
Extinguishing Media:USE WATER SPRAY, CARBON DIOXIDE, DRY CHEMICAL. USE
WATER TO KEEP CONTAINERS COOL.
Fire Fighting Procedures:WEAR SELF-CONTAINED POSITIVE PRESSURE
BREATHING APPARATUS & FULL FIRE-FIGHTING PROTECTIVE CLOTHING.
Unusual Fire/Explosion Hazard:NONE STATED

=====
===== Accidental Release Measures =====

Spill Release Procedures:CONTAIN SPILL W/ABSORBENT MATERIAL. PLACE IN
CONTAINER

