

BAROID DRILLING FLUIDS,INC. -- EZ MUD -- 9390-01-241-7430

=====  
===== Product Identification =====

Product ID:EZ MUD

MSDS Date:06/30/1996

FSC:9390

NIIN:01-241-7430

MSDS Number: CBQTZ

=== Responsible Party ===

Company Name:BAROID DRILLING FLUIDS,INC.

Address:3000 N SAM HOUSTON PKY E

Box:1675

City:HOUSTON

State:TX

ZIP:77251

Country:US

Info Phone Num:713-987-5900

Emergency Phone Num:800-424-5900 OR 713-987-5900

CAGE:HO821

=== Contractor Identification ===

Company Name:BAROID DRILLING FLUIDS

Address:A PRODUCT SVC LINE OF HALLIBURTON ENERGY SVC, INC

Box:1675

City:HOUSTON

State:TX

ZIP:77251

Country:US

Phone:(281) 871-4000

CAGE:HO821

Company Name:BAROID DRILLING FLUIDS,INC.

Address:3000 N SAM HOUSTON PKY E

Box:1675

City:HOUSTON

State:TX

ZIP:77251

Country:US

Phone:713-987-4000/713-987-5900

CAGE:20064

=====  
===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM HYDROCARB

ON,  
CAS:64742-47-8  
RTECS #:OA5504000  
Fraction by Wt: 24%  
Other REC Limits:400 PPM OSHA PER MFR  
OSHA PEL:5 MG/M3 (OIL MIST)  
ACGIH TLV:5 MG/M3 (OIL MIST)

=====  
Hazards Identification  
=====

LD50 LC50 Mixture:PRODUCT'S LD50 (ORAL RAT) WAS NOT STATED  
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:EYE:MAY CAUSE IRRITATION. SKIN:ON  
DIRECT CONTACT, MAY PRODUCE SEVERE SK  
IN IRRITATION. INGESTION:LARGE  
AMOUNTS MAY CAUSE INJURY. INHALATION:PROLONGED REPEATED EXPOSURE TO  
VAPOR MAY CAUSE CNS DAMAGE AND /OR CNS DEPRESSION AS WELL AS HEART  
& BLOOD DISORDERS. ASPIRATION MAY CAUSE CHEMICAL PNEUMONITIS.  
Explanation of Carcinogenicity:NOT ON NTP, IARC OR OSHA LISTS.  
Effects of Overexposure:EYE:IRRITATION. SKIN:SEVERE IRRITATION.  
INGESTION:LARGE AMOUNTS MAY CAUSE INJURY. INHALATION:PROLONGED  
REPEATED EXPOSURE TO VAPOR;CNS DAMAGE AND/OR CNS DEPRESSION, H  
EART  
& BLOOD DISORDERS. ASPIRATION MAY CAUSE CHEMICAL PNEUMONITIS.  
Medical Cond Aggravated by Exposure:MFR GAVE NO INFORMATION OF MSDS.

=====  
First Aid Measures  
=====

First Aid:IF ANY IRRITATION PERSISTS OR SEVERE, GET MEDICAL ATTENTION.  
EYE:FLUSH W/WATER FOR 15 MIN. SKIN:WASH W/SOAP & WATER. REMOVE  
CONTAMINATED CLOTHING & LAUNDER BEFORE REUSE. INHALED:REMOVE FROM  
CONTAMINATED AREA IF AFFECTED. CONSULT A PHYSICIAN.

=====  
Fire Fighting Measures  
=====

Flash Point:>200F,>93C  
Extinguishing Media:USE WATER SPRAY, CARBON DIOXIDE, DRY CHEMICAL. USE  
WATER TO KEEP CONTAINERS COOL.  
Fire Fighting Procedures:WEAR SELF-CONTAINED POSITIVE PRESSURE  
BREATHING APPARATUS & FULL FIRE-FIGHTING PROTECTIVE CLOTHING.  
Unusual Fire/Explosion Hazard:NONE STATED

=====  
Accidental Release Measures  
=====

Spill Release Procedures:CONTAIN SPILL W/ABSORBENT MATERIAL. PLACE IN  
CONTAINER

