

CLICK BOND INC -- CB200 PART A

=====
MSDS Safety Information
=====

FSC: 8040
NIIN: 01-344-2193
MSDS Date: 02/12/1996
MSDS Num: CBQXZ
Product ID: CB200 PART A
MFN: 01
Kit Part: Y
Responsible Party
Cage: MO938
Name: CLICK BOND INC
Address: 2151 LOCKHEED WAY
City: CARSON CITY NV 89706
In
fo Phone Number: 702-885-8000
Emergency Phone Number: 800-255-3924; 813-979-0626
Proprietary Ind: Y
Published: Y

=====
Contractor Summary
=====

Cage: 66530
Name: CLICK BOND DIV OF PHYSICAL SYSTEMS INC
Address: 2151 LOCKHEED WAY
City: CARSON CITY NV 89701-0713
Phone: 775-885-8000
Cage: MO938
Name: CLICK BOND INC
Address: 2151 LOCKHEED WAY
City: CARSON CITY NV 89706-0713
Phone: 702-885-8000

=====
Item Description Information
=====

Item Name: ADHESIVE

=====
Ingredients
=====

Name: *** PROPRIETARY ***

=====
Health Hazards Data
=====

LD50 LC50 Mixture: NONE SPECIF

IED BY MANUFACTURER.

Route Of Entry Inds - Inhalation: YES

Skin: YES

Ingestion: YES

Carcinogenicity Inds - NTP: NO

IARC: NO

OSHA: NO

Effects of Exposure: EYES: MAY CAUSE EYE IRRITATION. SKIN: MAY CAUSE SKIN IRRITATION. MAY CAUSE SKIN SENSITIZATION. MAY CAUSE ALLERGIC SKIN REACTION. MAY CAUSE DERMATITIS. INHALATION: MAY CAUSE RESPIRATORY TRACT IRRITATION. INGESTION: HARMFUL IF SWALLOWED. INGESTION IS NOT AN EXPECTED ROUTE OF ENTRY IN INDUSTRIAL OR (EFTS OF OVEREXP)

Explanation Of Carcinogenicity: NOT RELEVANT

Signs And Symptoms Of Overexposure: HLTH HAZ: COMMERCIAL USES. CHRONIC: CHRONIC SKIN CONTACT MAY CAUSE DERMATITIS.

Medical Cond Aggravated By Exposure: NONE SPECIFIED BY MANUFACTURER.

First Aid: EYE: FLUSH EYES IMMED W/LG AMTS OF WATER FOR AT LEAST 15 MIN HOLDING EYELIDS OPEN WHILE FLUSHING. GET PROMPT MED ATTN. SKIN: FLUSH CONTAMD SKIN W/LG AMTS OF WATER WHILE REMOVING CONTAMD CLTHG. WASH AFFECTED SKIN AREAS W/SOAP & WATER. GET MED ATTN IF SYMPS OCCUR. INHAL : MOVE PERSON TO FRESH AIR. RESTORE & SUPPORT CONTINUED BRTHG. IF BRTHG IS DFCLT, GIVE OXYGEN. GET IMMED MED ATTN. INGEST: (SUPDAT)

=====
Handling and Disposal
=====

Spill Release Procedures: AVOID BRTHG VAPS. USE NIOSH/MSHA APPRVD SELF-CONTAINED BRTHG EQUIP. NOTIFY APPROP AUTHS IF NEC. CNTN & REMOVE W/INERT ABSORB MATL. AVOID CNTCT. KEEP NON-ESSNTL PERS AWAY FROM SPILL AREA. BEF

ORE ATTEMPT PING CLEANUP, REFER TO HAZ CAUTION INFO

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Waste Disposal Methods: DISPOSAL SHOULD BE DONE IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL ENVIRONMENTAL CONTROL REGULATIONS. IF WASTE IS DETERMINED TO BE HAZARDOUS, USE LICENSED HAZARDOUS WASTE TRANSPROT AND DISPOSAL FACILITY.

Handling And Storage Precautions: STORE ONLY IN WELL-VENTILATED AREAS. KEEP CONTAINER CLOSED WHEN NOT IN USE.

Other Precautions: KEEP CLOSURE TIGHT & CNT

NR UPRIGHT TO PVNT LEAKAGE.

AVOID SKIN & EYE CONTACT. WASH THORO AFTER HANDLING. AVOID BRTHG OF VAP OR SPRAY MISTS. DO NOT HANDLE UNTIL ALL SAFETY PRECS HAVE BEEN READ & UNDERS TOOD. EMPTY CNTNRS SHOULD NOT

=====
Fire and Explosion Hazard Information
=====

Flash Point Method: SCC

Flash Point Text: >200F,>93C

Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL FOAM, WATER FOG.

F

Fire Fighting Procedures: USE NIOSH/MSHA APPRVD SCBA & FULL PROT EQUIP (FP N). IF WATER IS USED, FOG NOZZS ARE PREF. DURING FIRE, IRRITATING &/OR TOX GASES & PARTICULATE MAY BE (SUPDAT)

Unusual Fire/Explosion Hazard: CLOSED CONTAINERS MAY RUPTURE WHEN EXPOSED TO EXTREME HEAT. USE WATER SPRAY TO KEEP FIRE EXPOSED CONTAINERS COOL.

=====
Control Measures
=====

Respiratory Protection

: USE NIOSH/MSHA APPRVD AIR-PURIFYING ORG VAP RESP IF OCCUP LIMS ARE EXCEEDED. FOR EMER SITUATIONS, CONFINED SPACE USE, OR OTHER CNDTNS WHERE EXPOS LIMS MAY BE GREATLY EXCEEDED, USE NIOSH/MSHA APPRVD AIR-SUPPLIED RESP. OBSERVE

Ventilation: SUFFICIENT VENT IN PATTERN & VOL SHOULD BE PROVIDED IN ORDER TO MAINTAIN AIR CONTAM LEVELS BELOW RECOM EXPOS LIMITS.

Protective Gloves: NEOPRENE, NITRILE OR RUBBER GLOVES.

Eye Protection: ANSI APPRVD CHEM WORKERS GOGGLES (FP N).

Other Protective

Equipment: ANSI APPROVED EYE WASH & DELUGE SHOWER (FP N).

REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE.

Work Hygienic Practices: WASH HANDS BEFORE EATING, SMOKING OR USING TOILET FACILITY. DO NOT SMOKE IN ANY CHEM HNDLG/STORAGE AREAS.

Supplemental Safety and Health: USERS OF "L" VERSION SHOULD CONSULT "LR" VERSION FOR ADDNL INFO (FP N). FIRE FIGHT PROC: GENERATED BY THERMAL DECOMP/COMBUST. FIRST AID PROC: IF SWALLOWED, DO NOT INDUCE VOMIT. GIVE VICTIM 1 OR 2 GLAS SES OF WATER/MI

CALL MD/POIS CTL CTRIMMED FOR FURTHER INSTRUCTIONS. NEVER GIVE ANYTHING BY MOUTH TO AN UNCON PERSON.

=====
Physical/Chemical Properties
=====

B.P. Text: 212F,100C

Vapor Density: HVR/AIR

Spec Gravity: 1.19

VOC Grams/Liter: 30

Evaporation Rate & Reference: IS SLOWER THAN ETHER

Solubility in Water: INSOLUBLE

Appearance and Odor: YELLOW PASTE; NO ODOR.

Percent Volatiles by Volume: 3.0

=====

=====
Reactivity Data
=====

Stability Indicator: YES

Stability Condition To Avoid: HIGH TEMPERATURES.

Materials To Avoid: STRONG ACIDS, BASES AND STRONG OXIDIZERS.

Hazardous Decomposition Products: CARBON MONOXIDE, CARBON DIOXIDE.

Hazardous Polymerization Indicator: NO

Conditions To Avoid Polymerization: NOT RELEVANT
=====

Toxicological Information
==
=====

=====
Ecological Information
=====

=====
MSDS Transport Information
=====

=====
Regulatory Information
=====

=====
Other Information
=====

=====
Transportation Information
=====

Responsible Party Cage: MO938

Trans ID NO: 127475

Product ID: CB200 PART A

MSDS Prepared Date: 02/12/1996

Review Date: 01/07/1997

MFN: 1

Multiple KIT Number: 0

Kit Part IND: Y

Review IND: Y
=====

Detail DOT Inform

ation

=====
DOT PSN Code: KZJ
Symbols: G
DOT Proper Shipping Name: ORGANIC PEROXIDE TYPE E, SOLID
Hazard Class: 5.2
UN ID Num: UN3108
DOT Packaging Group: II
Label: ORGANIC PEROXIDE
Packaging Exception: 152
Non Bulk Pack: 225
Bulk Pack: NONE
Max Qty Pass: 10 KG
Max Qty Cargo: 25 KG
Vessel Stow Req: D
Water/Ship/Other Req: 12,40
=====

=====
Detail IMO Information
=====

=====
IMO PSN Code: LAV
IMO Proper Shipping Name: ORGANIC PEROXIDE TYPE E, SOLID
IMDG Page Number: 5228
UN Number: 3108
UN Hazard Class: 5.2
IMO Packaging Group: II
Subsidiary Risk Label: *
EMS Number: 5.2-01
MED First Aid Guide NUM: 735
=====

=====
Detail IATA Information
=====

IATA PSN Code: SNM
IATA UN ID Num: 3108
IATA Proper Shipping Name: ORGANIC PEROXIDE TYPE E, SOLID * +
IATA UN Clas
s: 5.2
IATA Label: ORGANIC PEROXIDE
UN Packing Group: II
Packing Note Passenger: 510
Max Quant Pass: 10KG
Max Quant Cargo: 25KG
Packaging Note Cargo: 513
Exceptions: A20
=====

=====
Detail AFI Information
=====

AFI PSN Code: SNM
AFI Symbols: *
AFI Proper Shipping Name: ORGANIC PEROXIDE TYPE E, SOLID
AFI PSN Modifier: (SPECIFIC TECHNICAL NAME REQUIRED, SEE PARAGRAPH A9.4)
AFI Hazard Class: 5.2
AFI UN ID

NUM: UN3108
AFI Packing Group: II
Special Provisions: P5
Back Pack Reference: TABLE A9.1

=====

HAZCOM Label

=====

Product ID: CB200 PART A
Cage: MO938
Assigned IND: Y
Company Name: CLICK BOND INC
Street: 2151 LOCKHEED WAY
City: CARSON CITY NV
Zipcode: 89706-0713
Health Emergency Phone: 800-255-3924; 813-979-0626
Label Required IND: Y
Date Of Label Review: 06/21/1996
Status Code: C
Label Date: 06
/21/1996
Origination Code: G
Chronic Hazard IND: Y
Eye Protection IND: YES
Skin Protection IND: YES
Signal Word: WARNING
Respiratory Protection IND: YES
Health Hazard: Slight
Contact Hazard: Moderate
Fire Hazard: Slight
Reactivity Hazard: None
Hazard And Precautions: COMBUSTIBLE. ACUTE: EYES: MAY CAUSE EYE IRRITATION.
SKIN: MAY CAUSE SKIN IRRITATION, SENSITIZATION, ALLERGIC SKIN REACTION,
DERMATITIS. INHALATION: MAY CAUSE RESPIRATORY TRACT IRRITATION. INGESTION: H
ARMFUL IF SWALLOWED. CHRO
NIC: MAY CAUSEDERMATITIS. MAY CAUSE SENSITIZATION.

=====

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor

any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situatio

n.