

DOW CORNING CORP -- Z MOLY POWDER -- 6810-00-086-3542

=====
Product Identification
=====

Product ID:Z MOLY POWDER

MSDS Date:02/07/1995

FSC:6810

NIIN:00-086-3542

MSDS Number: CBRVN

=== Responsible Party ===

Company Name:DOW CORNING CORP

Address:3901 SOUTH SAGINAW ROAD

Box:997

City:MIDLAND

State:MI

ZIP:48686

Country:US

Info Phone Num:517-496-6000

Emergency Phone Num:517-496-5900/800-424-9300(CHEMTR
EC)

CAGE:5D028

=== Contractor Identification ===

Company Name:DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

Company Name:DOW CORNING CORP

Address:2200 W SALZBURG RD

Box:City:AUBURN

State:MI

ZIP:48611

Country:US

Phone:517-496-4388

CAGE:71984

=====
Composition/Information on Ingredients
=====

Ingred Name:MOLYBDENUM DISULFIDE

CAS:1317-33-5

RTECS #:QA4697000

Fraction by Wt: 99%

Other R

EC Limits:NONE RECOMMENDED

OSHA PEL:5 MG MO/M3

ACGIH TLV:5 MG MO/M3

Ingred Name:SILICA, CRYSTALLINE - QUARTZ

CAS:14808-60-7

RTECS #:VV7330000

Fraction by Wt: 0.3%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:SEE TABLE Z-3

ACGIH TLV:0.1 MG/M3 RDUST;9596

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:YES OSHA:NO

Health Hazards A

cute and Chronic:EYES:DIRECT CONTACT IRRIT SLIGHTLY

W/REDNESS & SWELLING. SKIN:SINGLE RELATIVELY SHORT EXPO CAUSES NO KNOWN ADVERSE EFFECT.SEVERAL REP/RPOL EXPO(24-48HRS)MAY IRRIT.

INHAL:DUST MAY INJURE RESP SYS. ORAL :SM AMTS TRANSFERRED TO MOUTH BY FINGERS DURING USE,ETC SHOULD NOT INJURE.SWALLOWING LG AMTS MAY INJURE SLIGHTLY.

Explanation of Carcinogenicity:PER MSDS:MATL CONTAINS QUARTZ, IARC GROUP 2A. LISTED BY STATE OF CALIFORNIA PROP 65.

Effects of Overexposure:SLIG

HTLY EYE IRRIT, REDNESS, SWELLING. SKIN IRRIT. INJURE RESP SYSTEM.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:EYE:IMMED FLUSH W/WATER FOR 15MINS. SKIN:NO FIRST AID SHOULD BE NEEDED. INHAL:REMOVE TO FRESH AIR.GET MED ATT IF ILL EFFECTS PERSIST. ORAL:GET MED ATTN. COMMENTS:TREAT ACCORDING TO PERSON'S CONDITION & SPECIFICS OF EXPOSURE.

===== Fire Fighting Measures =====

Autoignition Temp:Autoignition Temp Text:NA

Lower Limits:NOT DETERMIN

Upper Limits:NOT DETERMIN

Extinguishing Media:WATER,WATER FOG(OR SPRAY), CARBON DIOXIDE, (CO2), DRY CHEMICAL, FOAM.

Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS & PROTECTIVE CLOTHING SHOULD BE WORN IN FIGHTING FIRES INVOLVING CHEMICALS.

Unusual Fire/Explosion Hazard:STATIC ELECTR MAY ACCUMULATE;IGN SUSPENDED DUST CAUSING EXPLO.BOND/GROUND CNTNRS/EQPMT AS APPROPRIA

TE.ALSO REFER TO STD THAT DESCRIBE APPROP EXPLO PREVENT
PRACT

===== Accidental Release Measures =====

Spill Release Procedures:DISPO MAY GOVNT REG.OBSERVE ALL APPLICABLE
LOC/STATE/FED WASTE MANAGEMENT REGS.SWEEPUP/VAC/CONTAIN FOR
SALVAGE/DISPO.REMOVE IGN SOURCES.USE NONSPARK
TOOL/EQPMT.DETERMINE:EVACUATE/ISOLATE DEPENDING ON SPEC
FACTORS.OBSERVE ALL PPE.REPORT REQMTS(SUPPLE)
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====

== Handling and Storage =====

Handling and Storage Precautions:USE PROPER VENTI TO AVOID ACCUMULATION
OF DUST THAT CAN FORM IGN DUST/AIR MIXTURES.USE REASONABLE CARE.
Other Precautions:NONE SPECIFIED BY MANUFACTURER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE RESP PROT UNLESS ADEQUATE LOC EXHAU VENTI IS
PROVIDED OR AIR SAMPLING DATA SHOW EXPO ARE WITHIN RECOMMENDED EXPO
GUIDELINES.INUDSTRIAL HYGIENE PERSONNEL CA
N ASSIST IN JUDGING

ADEQUACY OF EXISTING ENGINEERING CONTROLS.DUST/MIST TYP RESP

Ventilation:LOCAL EXHAUST/GENE VENTILATION:RECOMMENDED.

Protective Gloves:NO SPECIAL PROTECTION NEEDED.

Eye Protection:SAFET GLASSES AS MINIMUM.

Other Protective Equipment:PRECAUTIONS FOR RM TEMP HDN LG;@ELEVATED
TEMPS/AEROSOL/SPRAY APPLICATIONS MAY REQUIRE ADDED PRECAUTIONS.

Work Hygienic Practices:USE GOOD HOUSEKEEPING PROCEDURES TO AVOID
ACCUMULATION OF DUST.WASH @MEALTIME/END OF SHIFT IS ADEQUATE.

Su
pplemental Safety and Health
SPILL:MAY APPLY.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:NA

Melt/Freeze Pt:M.P/F.P Text:N/DETERMINE

Decomp Temp:Decomp Text:NP

Vapor Pres:NA

Vapor Density:NA

Spec Gravity:4.80 @25C

pH:NA

Viscosity:NA

Evaporation Rate & Reference:NP

Solubility in Water:NONE.

Appearance and Odor:FINE POWDER CHARCOAL GRAY COLOR, ODORLESS.

Percent Volatiles by Volume:NP

Corrosion Rate:NP

===== Stability and Reac

tivity Data =====

Stability Indicator/Materials to Avoid: YES

OXIDIZING MATERIALS CAN CAUSE A REACTION.

Stability Condition to Avoid: NONE.

Hazardous Decomposition Products: THERM BREAKDOWN OF PROD DURING
FIRE/VERY HIGH HEAT CONDITIONS MAY EVOLVE HAZ DECOM
PROD: QUARTZ, SULFUR OXIDES, METAL OXIDE

===== Disposal Considerations =====

Waste Disposal Methods: COMPLETE INFO NOT YET AVAILABLE. CALL DOW
CORNING ENVIRO MGMT 517-496-6315 IF MORE INFO D
ESIRED. NO
CERCLA/SEC 313 TOXIC CHEM PRESENT.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.