View NSN Online: https://aerobasegroup.com/nsn/4210-01-144-0291

MINNESOTA MINING AND MFG CO -- FC-203CF LIGHT WATER BRAND AQUEOUS FILM FORMING FOAM -- 4210-01-144-0291

Product ID:FC-203CF LIGHT WATER BRAND AQUEOUS FILM FORMING FOAM MSDS Date:11/13/1995 FSC:4210 NIIN:01-144-0291 MSDS Number: CBSGZ === Responsible Party === Company Name: MINNESOTA MINING AND MFG CO Address:3M CTR City:SAINT PAUL (FORMALLY IN DETROITT, MI) Stat e:MN ZIP:55144-1000 Country:US Info Phone Num:612-733-1341/612-733-1110 Emergency Phone Num:612-733-1341 CAGE:76381 === Contractor Identification === Company Name: MINNESOTA MINING AND MFG CO, DBA 3M Address:3M CENTER BLDG 224-5S-04 Box:City:SAINT PAUL State:MN ZIP:55144-1000 Country:US Phone:866-556 5712 / 612-733-1110 CAGE:76381 Company Name: MINNESOTA MINING AND MFG CO PERFOMANCE CHEM AND FLUIDS DIV Address:3M CTR Box:City:SAINT PAUL State:MN ZIP:55144-1000 Country:US Phone:800-364-3577/651-73 7-6501 CAGE:28112 Ingred Name:WATER CAS:7732-18-5 RTECS #: ZC0110000 Fraction by Wt: 69-71% Other REC Limits:NONE RECOMMENDED Ingred Name: DIETHYLENE GLYCOL MONOBUTYL ETHER CAS:112-34-5 RTECS #:KJ9100000 Fraction by Wt: 19-21% Other REC Limits:NONE RECOMMENDED

Ingred Name:TRADE SECRET COMPONENT, ALKYL SULFATE SALT Fraction by Wt: 4-6% Other REC Limits:NONE RECOMMENDED AMIDE DERIVATIVE Fraction by Wt: 1-5% Other REC Limits:NONE RECOMMENDED

Ingred Name:ETHANOL, 2,2',2"-NITRILOTRI-; (TRIETHANOLAMINE) CAS:102-71-6 RTECS #:KL9275000 Fraction by Wt: 0.5-1.5% Other REC Limits:NONE RECOMMENDED ACGIH TLV:5 MG/M3

Ingred Name:TRADE SECRET COMPONENT-PERFLUOROALKYL SULFONATE SALT Fraction by Wt: 0.5-1.5% Other REC Limits:NONE RECOMMENDED

Ingred Name:1H-BENZOTRIAZOLE,METHYL-CAS:29385-43-1 Fraction by Wt: 0-0.1% Other REC Limits:NONE RECOMMENDED

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYE-MODERATE EYE IRRITATION. SKIN-MILD SKIN IRRITATION. INHALATION-SINGLE OVEREXPOSURE, ABOVE RECOMMENDED GUIDELINES, MAY CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION & IRRITATION (UPPER RESPIRATORY), BLOO D DISORDERS, BONE MARROW DEPRESSION, KIDNEY EFFECTS, LIVER EFFECTS, PULMONARY EDEMA. S

WALLOWED-NO LIKELY ROUTE EXPOSURE.

Explanation of Carcinogenicity:PRODUCT CONTAINS NO INGREDIENTS CURRENTLY CLASSIFIED AS CARCINOGENIC BY NTP, IARC OR OSHA.
Effects of Overexposure:EYE-REDNESS, SWELLING, PAIN, TEARING & HAZY VISION. SKIN-REDNESS, SWELLING, & ITCHING. INHALATION-HEADACHE, DIZZINESS, DROWSINESS, INCOORDINATION, SLOWED REACTION TIME, SLURRED SPEECH, GIDDINESS & UNC ONSCIOUSNESS. SORENESS OF THE NOSE & THROAT, COUGHING AND SNEEZING.

Medical Cond Aggravated by Exp

osure:NONE SPECIFIED BY MANUFACTURER.

First Aid:EYES: IMMEDIATELY FLUSH WITH WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION. SKIN: FLUSH SKIN WITH LARGE AMOUNTS OF WATER. INHALATION: REMOVE PERSON TO FREAH AIR. IF SYMPTOMS CONTINUE, CALL A PH YSICIAN. INGESTION: DRINK TWO GLASSES OF WATER. CALL A PHYSICIAN IMMEDIATELY.

Flash Point Met hod:SCC Flash Point:NONE Extinguishing Media:PRODUCT IS A FIRE EXTINGUISHING AGENT. DLA-HMIS: USE MEDIA APPROPRIATE FOR SURROUNDING FIRE. Fire Fighting Procedures:NOT APPLICABLE.

Unusual Fire/Explosion Hazard:SEE HAZARDOUS DECOMPOSITION PRODUCTS SECTION FOR PRODUCTS OF COMBUSTION.

Spill Release Procedures:OBSERVE PRECAUTIONS FROM OTHER SECTION. COVER WITH ABSORBENT MATERIAL. COLLECT SPILLED MATERIAL. CLEANUP RESIDU E

WITH WATER. PLACE IN U. S. DOT APPROVED CONTAINER AND SEAL. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

 Handling and Storage Precautions:STORE IN A COOL PLACE. STORE AWAY FROM HEAT. STORE OUT OF DIRECT SUNLIGHT. KEEP CONTAINER DRY. KEEP CONTAINER IN WELL- VENTILATED AREA.
 Other Precautions:KEEP CONTAINER TIGHTLY CLOSED.

======= Exposure Controls/Personal Protection ==========

Respiratory Prote

ction: AVOID BREATHING OF VAPORS, MISTS OR SPRAY.

SELECT ONE OF THE FOLLOWING NIOSH APPROVED RESPIRATORS BASED ON AIRBORNE CONCENTRATION OF CONTAMINANTS: HALF MASK ORGANIC VAPOR RESPIRATOR WITH DUST.MIST PRE FILTER.

Ventilation: USE WITH ADEQUATE DDILUTION VENTILATION.

Protective Gloves: BUTYL RUBBER GLOVES RECOMMENDED.

Eye Protection:WEAR VENTED GOGGLES.

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices: WASH EXPOSED AREAS THOROUGHLY WITH SOAP & WATE

R. WASH HANDS AFTER HANDLING & BEFORE EATING. Supplemental Safety and Health

HCC:B3 Boiling Pt:B.P. Text:212F,100C Vapor Pres:17 Vapor Density:0.77 Spec Gravity:1 pH:8.50 Evaporation Rate & amp; Reference: