

CRC CHEMICALS U.S.A./CRC INDUSTRIES, INC. -- 5018, 5018T LECTRA MOTIVE (AEROSOL) --
6850-01-244-9614

===== Product Identification =====

Product ID:5018, 5018T LECTRA MOTIVE (AEROSOL)
MSDS Date:05/26/1994
FSC:6850
NIIN:01-244-9614
MSDS Number: CBSJX
=== Responsible Party ===
Company Name:CRC CHEMICALS U.S.A./CRC INDUSTRIES, INC.
Address:885 LOUIS DRIVE
City:WARMINSTER
State:PA
ZIP:18974-2820
Country:US
Info Phone Num:215-674-4300
Emergency Phone Num:800-424-9300(CHEMTREC)
Preparer's Name:ADAM SELISKER
CAGE:10136
=== Contractor Identification ===
Company Name:CRC INDUSTRIES, INC.
Address:885 LOUIS DRIVE
Box:City:WARMINSTER
State:PA
ZIP:18974-2869
Country:US
Phone:215-674-4300/ 800-521-3168
CAGE:023V4
Company Name:CRC INDUSTRIES, INC.
Address:885 LOUIS DRIVE
Box:City:WARMINSTER
State:PA
ZIP:18974-2820
Country:US
Phone:215-674-4300/800-424-9300
CAGE:10136

===== Composition/Informat

ion on Ingredients =====

Ingred Name:METHYLENE CHLORIDE (SARA 313) (CERCLA) (DICHLOROMETHANE)
CAS:75-09-2
RTECS #:PA8050000
Fraction by Wt: 1-20%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:500 PPM; Z-2
ACGIH TLV:50 PPM, A2; 9596
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:PERCHLOROETHYLENE (TETRACHLOROETHYLENE) (SARA 313) (CERCLA)
CAS:127-18-4
RTECS #:KX3850000
Fraction by Wt: 70-100%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM, Z-2
ACGIH TLV:25PPM/100STEL,A3; 96
EPA
Rpt Qty:100 LBS
DOT Rpt Qty:100 LBS

Ingred Name:CARBON DIOXIDE
CAS:124-38-9
RTECS #:FF6400000
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:5000 PPM
ACGIH TLV:5000PPM/30000STEL;96

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES
Health Hazards Acute and Chronic:ACUTE:INHAL:HEADACHES, DIZZINESS,

ANESTHESIA, UNCONSCIOUSNESS. EYE:CAUSES PAIN, SOME IRRIT.
SKIN:IRRIT ON REPEATED EXPOSURE. CHRONIC:REPEATED OVEREXPO HAVE
CAUSED LIVER & KIDNEY EFFECTS IN ANIMALS.

Explanation of Carcinogenicity:PER
MSDS:NTP/IARC/OSHA:YES.TETRACHLOROETHYLENE,DICHLOROMETHANE.HMIS:OSH
A-NONE.NTP/IARC-DICHLOROMETHANE,(SEE OTHER PRECA)
Effects of Overexposure:HEADACHES, DIZZINESS, ANESTHESIA,
UNCONSCIOUSNESS, EYE PAIN, IRRIT. SKIN IRRIT.
Medical Cond Aggravated by Exposure:RISK TO YOUR HEALT

H DEPEDNS ON
DURATION & LEVEL OF EXPOSURE.

===== First Aid Measures =====

First Aid:IF SYMPTOMS PERSIST CALL PHYSICIAN. INHAL:REMOVE TO FRESH AIR.APPLY ARTIFICIAL RESPIRATION IF NECESSARY. EYE:FLUSH W/LG AMTS OF WATER FOR 15MINS. SKIN:REMOVE CONTAMIN CLOTH.WASH AREA W/SOAP/WATER. ING EST:DO NOT INDUCE VOMIT.CALL PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:NONE
Autoigni
tion Temp:Autoignition Temp Text:NP
Lower Limits:NA
Upper Limits:NA
Extinguishing Media:WATER FOG.
Fire Fighting Procedures:NONE SPECIFIED BY MANUFACTURER.
Unusual Fire/Explosion Hazard:AEROSOL CONTAINERS MAY EXPLODE WHEN HEATED ABOVE 120F.

===== Accidental Release Measures =====

Spill Release Procedures:USUALLY NOT A PROBLEM W/AEROSOLS. AREA SHOULD BE VENTILATED & AN ABSORBENT USED TO PICK UP EXCESS MATL.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL DRY PLACE.VAPORS ARE HEAVIER THAN AIR.DO NOT USE IN CONFINED SPACE W/OUT ADEQUATE VENTILATION.USE BREATHING APPARATUS IF NECESSARY.
Other
Precautions:CARCINOGEN:NTP-TETRACHLOROETHYLENE;IARC-TETRACHLOROETHY LENE NOT CLASSIFIABLE AS HUMAN CARCI.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:ABOVE TLV USE SELF-CONTAINED BR

EATING

APPARATUS.

Ventilation:MAINTAIN VAPOR CONCENTRATION BELOW TLV.USE MECHANICAL MEANS IF NECESSARY.

Protective Gloves:SOLVENT RESISTANT GLOVES.

Eye Protection:SAFETY GLASSES.

Other Protective Equipment:NOT NORMALLY REQUIRED W/AEROSOL PRODUCT USAGE.

Work Hygienic Practices:WASH CONTAMIN CLOTH BEF REUSE.

Supplemental Safety and Health

PER MSDS:GOOD SOLVENT FOR MANY ORGANIC MATLS.

===== Physical/Chemical Properties =====

HCC:V2

Boiling Pt:B.P. Text:>25

0F,>121C

Melt/Freeze Pt:M.P/F.P Text:ND

Decomp Temp:Decomp Text:NP

Vapor Pres:ND

Vapor Density:ND

Spec Gravity:1.60 @25C

pH:NA

Viscosity:NP

Evaporation Rate & Reference:RAPID, REF NOT GIVEN

Solubility in Water:SLIGHT SOLUBILITY

Appearance and Odor:COLORLESS LIQUID, IRRIT ODOR @HIGH CONCENTRATIONS.

Percent Volatiles by Volume:100

Corrosion Rate:NP

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

AVOID STORAGE IN ALUMINUM CONTAINERS OR CONTACT W/ALUMINUM &/OR ZINC PRODUCTS.

Stability Condition to Avoid:AVOID OPEN FLAMES, ARCS OR HIGH TEMPERATURES.

Hazardous Decomposition Products:THERMAL-HYDROGEN CHLORIDE, CHLORINE, & SOME PHOSGENE.

===== Disposal Considerations =====

Waste Disposal Methods:ALL USED & UNSED PRODUCT SHOULD BE DISPOSED OF IN CONFORMANCE W/LOCAL, STATE AND FEDERAL REGULATIONS.CONTAINS CHEM SUBJ TO RELEASE REPORTING UNDER SEC 313 OF SARA TITLE III:DIC

HLOROMETHANE 1-20%;TETRA CHLOROETHYLENE 70-100%.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.