

ULTRALIFE BATTERIES INC -- HIGH RATE LITHIUM MANGANESE DIOXIDE CELLS/BATTERIES --
6135-01-407-8252

===== Product Identification =====

Product ID:HIGH RATE LITHIUM MANGANESE DIOXIDE CELLS/BATTERIES

MSDS Date:02/07/1995

FSC:6135

NIIN:01-407-8252

MSDS Number: CBTKK

=== Responsible Party ===

Company Name:ULTRALIFE BATTERIES INC

Address:1350 RT 88 S

Box:622

City:NEWARK

State:NY

ZIP:14513

Country:US

Inf

o Phone Num:315-332-7100

Emergency Phone Num:315-332-7100

CAGE:0UU59

=== Contractor Identification ===

Company Name:BATTERY OUTLET OF HAMPTON INC

Address:2815 GEORGE WASHINGTON HWY

Box:City:TABB

State:VA

ZIP:23602

Country:US

Phone:804-867-8280

CAGE:0FTM0

Company Name:ULTRALIFE BATTERIES INC

Address:2000 TECHNOLOGY PARKWAY

Box:City:NEWARK

State:NY

ZIP:14513

Country:US

Phone:800-424-9300

CAGE:0UU59

===== Composition/Information on Ingredients =====

Ingred Name:LITHIUM (LI)

CAS:

7439-93-2

RTECS #:OJ5540000

Other REC Limits:NONE RECOMMENDED

Ingred Name:MANGANESE DIOXIDE (MNO2)

CAS:1313-13-9

RTECS #:OP0350000

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG MN/M3 CEILING

ACGIH TLV:5 MG MN/M3

Ingred Name:PROPYLENE CARBONATE (C3H6CO3)

CAS:108-32-7

RTECS #:FF9650000

Other REC Limits:NONE RECOMMENDED

Ingred Name:1,2-DIMETHOXYETHANE (CH3OCH2CH2OCH3)

CAS:110-71-4

RTECS #:KI1451000

Other REC Limits:NONE RECOMMENDED

Ingred Name:TETRAHYDROFURAN (CERCLA) (C4H8O)

CAS:109-99-9

RTE

CS #:LU5950000

Other REC Limits:NONE RECOMMENDED

OSHA PEL:200 PPM

ACGIH TLV:200 PPM/250STEL;9596

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:LITHIUM PERCHLORATE (LICLO4)

CAS:7791-03-9

Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:LI:HIGHLY FLAMM/CORR.RXS VIGOROUSLY
W/WATER EMTTNG FLAMM GA

S.MN02:TOX,IRRIT,OXIDZING AGENT,HARMFUL BY
INGEST.PROPYLENE CARBONATE:CLEAR COLORLESS LIQ,MAY BE HARMFUL IF
INHAL,INJECT,SKIN ABSORPTION.CAU SE EYE IRRIT,SKIN
IRRIT.1,2-DIMETHOXYEHTANE:HIGHLY FLAMM COLORLESS LIQ,HARMFUL BY
INHAL,INGEST,SKIN ABSORPT (SIGN/SYMPT)

Effects of Overexposure:HEALTH HAZ:TETRAHYDROFURAN:FLAMM COLORLESS LIQ
W/CHARACTERISTIC ODOR.HARMFUL BY INGEST,INHAL,SKIN CONTACT CAUSING
HEAD,DIZZ,NAU.LITHIUM PERCHLOORATE:COLORLESS SOLID,HARMFUL/IRRIT IF
INGES

T,IRRIT SKIN/E YE/RESP SYS.EXPLO IN CONTACT W/COMBUSTIBLE
MATL.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:SHOULD LIQ ELECTROLYTE COME INTO DIRECT CONTACT W/SKIN IT
SHOULD BE REMOVED BY FLUSHING W/WARM SOAPY WATER.

===== Fire Fighting Measures =====

Flash Point:NP

Autoignition Temp:Autoignition Temp Text:NP

Lower Limits:NP

Upper Limits:NP

Extinguis

hing Media:DRY POWDER EXT BASED ON GRAPHITE(LITH-X)/OTHER
SUITABLE EXT DESIGNED FOR ALKALI METAL FIRE FIRES.DON'T USE
H2O/CO2/HALON

Fire Fighting Procedures:NONE SPECIFIED BY MANUFACTURER.

Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.

===== Accidental Release Measures =====

Spill Release Procedures:IN EVENT OF CELL LEAKING IT SHOULD BE
CAREFULLY ISOLATED FROM ANY OTHER CELLS/PLACED INSIDE POLYETHENE
BAG.ULTRALIFE BATT SHOULD BE CONTACTED FOR ADVICE ON DISPO.LEADAGE
OCCURS FROM CELL WHILST CONNEC TED TO PRINTED CIRCUIT BOARD IT
SHOULD BE (SUPP)

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:PROD SHOULDN'T BE OPEN/INCINER SINCE
CONTAINS INGRED S THAT WOULD BE EXPO COULD BE HARMFUL.STORE IN WELL
VENTI DRY AREA @TEMP