

PRATT AND LAMBERT, INC; INDUSTRIAL COATINGS DIV -- ENAMEL, ALKYD, GLOSS, LO VOC CN
BLUE 15044, ID 774504 -- 8010-00-298-2302

=====
Product Identification
=====

Product ID:ENAMEL, ALKYD, GLOSS, LO VOC CN BLUE 15044, ID 774504

MSDS Date:12/21/1996

FSC:8010

NIIN:00-298-2302

MSDS Number: CBTNC

=== Responsible Party ===

Company Name:PRATT AND LAMBERT, INC; INDUSTRIAL COATINGS DIV

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency Phone Num:716-873-6000/DOT: 800-255-3924

Preparer's Name:W A ELLSION

CAGE:61196

=== Contractor Identification ===

Company Name:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

=====
Composition/Information on Ingredients
=====

Ingred Name:N-BUTYL ACETATE (SOLVENT) (VAPOR PRESSURE 10 MM HG @ 20C)

(LFL 1.7; UFL 7.6)

CAS:123-86-4

RTECS #:AF735000

0

Fraction by Wt: 10.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:150 PPM;STEL 200 PPM

ACGIH TLV:150 PPM;STEL 200 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:XYLENE (SOLVENT) (SARA III) (VAPOR PRESSURE 5 MM HG @ 20C)

(LFL 1.0; UFL 7.0)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 5.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM;STEL 150 PPM

ACGIH TLV:100 PPM;STEL 150 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:METHYL ISOAMYL KETONE (SOLVENT)

2-3

RTECS #:MP3850000

Fraction by Wt: 5.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:50 PPM; 240 MG/M3

ACGIH TLV:50 PPM; 240 MG/M3

Ingred Name:MINERAL SPIRITS (SOLVENT) (VAPOR PRESSURE 2 MM HG @ 20C)

(LFL: 1.0 UFL: 7.0)

CAS:64475-85-0

RTECS #:PY8240000

Fraction by Wt: