View NSN Online: https://aerobasegroup.com/nsn/8010-01-419-1169

Product ID:MIL-C-22750F, ACTIVATOR, PART B UO-143 MSDS Date:03/07/1996 FSC:8010 NIIN:01-419-1169 Kit Part:Y MSDS Number: CBVLF === Responsible Party === Company Name: CRAWFORD LABORATORIES, INC. Address:4165 SOUTH EMERALD AVENUE City:CHICAGO State:IL ZIP:60609 Country:US Inf o Phone Num:312-376-7132 Emergency Phone Num:800-424-9300 Preparer's Name: DAVID SCHMETTERER CAGE:DO165 === Contractor Identification === Company Name: CRAWFORD LABORATIES, INC Address:4165 SOUTH EMERALD AVENUE City:CHICAGO State:IL ZIP:60609 Phone:800-424-9300 CHEMTREC CAGE:DO165 Company Name: CRAWFORD LABORATORIES, INC Address:4165 SOUTH EMERALD AVENUE Box:City:CHICAGO State:IL ZIP:60609 Country:US Phone:312-376-7132 CAGE:5V430

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III) (VP = 71.2 MMHG) CAS:78-93-3 RTECS #:EL6475000 Fraction by Wt: 40.0% OSHA PEL:200 PPM/300 STEL ACGIH TLV:200 PPM/300STEL 9192 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:NONYL PHENOL (VP = 0.9 MMHG) CAS:84832-15-3 Fraction by Wt: 40.0% Other REC Limits:NONE RECOMMENDED

Ingred Name:MXDA (METAXYLENE DIAMINE) CAS:1477-55-0 RTECS #:PF8970000 Fraction by Wt: 20.0% Other REC Limits:NONE RECOMMENDED ACGIH TLV:0.1 MG/M3

===

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:REPEATED/PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS ASSOCIATED W/PERMANENT BRAIN/NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL O R FATAL. PROLONGED OVEREXPOSURE (INHAL)MAY CAUSE DELAYED LUNG DISEASE.

Ex

 planation of Carcinogenicity:MAY CONTAIN TRACE AMTS OF SOME CHEM KNOWN TO THE STATE OF CATO BE CARCINOGENS OR REPRODCTIVE TOXINS.
Effects of Overexposure:OVEREXPOSURE MAY PRODUCE VARIOUS EFFECTS. ACUTE TOXICITY (HEADACHE, DIZZINESS, NAUSEA, LOSS CONSCIOUSNESS. SEVERE EYE IRRITATION POSSIBLY RESULTING PERMANENT DAMAGE. IRRITATED MUCOUS MEMBRANES. VOMITI NG FROM INGESTION. SKIN DEFATTING/DRYING. SENSITIZATION AFTER REPEATED CONTACT.

======= First Aid Measures

First Aid:EYE: FLUSH W/PLENTY CLEAN H20 15 MIN, LIFTING LIDS, GET MED ATTN. INHAL: GET FRESH AIR, PROVIDE OXYGEN IF BREATH DIFFICULT. GIVE ARTIF RESP IF NOT BREATHING. GET MED ATTN. KEEP VICTIM WARM/QUIET. NEVE R GIVE UNCONS PERSON LIQ. INGEST: CALL DR. IMMED. DON'T INDUCE VOMIT. IF VOMIT SPONTANEOUSLY, KEEP HEAD BELOW HIPS. SKIN: FLUSH W/H20 WHILE REMOVING CONTAM CLOTHES/SHOES. IF IRRIT PERSIST, GET MED AID

======= Fire Fighting

Flash Point Method:SCC Flash Point:22.0F,-5.6C Lower Limits:1.8 Extinguishing Media:FOAM, CO2, OR DRY CHEMICAL Fire Fighting Procedures:WATER MAY BE USED TO KEEP EXPOSED CONTAINERS COOL & KEEP FLAMMABLE STRUCTURE WETDON'T ENTER FIRE AREA WITHOUT PROPER PROTECTION, HAZARDOUS DECOMP MAY BE PRESENT Unusual Fire/Explosion Hazard:WATER PRESSURE MAY SPREAD A FLAMMABLE LIQUID FIRE. SEALED CONTAINERS MAY EXPLODE IF OVER HEATED.

============== Accidental

Release Measures =============

Spill Release Procedures:WARNING - FLAMMABLE. ELIMINATE ALL IGNITION SOURCES. HANDLING EQUIPMENT MUST BE GROUNDED TO PREVENT SPARKING. SOAK UP WITHABSORBENT & PLACE IN NON-LEAKING CONATINERS. SEAL TIGHTLY FOR PROPER DISPOSAL.

Handling and Storage Precautions: TREAT AS A HAZARDOUS-FLAMMABLE MATERIAL. KNOW APPLICABLE D.O.T. REG. BEFORE ATTEMPTING TO TRANSPORT THIS MATERIA

L.

Other Precautions:WARNING: HOT ORGANIC CHEMICAL VAPORS OR MISTS ARE SUSCEPTIBLE TO SUDDEN SPONTANEOUS COMBUSTION WHEN MIXED W/AIR. IGNITION MAY OCCUR @ TEMPS BELOW THOSE PUBLISHED AS AUTOIGNITION/IGNITION TEMPS. IGNITI ON TEMPS DECREASE W/INCREASING VAPOR\*

======= Exposure Controls/Personal Protection ==========

Respiratory Protection: IMPORTANT-MUST PROVIDE ADEQUATE VENT TO MAINTAIN VAPOR CONCENTRATE BELOW ESTAB- LISHED TLV LIMIT AS GIVEN BY OSHA. IN MORE

CONFINED AREAS A NIOSH/MSHA APPROVED RESPIRATOR EQUIPPED WITH ORGANIC VAPOR C ARTRIDGE SHOULD BE WORN.

Ventilation: MUST PROVIDE ADEQUATE VENTILATION, SEE PARAGRAPH ABOVE. Protective Gloves: USE RUBBER GLOVES

Eye Protection: APPROVED SAFETY GOGGLES &/OR FACE SHIELD

Other Protective Equipment: HAVE EYE BATH & SAFETY SHOWER AVAILABLE. Supplemental Safety and Health

VOLUME AND VAPOR/AIR CONTACT TIME AND ARE INFLUENCED BY PRESSURE CHANGES. IGNITION MAY OCCUR AT TYPICAL ELEVATED TEMPERATURE PROCE SS

CONDITIONS, ESPECIALLY IN PROCESS OPERATING UNDER VACUUM IF SUBJECT ED TO SUDDEN INGRESS OF AIR, OUTSIDE PROCESS EQUIPMENT OPERATING UNDER ELEVATED PRESSURE IF SUDDEN ESCAPE OF VAPORS/MIST

Boiling Pt:B.P. Text:175 TO 545F Vapor Density:>AIR Spec Gravity:0.89 Viscosity:20 CPS Evaporation Rate & amp; Reference:4.82 X N-BUTYL ACETATE Solubility in Water:SLIGHT Appearance and Odor:CLEAR LIQUID Percent Volatiles by V olume:44.4

Stability Indicator/Materials to Avoid:YES OXIDIZING AGENTS & STRONG ALKALIES. NOT CORROSIVE TO METAL. Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAMES, STRONG ALKALIES, & OXIDIZING AGENTS.

Hazardous Decomposition Products:INCOMPLETE COMBUSTION OR PRODUCTS LIKE THIS MAY GENERATE HIGHLY POISONOUS CARBON MONOXIDE AND OTHER TOXIC GASES

Waste Disposal Methods:DISPOSAL MUST BE IN ACCORDANCE WITH CURRENT LOCAL, STATE & FEDERAL REG. CONTACT AN APPROVED DISPOSAL FACILITY

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document shoul d seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.