

BLACKHAWK AUTOMOTIVE INC -- AWS CLASS E7018 (84-053) (COVERED ELECTRODE FOR SMAW)
-- 3439-01-039-6408

===== Product Identification =====

Product ID:AWS CLASS E7018 (84-053) (COVERED ELECTRODE FOR SMAW)

MSDS Date:09/15/1988

FSC:3439

NIIN:01-039-6408

MSDS Number: CCCDL

=== Responsible Party ===

Company Name:BLACKHAWK AUTOMOTIVE INC

Box:1606

City:WAUKESHA

State:WI

ZIP:53187

Country:US

Info Phone Num:

414-542-6611

Emergency Phone Num:414-542-6611

CAGE:EO393

=== Contractor Identification ===

Company Name:BLACKHAWK AUTOMOTIVE INC

Box:1606

City:WAUKESHA

State:WI

ZIP:53187

Country:US

Phone:414-542-6611

CAGE:EO393

Company Name:NAPA, A DIVISION OF LINCOLN AUTOMOTIVE

Address:ONE LINCOLN WAY

Box:City:ST. LOUIS

State:MO

ZIP:63120-1578

Country:US

Phone:414-255-5520

CAGE:050Q3

===== Composition/Information on Ingredients =====

Ingred Name:30-40

CAS:7439-89-6

RTECS #:NO4565500

Other R

EC Limits:NONE RECOMMENDED

Ingred Name:MANGANESE (SARA 313)
CAS:7439-96-5
RTECS #:OO9275000
Fraction by Wt: 1-11%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:C, 5 MG/M3 (FUME)
ACGIH TLV:0.2 MG/M3; 9596

Ingred Name:TITANIUM DIOXIDE
CAS:13463-67-7
RTECS #:XR2275000
Fraction by Wt: 2-12%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9596

Ingred Name:SILICA DIOXIDE
CAS:112945-52-5
RTECS #:VV7310000
Fraction by Wt: 1-11%
Other REC Limits:NONE RECOMMENDED
OSHA P
EL:6 MG/M3
ACGIH TLV:10 MG/M3

Ingred Name:SODIUM SILICATE
CAS:1344-09-8
Fraction by Wt: 2-12%
Other REC Limits:NONE RECOMMENDED

Ingred Name:POTASSIUM SILICATE
CAS:1312-76-1
Fraction by Wt: 2-12%
Other REC Limits:NONE RECOMMENDED

Ingred Name:FELDSPAR
CAS:68476-25-5
Fraction by Wt: 1-11%
Other REC Limits:NONE RECOMMENDED

Ingred Name:IRON OXIDE
CAS:1309-38-2
RTECS #:OM4800000
Fraction by Wt: 1-11%
Other REC Limits:NONE RECOMMENDED

Ingred Name:CALCIUM CARBONATE (MARBLE) (LIMESTONE)
CAS:1317-65-

3
RTECS #:EV9580000
Fraction by Wt: 18-28%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9596

Ingred Name:FLUORSPAR
CAS:14542-23-5
Fraction by Wt: 10-20%
Other REC Limits:NONE RECOMMENDED

Ingred Name:POTASSIUM HYDROXIDE (CERCLA)
CAS:1310-58-3
RTECS #:TT2100000
Fraction by Wt: 0.1-1%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:C 2 MG/M3
ACGIH TLV:C 2 MG/M3; 9596
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

===== Hazards Identification =====
=====

LD50 LC50 Mixture:TLV-TWA WELD FUME:5MG/M3.
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:WELDING FUMES/GASES CAN BE DANGEROUS
TO HEALTH.SHORT-TERM(ACUTE)OVEREXPO TO WELDING FUMES MAY RESULT IN
DISCOMFORT SUCH AS DIZZ,NAU,DRYNESS/IRRIT OF NOSE/THROAT/EYES.LONG
TERM:SIDEROSIS(IRON DEPOSIT I N LUNGS)WHICH AFFECT PULM
FUNCTION.ARC RAYS CAN INJURE EYE/BURN SKIN.ELECTRIC SHOC
K CAN KILL.
Explanation of Carcinogenicity:PER MSDS:CARCINOGENICITY:NO FOR ALL
INGREDIENTS PRESENT.
Effects of Overexposure:DIZZINESS, NAUSEA, DRYNESS OR IRRIT OF
NOSE/THROAT/EYES. ARC RAYS:INJURE EYE, BURN SKIN. ELECTRIC SHOCK
CAN KILL. SIDEROSIS (RION DEPOSIT IN LUNGS) WHICH AFFECTS PULM
FUNCITON.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:CALL FOR MEDICAL AID. EMPLOY FIRST

AID TECHNIQUES RECOMMENDED
BY AMERICAN RED CROSS.

===== Fire Fighting Measures =====

Flash Point:NA
Autoignition Temp:Autoignition Temp Text:NA
Lower Limits:NA
Upper Limits:NA
Extinguishing Media:NONE SPECIFIED BY MANUFACTURER.
Fire Fighting Procedures:NONE SPECIFIED BY MANUFACTURER.
Unusual Fire/Explosion Hazard:NON-FLAMMABLE. WELDING ARC & SPARKS CAN
IGNITE COMBUSTIBLES. REFER TO AMERICAN NATL STD 249.1 FOR FIRE
PREVENTION DURING WELDING.

===== Accidental Release Measures =====

Spill Release Procedures:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:READ/UNDERSTAND MFG INSTRUCT/PRECAUT
LABEL.FILTER LENSES:RULE OF THUMB:START W/SHADE TOO DARK TO SEE
WELD ZONE,THEN GO TO NEXT LIGHTER GIVES SUFF VIEW
Other Precautions:RECOMMENDED WAY TO DETERMINE FUME/GAS COMP/QUANT
WORKERS EXPO:TAKE AIR SMPL INSIDE WELDER HELME
T/WORKER BREATH
ZONE.ANSI/AWS F1.1 AVAILABLE FROM AMER WELD SOC,POB 351040,MIA,FL
33135.SEE AMER NAT STD Z-49.1 & OSHA 29CFR 1910.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE RESPIRABLE FUME RESPIRATOR OR AIR SUPPLIED
RESP WHEN WELDING IN CONFINED SPACE OR WHERE LOCAL EXHAUST OR
VENTILATION DOES NOT KEEP EXPOSURE BELOW TLV.
Ventilation:USE ENOUGH VENTI,LOC EXHASUT @ARC OR BOTH TO KEEP
FUMES/GASES BELOW TLV IN WORKER BREATH
ZONE/GENERAL AREA.
Protective Gloves:WELDER GLOVES.
Eye Protection:FCSHIELD W/FILT LENSES(SEE HNDLG PRCAUT)
Other Protective Equipment:HELMET;SCREENS/FLASH GOGG IF NECESSARY TO
SHIELD OTHERS.HEAD/HAND/BODY PROT FROM RADIATION/SPARK/ELECTR
SHOCK.
Work Hygienic Practices:TRAIN WELDER TO KEEP HEAD OUT OF FUMES/NOT
TOUCH LIVE ELCTRICAL PARTS/INSULATE HIMSELF FROM WORK/GROUND.
Supplemental Safety and Health
HAZ DECOMP PROD:USED.ALSO COAT ON METAL BEING WELDED,#OF
WELDER/VOL,QUAL/AMT

OF VENTI, POSITION OF WELDER HEAD W/FUME
PLUME, PRESENCE OF ATM CONTAMIN. DECOMP PROD: ORIGINATING FROM
VOLATIZ/RX/OXIDAT OF MA TL+BASE METAL, COAT, ETC. PRESENT AS COMPLEX
CMPDS-NOT METALS. REASONABILITY: FLOURIDES, FE
OXIDES, MN, SI, CO, CO₂, OZONE, NOX.

===== Physical/Chemical Properties =====

HCC: V7

Boiling Pt: B.P. Text: NA

Melt/Freeze Pt: M.P/F.P Text: NA

Decomp Temp: Decomp Text: NA

Vapor Pres: NA

Vapor Density: NA

Spec Gravity: NA

pH: NA

Viscosity: NA

Evaporation Rate &

amp; Reference: NA

Solubility in Water: NA

Appearance and Odor: NA

Percent Volatiles by Volume: NA

Corrosion Rate: NA

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

NONE SPECIFIED BY MANUFACTURER.

Stability Condition to Avoid: NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products: WELD FUME/GAS CAN'T BE CLASSIFIED

SIMPLY. COMPO/QUANT DEPENDENT UPON METAL BEING WELD/PROCEDURES
FOLLOWED/ELECTRODE(SUPP)

=====

== Disposal Considerations =====

Waste Disposal Methods: NONE SPECIFIED BY MANUFACTURER. HMIS: DISPOSE OF
ANY GRINDING DUST OR WASTE RESIDUES IN ACCORDANCE W/EPA OR LOCAL
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all

liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.