Product ID:OATEY ALL PURPOSE CEMENT MSDS Date:10/20/1995 FSC:8040 NIIN:01-307-0504 **MSDS Number: CCCHT** === Responsible Party === Company Name:OATEY CO Address:4700 W. 160TH STREET Box:35906 City:CLEVELAND State:OH ZIP:44135-2632 Country:US Info Phone Num:216-267-7100 Emergency Phone Num:216-267-7100 OR 303-6 23-5716 COLLEC CAGE:53472 === Contractor Identification === Company Name: OATEY CO Address:4700 WEST 160TH STREET Box:35906 City:CLEVELAND State:OH ZIP:44135 Country:US Phone:216-267-7100/303-623-5716 CAGE:53472

Ingred Name:CHLORINATED POLYVINYL CHLORIDE CAS:68648-82-8 Fraction by Wt: 3-7% Other REC Limits:NONE RECOMMENDED

Ingred Name:TETRAHYDROFURAN (CERCLA) CAS:109-99-9 RTECS #:LU5950000 Fraction by Wt: 30-45% Other REC Lim its:NONE RECOMMENDED OSHA PEL:200 PPM ACGIH TLV:200 PPM/250STEL;9596 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:ACETONE (SARA 313) (CERCLA) CAS:67-64-1 RTECS #:AL3150000 Fraction by Wt: 0-5% Other REC Limits:NONE RECOMMENDED OSHA PEL:1000 PPM ACGIH TLV:750PPM/1000STEL;9596 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA 313) (CERCLA) CAS:78-93-3 RTECS #:EL6475000 Fraction by Wt: 25-40% Other REC Limits:NONE RECOMMENDED OSHA PEL:200 PPM ACGIH TLV:200 PPM/300STEL;9596 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:CYCLOHEXANONE (CERCLA) CAS:108-94-1 RTECS #:GW1050000 Fraction by Wt: 11-16% Other REC Limits:NONE RECOMMENDED OSHA PEL:S, 50 PPM ACGIH TLV:S, 25 PPM; 9596 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:SILICA, AMORPHOUS (FUMED) CAS:112945-52-5 RTECS #:VV7310000 Fraction by Wt: 1-4% Other REC Limits:NONE RECOMMENDED OSHA PEL:6 MG/M3 ACGIH TLV:10 MG/M3

Ingred Name:POLYVINYL CHLORIDE CAS:9002-86-2 RT ECS #:KV0350000 Fraction by Wt: 8-12% Other REC Limits:NONE RECOMMENDED

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: TARGET ORGANS: EYE, SKIN, KIDNEY, LUNGS, LIVER, CENTRAL NERVOUS SYSTEM. SKIN-CHRONIC CONTACT MAY LEAD TO IRRITATION & DERMATITIS. CHRONIC EXPOSURE MAY CAUSE DERMATITIS. EYE-VAPOR OR DIRECT CONTACT MAY CAUSE IRRITATION. INGESTION-MAY BE ASPIRATED INTO THE LUNGS OR CAUSE SYSTEMIC EFFECTS DESCRIBED UNDER INHALATION. Explanation of Carcinogenicity:NOT CARCINOGENIC. Effects of Overexposure: INHALATION-MAY CAUSE IRRITATION OF MUCOUS MEMBRANES, NOSE & THROAT, HEADACHE, DIZZINESS, NUASEA, NUMBNESS OF THE EXTREMITIES AND NARCOSIS IN HIGH CONCENTRATIONS. MAY CAUSE CNS DEPRESSION & LIVER DAMAG E IN ANIMALS, AND HIGH CONCENTRATIONS HAVE CAUSED RETARDATION OF FETAL DEVELOPMENT IN RA TS. Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER. 

First Aid:SKIN-WASH THOROUGHLY WITH SOAP AND WATER. SEEK MEDICAL ATTENTION FOR IRRITATION. EYES-MOVE TO FRESH AIR & IRRIGATE EYES WITH WATER FOR 15 MIN. SEEK MEDICAL ATTENTION. INHALATION-MOVE TO FRESH AIR. IF BREATHING IS DIFFICULT, GIVE IXYGEN. IFNOT BREATHING, GIVE ARTIFICIAL RESPIRATION. CALL POISON CONTROL OR PHYSICIAN. INGESTION

-DRINK WATER & CALL POISON CONTROL OR PHYSICIAN. AVOID ALCOHOL BEVERAGES.

Flash Point Method:PMCC Flash Point:5F,-15C Lower Limits:1.8 Upper Limits:11.8 Extinguishing Media:FOR SMALL FIRES: USE DRY CHEMICAL, CARBON DIOXIDE, WATER OR FOAM EXTINGUISHER. Fire Fighting Procedures:FOR LARGE FIRES: EVACUATE AREA AND CALL FIRE DEPARTMENT IMMEDIATELY. Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.

=======

Spill Release Procedures: VENTILATE AREA, STOP LEAK. IF IT CAN BE DONE WITHOUT RISK. TAKE UP WITH SAND, EARTH OR OTHER NON-COMBUSTIBLE
ABSORBING MATERIAL. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.
======================================
Handling and Storage Precautions:KEEP AWAY FROM HEAT, SPARKS, AND FLAMES. STORE IN COOL, DRY PLACE. CONTAINER EVEN EMPTY WILL RETAIN RESIDUE AND VAP
ORS. Other Precautions:NONE
========= Exposure Controls/Personal Protection ====================================
Respiratory Protection:NIOSH-APPROVED CANNISTER RESPIRATOR IN ABSENCE OF ADEQUATE VENTILATION.
Ventilation: GENERAL MECHANICAL: EXHAUST VENTILATION AT THE POINT OF USE. LOCAL EXHAUST: OPEN DOORS/WINDOWS. ENCLOSED USE EXHAUST FAN
Protective Gloves:RUBBER GLOVES. Eye Protection:SAFETY GLASSES WITH SIDE SHIELD. Other Protective Equipment:EYE WASH AND SAFETY SHOWER SHOULD BE AVALIABLE.
Work H
ygienic Practices:WASH THOROUGHLY AFTER HANDLING. Supplemental Safety and Health NONE
======================================
HCC:F2 Boiling Pt:=66.C, 150.8F Vapor Pres:145 Vapor Density:2.5
Spec Gravity:0.9 Evaporation Rate & amp; Reference:5.5-8 (N-BUTYL ACETATE=1)
Solubility in Water:NEGLIGIBLE Appearance and Odor:LIQUID;MILKY WHITE;ETHER-LIKE ODOR. Percent Volatiles by Volume:84-88
======================================

Stability I

ndicator/Materials to Avoid:YES ACIDS, OXIDIZING MATERIALS, ALKALIS, CHLORINATED INORGANICS (POTASSIUM, CALCIUM AND SODIUM HYPOCHLORITE) COPPER & ALOOY. Stability Condition to Avoid:HEAT, SPARKS AND OPEN FLAMES. Hazardous Decomposition Products:CARBON MONOXIDE/CARBON DIOXIDE/HYDROGEN CHLORIDE/SMOKE.

Waste Disposal Methods:DISPOSE OF ACCORDING TO LOCAL, STATE AND FEDERAL REGULATIONS. CONSUMER COMMODITY, ORM-D. EPA H AZARDOUS WASTE NUMBER:D001. EPA HAZARDOUS WASTE CLASS: IGNITABLE WASTE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume respon sibility for the suitability of this information to their

particular situation.