

EASTMAN KODAK COMPANY -- 140 8913, HC-110 DEVELOPER REPLENISHER, WORKING SOLUTION
-- 6750-01-066-7332

===== Product Identification =====

Product ID:140 8913, HC-110 DEVELOPER REPLENISHER, WORKING SOLUTION

MSDS Date:11/08/1995

FSC:6750

NIIN:01-066-7332

MSDS Number: CCHXZ

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:U

S

Info Phone Num:716-477-3194 MSDS: 800-242-2424

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name:EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD

Box:City:ROCHESTER

State:NY

ZIP:14650-3129

Country:US

Phone:800-828-6203

CAGE:5K871

===== Composit

ion/Information on Ingredients =====

Ingred Name:DIETHANOLAMINE-SULFUR DIOXIDE COMPLEX

CAS:63149-47-3

Fraction by Wt: 5-10%

Other REC Limits:NONE RECOMMENDED

Ingred Name:DIETHANOLAMINE (SARA 313) (CERCLA)

CAS:111-42-2

RTECS #:KL2975000

Fraction by Wt: 1-5%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:3 PPM

ACGIH TLV:0.46 PPM; 9495

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000

Fraction by Wt: 85-90%

Other REC Limits:NONE RECOMMENDED

Ingred Name:HYD

ROQUINONE (SARA 302/313) (CERCLA)

CAS:123-31-9

RTECS #:MX3500000

Fraction by Wt: 1-5%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:2 MG/M3

ACGIH TLV:2 MG/M3; 9495

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:DIETHYLENE GLYCOL

CAS:111-46-6

RTECS #:ID5950000

Fraction by Wt: 1-5%

Other REC Limits:NONE RECOMMENDED

Ingred Name:ETHANOLAMINE

CAS:141-43-5

RTECS #:KJ5775000

Fraction by Wt: 212F,>100C

Vapor Pres:18

Vapor Density:0.6

Spec Gravity:1.02

pH:9.0-.2

Solubility in Water:COMPLETE

Appearance and

Odor:LIQUID,COLORLESS,SLIGHT AMINE ODOR
Percent Volatiles by Volume:85-90

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:HOWEVER, MATERIAL CAN DECOMPOSE ABOVE 145C
(293F). AVOID TEMPERATURES ABOVE 45C (113F).

Hazardous Decomposition Products:CARBON DIOXIDE, CARBON MONOXIDE,
OXIDES OF NITROGEN, OXIDES OF SULFUR

===== Disposal Considerations =====

=====

Waste Disposal Methods:FLUSH TO SEWER W/LARGE AMOUNTS OF WATER.

OTHERWISE, ABSORB SPILL W/VERMICULITE OR OTHER INERT MATERIAL &
PLACE IN CONTAINER FOR CHEMICAL WASTE. CLEAN SURFACE THOROUGHLY TO
REMOVE RESIDUAL CONTAMINATION.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.