

T&R CHEMICALS -- GUM TERPENTINE -- 8010-00-261-4160

=====  
Product Identification  
=====

Product ID:GUM TERPENTINE

MSDS Date:06/24/1986

FSC:8010

NIIN:00-261-4160

MSDS Number: CCJSB

=== Responsible Party ===

Company Name:T&R CHEMICALS

Box:330

City:CLINT

State:TX

ZIP:79836

Country:US

Info Phone Num:915-851-2761

Emergency Phone Num:915-851-2761 FOR ADDITIONAL INFO

CAGE:KO922

=== Contractor Identificati

on ===

Company Name:CHEMICAL SPECIALISTS & DEVELOPMENT

Box:UNKNOW

CAGE:5W443

Company Name:STARTEX (409-539-6244)

Box:UNKNOW

CAGE:NO735

Company Name:T&R CHEMICALS

Box:330

City:CLINT

State:TX

ZIP:79836

Country:US

Phone:915-851-2761

CAGE:KO922

Company Name:TRI-CHEM CORP

Box:City:SOUTHFIELD

State:MI

ZIP:48037-0448

Country:US

Phone:800-456-6255

CAGE:TRCHE

=====  
Composition/Information on Ingredients  
=====

Ingred Name:TURPENTINE

CAS:8006-64-2

RTECS #:YO8400000

Other REC Limits:NONE

RECOMMENDED  
ACGIH TLV:100 PPM

=====  
Hazards Identification  
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE: MODERATELY IRRITATING. MAY BE ALLERGENIC TO SOME WORKERS. ABOVE AVERAGE EXPOSURE MAY CAUSE DERMATITIS. CHRONIC: SAME AS ABOVE EXCEPT MILD BOTH AS IRRITANT & ALLERGENIC. EXPOSURE OVER LONG TIME PERIOD MAY RESULT IN SERIOUS KIDNEY IR RITATION. INGEST: LARGE OVEREXPOSURE, HEAVY BREATHING/COLLAPSE/COMA.  
Effects of Overexposure:INHALATION: CHARACTERISTIC ODOR ON BREATH. GIDDINESS/RESTLESSNESS/EXCITABLE/INTOXICATION/NAUSEA. SKIN/EYES: DIALATES. IRRITATES SKIN. ABSORPTION:ATAXIA/INSOMNIA/ALBUMINURIA/CYANOSIS/DILERIUM.  
Medical Cond Aggravated by Exposure:CONTINUED EXPOSURE TO FUMES/VAPORS IN EXCESS OF 100 PPM WOULD CONSTITUTE OVEREXPOSURE & COULD CAUSE KIDNEY DAMAGE.

=====  
First Aid Meas  
ures  
=====

First Aid:EYES: FLUSH WELL W/WARM WATER. CALL DR. SKIN: REMOVE CONTAM CLOTHES. WASH SKIN W/LARGE AMTS LUKE WARM WATER USING BLAND SOAP SOLUTION. INHALATION: GET TO FRESH AIR. KEEP WARM. INGESTION: GIVE LAVAGE O R EMETIC & COPIOUS AMTS WATER. CONSULT DR IMMEDIATELY.

=====  
Fire Fighting Measures  
=====

Flash Point Method:TCC  
Flash Point:105F,41C  
Autoignition Temp:Autoignition Temp Text:488F  
Lower Limits:0.8  
Extinguishing  
Media:CO2, FOAM, DRY CHEMICAL.  
Fire Fighting Procedures:AVOID IMPREGNATION OF ANY LEAKAGE W/OXIDANTS OR COMBUSTIBLES.  
Unusual Fire/Explosion Hazard:EMITS ACRID FUMES WHEN HEATED ALONG W/COMBUSTIBLE VAPORS.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:STOP SPILL PROMPTLY. REMOVE IGNIT SOURCES. CONTAIN SPILL W/DIKE ETC. CONTAINMENT REQUIRED. PUMP TO TANK FOR CONTAINMENT. SALVAGE/CONTROL DISPOSAL AS NECESSARY.

=====

= Handling and Storage =====

Handling and Storage Precautions:AS MAY BE SPECIFIED FOR HEALTH & SAFETY.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USBM TYPE N CANISTER OR EQUAL AS APPROVAL FOR CONCERNED PRODUCT.

Ventilation:ADEQUATE EXHAUST TO PREVENT BUILD-UP VAPOR/FUMES/IGNITABLE MATERIAL.

Protective Gloves:NEOPRENE RUBBER

Eye Protection:SAFETY GOGGLES/FACE SHIELDS (OSHA)

Other Protective Equipment:OVERALLS & APRON

S - NEOPRENE.

Work Hygienic Practices:WASHING & SHOWER FACILITIES READILY AVAILABLE.

Supplemental Safety and Health

PROTECTIVE MEASURES DURING MAINTAINANCE OF CONTAMINATED EQUIPMENT AS MAY BE REQUIRED TO MEET STATE, FEDERAL, LOCAL REGULATIONS.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:307F,153C

Melt/Freeze Pt:M.P/F.P Text:LIQ@AMBIENT

Vapor Pres:760

Vapor Density:4.84

Spec Gravity:0.864 @ 25C

Evaporation Rate & Reference:1.0 (BUAC=1)

Solub

ility in Water:NEGLIGIBLE

Appearance and Odor:COLORLESS TO LIGHT AMBER, TERPENE AROMA

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZING MATERIALS.

Stability Condition to Avoid:UNCONTROLLED EXPOSURE TO HEAT/FLAME. KEEP COOL.

Hazardous Decomposition Products:OVERHEATED ACRID FUMES/DEGREDDATION TERPENES RELEASED.COMBUS PRODS INCLUDE DECOMPOSED HYDROCARBONS/CARBON MONOXIDE/CO2.

Conditions to Avoid Polymerization:AVOI

D ALL CONTACT W/STRONG MINERAL  
ACIDS & LEWIS ACIDS (BORON TRIFLUORIDE/SUBSTANCES CAPABLE OF  
RELEASING PROTON MATTER)

===== Disposal Considerations =====

Waste Disposal Methods:AVOID DIRECT CONTACT W/LIQUID/VAPOR/SPRAY/MIST  
BY WEARING PROTECTIVE CLOTHES/SAFETY GOGGLES/SAFETY SHIELDS/USING  
RESP PROTECTION AS NECESSARY. FOLLOW REQ OF RCRA 1976 & ADDENDA OF  
US FOR INFO ON LEGAL DISPOSAL OF HAZARDOUS SOLIDS. COMPLY W/APPLIC  
LAW

Disclaimer (  
provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.