View NSN Online: https://aerobasegroup.kr/nsn/3439-00-250-2629

AMERICAN CHEMICAL & FLUX PRODUCTS -- SOFT SOLDER FLUX-ACTIVE ACID -- 3439-00-250-2629

======== Product Identification ============

Product ID:SOFT SOLDER FLUX-ACTIVE ACID

MSDS Date:02/17/1997

FSC:3439

NIIN:00-250-2629

MSDS Number: CCLPV === Responsible Party ===

Company Name: AMERICAN CHEMICAL & FLUX PRODUCTS

Address:5722 UNION PACIFIC AVE

City:LOS ANGELES

State:CA ZIP:90022 Country:US

Info Phone Num:213-723

-0713

Emergency Phone Num:213-723-0713

CAGE:OBTX0

=== Contractor Identification ===

Company Name: AMERICAN CHEMICAL CORP

Address:35555 CURTIS BLVD

Box:City:EAST LAKE

State:OH ZIP:44094

Phone:215-943-7600

CAGE:OBTX0

Company Name: JO-JON INC

Address:360 FREEPORT BLVD SUITE 1 & 2

Box:UNKNOW City:SPARKS State:NV

ZIP:89431 Country:US

Phone:702-356-6988

CAGE:009J0

Company Name: SPECIALTY WELDING SUPPLY

Box: UNKNOW CAGE: 09654

======= Composition/Information on Ingredients ========

Ingred Nam

e:ZINC CHLORIDE (SARA 313) (CERCLA)

CAS:7646-85-7

RTECS #:ZH1400000

Other REC Limits: NONE RECOMMENDED

OSHA PEL:1 MG/M3

ACGIH TLV:1MG/M3/2STEL(FUME)96

EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name: WATER (DEIONIZED)

CAS:7732-18-5

RTECS #:ZC0110000

Other REC Limits: NONE RECOMMENDED

OSHA PEL:NOT RELEVANT ACGIH TLV:NOT RELEVANT

Ingred Name: AMMONIUM CHLORIDE (CERCLA)

CAS:12125-02-9 RTECS #:BP4550000

Other REC Limits: NONE RECOMMENDED

OSHA PEL:10 MG/M3

ACGIH TLV:10 MG/M3 FUME; 9596

EPA Rpt Qty :5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name: HYDROGEN CHLORIDE (HYDROCHLORIC ACID) (SARA 302/313)

(CERCLA) CAS:7647-01-0

RTECS #:MW4025000

Other REC Limits: NONE RECOMMENDED

OSHA PEL:C 5 PPM

ACGIH TLV:C 5 PPM; 9596

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name: METHYL ORANGE (BENZENESULFONIC

ACID,P-((P-((DIMETHYLAMINO)PHENYL)AZO)-,SODIUM SALT

CAS:547-58-0

RTECS #:DB6327000

Other REC Limits: NONE RECOMMENDED

OSHA PEL:NOT ESTABLISHED. ACGIH TLV:NOT ESTABLISHED.

	I dantification	=======================================
Hazaluə	IUGHIIIIGAIIGH	

LD50 LC50 Mixture:LD50 (ORAL, RAT) IS NOT RELEVANT.

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:TARGET ORGANS:EYE, SKIN, RESPIRATORY & GI TRACTS. ACUTE- CORROSIVE. CAN CAUSE EYES, SKIN, RESPIRATORY & GI TRACTS SEVERE IRRITATION & BURNS. FUMES & GASES FROM WELDING CAN BE DANGEROUS TO YOUR HEALTH. ARC RAYS CAN INJURE EYES & BURN SKIN. OV

EREXPOSURE MAY CAUSE DIZZINESS, CHEST PAIN. CHRONIC- AFFECTS PULMONARY FUNCTION

Explanation of Carcinogenicity:NONE

Effects of Overexposure:SEVERE IRRITATION AND BURNS, COUGHING, CHOKING, CHEST PAIN, DIFFICULTY IN BREATHING, DIFFICULTY IN SWALLOWING, SEVERE ABDOMINAL PAIN, NAUSEA, VOMITING, DIARRHEA, COLLAPSE AND UNCONSCIOUSNESS, TEARING

Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING SKIN DISORDERS, EYE PROBLEMS OR IMPAIRED RESPIRATORY FUNCTION SUCH AS ASTH

MA, BRONCHITIS, EMPHYSEMA MAY BE MORE SUSCEPTIBLE TO THE EFFECTS OF THIS PRODUCT.

 First Aid Massuras	
 I II SI MIU IVICASUICS	

First Aid:GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. EMPLOY FIRST AID TECHNIQUE RECOMMENDED BY RED CROSS. IF BREATHING IS DIFFICULT, PROVIDE OXYGEN/CPR. FOR ELECTRIC SHOCK, DISCONNECT POWER. FOR ARC BURNS, APPL Y COLD, CLEAN COMPRESSES & CALL A PHYSICIAN. IF EYE CONTACT, FLUSH WITH WATER FOR 15 MINUTES. IF INGESTED, CALL

PHYSICIAN/POISON CONTROL CENTER. IF SKIN CONTACT, WASH WITH SOAP & WATER.

	Fire Fighting Measures	=======================================
--	------------------------	---

Flash Point Method:TOC Flash Point:221F,105C

Extinguishing Media:WATER SPRAY, CARBON DIOXIDE, FOAM OR DRY CHEMICAL FOR SURROUNDING FIRE. USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS.

Fire Fighting Procedures:WEAR FULL PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE OPERATED IN THE POSI

Unusual Fire/Explosion Hazard:WELDING ARC AND SPARKS CAN IGNITE COMBUSTIBLES.
========= Accidental Release Measures ==========
Spill Release Procedures:WEAR PROPER PROTECTIVE EQUIPMENT. VENTILATE AREA. NEUTRALIZE SPILLS WITH SODIUM CARBONATE. PLACE MATERIAL INTO CLEAN CONTAINER FOR DISPOSAL. WASH SPILL AREA WITH WATER. Neutralizing Agent:SODA ASH (SODIUM CARBONATE), TRI-SODIUM PHOSPHATE
======================================
Handling and Storage Precautions:STORE IN COOL, VENTILATED PLACE. KEEP CONTAINERS TIGHTLY CLOSED. KEEP OUT OF REACH OF CHILDREN. Other Precautions:CORROSIVE. DO NOT GET IN EYES, ON SKIN/CLOTHING. AVOID BREATHING VAPORS/MIST/GAS. USE WITH ADEQUATE VENTILATION. PROTECT CONTAINERS AGAINST PHYSICAL DAMAGE.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:USE NIOSH APPROVED SUPPLIED AIR RESPIRATORY PROTECTION OR RESPIRABLE FUME RESPIRATOR WHEN WELDING, BRAZING OR SOLDERING IN CONFINED SPACE OR WHERE LOCAL EXHAUST VENTILATION DOES NOT KEEP EXPOSURE BELO W TLV. Ventilation:USE GENERAL & LOCAL EXHAUST AT FLAME TO KEEP FUMES AND GASES BELOW TLV'S IN THE WORKER'S BREATHING ZONE & GENERAL AREA. Protective Gloves:WELDER'S GLOVE WHEN WELDING/RUBBER Eye Protection:HELMET OR USE FACE SHIELD + FILTER LENS Other Protective Equipment:EYEWASH AND SAFETY SHOWER SHOULD BE LOCATED NEARBY. Work Hygienic Practices:OBSERVE GOOD INDUSTRIAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. TRAIN WELDER NOT TO TOUCH LIVE ELECTRICAL PARTS. Supplemental Safety and Health
========= Physical/Chemical Properties ==========
HCC:C1 NRC/State Lic Num:NOT RELEVANT Vapor Pres:115 pH:2 - 3 Solubility in Water:SOLUBLE Appearance and Odor:RED LIQUID - ODORLESS ===================================
Stability Indicator/Materials to Avoid:YES
NONE Stability Condition to Avoid

TIVE PRESSURE MODE.

:NONE Hazardous Decomposition Products:WELDING FUMES (OVIDES OF ME

Hazardous Decomposition Products:WELDING FUMES (OXIDES OF METAL BEING WELD) AND GASES SUCH AS OZONE, CARBON MONOXIDE, CARBON DIOXIDE, NITROGEN OXIDES...

====== Disposal Considerations ===========

Waste Disposal Methods:PREVENT WASTE FROM CONTAMINATING SURROUNDING ENVIRONMENT. KEEP PERSONNEL AWAY. DISCARD ANY PRODUCT, RESIDUE, DISPOSABLE CONTAINER OR LINER IN AN ENVIRONMENTALLY ACCEPTABLE MANNER, IN FULL COMPLIANCE W ITH LOCAL, STATE AND FEDERA

REGULATIONS.

L

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their

particular situation.