

UNI-KEM INTERNATIONAL CORPORAT -- SLYDE II

=====
MSDS Safety Information
=====

FSC: 9150
NIIN: 00-823-7860
MSDS Date: 06/01/1996
MSDS Num: CCLTB
Product ID: SLYDE II
MFN: 02
Responsible Party
Cage: 4S446
Name: UNI-KEM INTERNATIONAL CORPORATION/MFR OXYCHEM
Address: 513 HICKORY AVENUE
City: NEW ORL
EANS (FORMALLY HARAHAN) LA 70123
Info Phone Number: 504-738-1623/713-623-2246
Emergency Phone Number: 504-738-1623/800-533-2246
Proprietary Ind: Y
Published: Y

=====
Contractor Summary
=====

Cage: 4S446
Name: UNI-KEM INTERNATIONAL
Address: 1001 HARIMAW COURT EAST
City: METAIRIE LA 70001
Phone: 504-835-7600/FAX:504-835-7608

=====
Item Description I
nformation
=====

Item Manager: S9G
Item Name: LUBRICATING COMPOUND,DIMETHYLSILICONE
Specification Number: NONE
Type/Grade/Class: NONE
Unit of Issue: CN
Quantitative Expression: 00000000016OZ
UI Container Qty: B
Type of Container: AEROSOL CAN

=====
Ingredients
=====

Name: *** PROPRIETARY ***

=====

=====
Health Hazards Data
=====

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER.

Route Of Entry Inds - Inhalation: YES

Skin: YES

Ingestion: NO

Carcinogenicity Inds - NTP: NO

IARC: NO

OSHA: NO

Effects of Exposure: HEADACHE,DIZZINESS,NAUSEA.

Signs And Symptions Of Overexposure: HEADACHE, DIZZINESS, NAUSEA.

Medical Cond Aggravated By Exposure: NONE SPECIFIED BY MANUFACTURER.

First Aid: INHAL:REMOVE VICTIM TO FRESH AIR.DO

NOT GIVE ANYTHING BY MOUTH TO

UNCONSCIOUS PERSON. INGEST:DO NOT INDUCE VOMIT.CONTACT PHYSICIAN. EYE:WASH
W/PLENTY OF WATER FOR 15MINS. SKIN:FLUSH W/WATER.

=====
Handling and Disposal
=====

Spill Release Procedures: SM:MOP,WIPE,COSK UP W/ABSORBENT MATL USING PROPER
PROTECTIVE EQPMT. LG:FLUSH SPILL TO GROUND & LET EVAPORATE.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Waste Disposa

I Methods: DO NOT INCINERATE OR PUNCUTRE CAN, WRAP CNTNR &
DISPO OF IN TRASH COLLECTION.

Handling And Storage Precautions: DO NOT STORE ABOVE 120F.

Other Precautions: AVOID BREATHING OF VAPORS. USE ADEQUATE VENITLATION.

=====
Fire and Explosion Hazard Information
=====

Flash Point Text: SUPPLEMENTAL

Autoignition Temp Text: N/DETR

Lower Limits: 6.2

Upper Limits: 17.2

Extinguishing Media: MEC

HANICAL FORM, DRY CHEMICAL, WATER, CO2.

Fire Fighting Procedures: SELF CONTAINED RESPIRATORY EQPMT.

Unusual Fire/Explosion Hazard: NONE.

=====
Control Measures
=====

Respiratory Protection: IF CONCENTRATION WILL EXCEED TLV USE SELF CONTAINED
BREATHING APPARATUS.

Ventilation: LOCAL EXHAUST/MECHANICAL (GENERAL):RECOMMENDED.
SPECIAL/OTHER:NONE.

Protective Gloves: NEOPRENE GLOVES.

Eye Protection:

GOGGLES.

Other Protective Equipment: RUBBER APRON TO AVOID WETTING CLOTHES.

Work Hygienic Practices: READ INZTRUCTIONS CAREFULLY BEFORE USING. KEEP AWAY FROM CHILDREN.

Supplemental Safety and Health: FLASH PT:FLAMMABLE BY CANDLE FLAME EXTENTION TEST.

Physical/Chemical Properties

HCC: V3

B.P. Text: NA

M.P/F.P Text: NA

Vapor Pres: NA

Vapor Density: NA

Spec Gravity: NA

Evaporation R

ate & Reference: 1.2, REF NOT GIVEN

Solubility in Water: NEGLIGIBLE.

Appearance and Odor: AEROSOL WITH HYDROCARBON ODOR.

Reactivity Data

Stability Indicator: YES

Stability Condition To Avoid: OPEN FLAME OR WELDING ARCS.

Materials To Avoid: NONE.

Hazardous Decomposition Products: EXPOSURE TO HIGH TEMPERATURES OR OPEN FLAME GENERATE HYDROCARBON & SMAL AMTS OF CHLORINE/PHOSGENE.

Hazardous Polymerization Indicator: NO

Toxicological Information

Ecological Information

MSDS Transport Information

Regulatory Information

Other Information

Transportation Information

Responsible Party Cage: 4S446

Trans ID NO: 86986

Product ID: SLYDE II

MSDS Prepared Date: 06/01/1996

Review Date: 01/13/1997

MFN: 2

Tech Entr

y NOS Shipping Nm: SIOBUTANE/PROPANE PROPELLANT.

Net Unit Weight: 16 OZ

Multiple KIT Number: 0

Review IND: Y

Unit Of Issue: CN

Container QTY: B

Type Of Container: AEROSOL CAN

Additional Data: PER MSDS:FLAMM BY CANDLE FLAME EXTENTION TEST; PER
CTDF:AEROSOL CAN.

=====
Detail DOT Information
=====

DOT PSN Code: AGC

DOT Proper Shipping Name: AEROSOLS, FLAMMABLE,

DOT PSN Modifier: (EACH NOT EXCEEDIN
G 1 L CAPACITY)

Hazard Class: 2.1

UN ID Num: UN1950

Label: FLAMMABLE GAS

Special Provision: N82

Non Bulk Pack: NONE

Bulk Pack: NONE

Max Qty Pass: 75 KG

Max Qty Cargo: 150 KG

Vessel Stow Req: A

Water/Ship/Other Req: 40,48,85
=====

=====
Detail IMO Information
=====

IMO PSN Code: AIY

IMO Proper Shipping Name: AEROSOL DISPENSERS ?

IMO PSN Modifier: ,WITH A CAPACITY OF 1000 CUBIC CM OR LESS

IMDG Page Numbe

r: 9022

UN Number: 1950

UN Hazard Class: 9?

IMO Packaging Group: -

Subsidiary Risk Label: -

EMS Number: 2-13
=====

=====
Detail IATA Information
=====

IATA PSN Code: ALS

IATA UN ID Num: 1950

IATA Proper Shipping Name: AEROSOLS, FLAMMABLE

IATA PSN Modifier: (EACH NOT EXCEEDING 1 L CAPACITY)

IATA UN Class: 2.1

IATA Label: FLAMMABLE GAS

Packing Note Passenger: 203

Max Quant Pass: 75KG

Max Quant Cargo: 150

KG
Packaging Note Cargo: 203

=====
Detail AFI Information
=====

AFI PSN Code: ALR
AFI Symbols: *
AFI Proper Shipping Name: AEROSOLS, FLAMMABLE, N.O.S.
AFI PSN Modifier: (EACH NOT EXCEEDING 1L CAPACITY)
AFI Hazard Class: 2.1
AFI UN ID NUM: UN1950
Special Provisions: P4
Back Pack Reference: A6.3
=====

HAZCOM Label
=====

=====
Product ID: SLYDE II
Cage: 4S446
Company Name: UNI-KEM INTERNATIONAL
Street: 1001 HARIMAW COURT EAST
City: METAIRIE LA
Zipcode: 70001
Health Emergency Phone: 504-738-1623/800-533-2246
Label Required IND: Y
Date Of Label Review: 01/13/1997
Status Code: C
Label Date: 01/13/1997
Origination Code: F
Chronic Hazard IND: Y
Eye Protection IND: YES
Skin Protection IND: YES
Signal Word: DANGER
Respiratory Protection IND: YES
Health Hazard: Slight
Contact Hazard: Slight
Fire Hazard:
Severe
Reactivity Hazard: None
Hazard And Precautions: HEADACHE,DIZZINESS,NAUSEA. DO NOT STORE ABOVE 120F.
FIRST AID: INHAL:REMOVE VICTIM TO FRESH AIR.DO NOT GIVE ANYTHING BY MOUTH TO
UNCONSCIOUS PERSON. INGEST:DO NOT INDUCE VOMIT.CONTACT PHYSICIAN. EYE:W ASH
W/PLENTY OF WATER FOR 15MINS. SKIN:FLUSH W/WATER. FIRE:USE MECHANICAL FORM,
DRY CHEM, WATER, CO2. SPILL:MOP/WIPE/SOAK W/ABSORBENT MATL USING PROPER
PROTECTIVE EQPMT.LG SPILLS FLUSH TO GROUND & LET EVAPORATE. DISPO:DO NOT
INC

INERATE OR PUNCUTRE CAN,WRAP CONTAINER & DISPO OF IN TRASH COLLECTION.

=====
Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.