

CHEMTRONICS INC -- ULTRAJET 2000 SYSTEM REFILL ES520/ES1020/ES1020K/ES1020R --
6350-01-261-9862

===== Product Identification =====

Product ID:ULTRAJET 2000 SYSTEM REFILL ES520/ES1020/ES1020K/ES1020R

MSDS Date:07/13/1994

FSC:6350

NIIN:01-261-9862

MSDS Number: CCLZC

=== Responsible Party ===

Company Name:CHEMTRONICS INC

Address:8125 COBB CENTER DRIVE

City:KENNESAW

State:GA

ZIP:30144

Country:US

Info

Phone Num:800-645-5244

Emergency Phone Num:800-424-9300 CHEMTREC

Preparer's Name:MICHAEL S. WATKINS

CAGE:2M589

=== Contractor Identification ===

Company Name:CHEMTRONICS INC (CANCELLED USE 21267)

City:HAUPPAUGE

State:NY

ZIP:11760

Country:US

CAGE:2M589

Company Name:SIGNALTONE INC

Address:946 FRISBIE ST.

Box:City:CADILLAC

State:MI

ZIP:49601

Country:US

Phone:616-775-1373

CAGE:64189

Company Name:SUPPLY DEPOT INC

Address:2830 VIA ORANGE WAY

Box:UNKNOWN

City:SPRING VALLEY

State:CA

ZIP:91978

Country:US

Phone:619-660-2813/FAX 800-236-5519
CAGE:04ZR5

===== Composition/Information on Ingredients =====

Ingred Name:TETRAFLUOROETHANE
CAS:811-97-2
Fraction by Wt: 100%
Other REC Limits:100 PPM AEL-DUPONT

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: HARMFUL IF INHALED; MAY CAUSE ASPHYXIATION. CONTACT WITH LIQUID MAY CAUSE FROSTBITE, IRRITATION. INGESTION MAY CAUSE FROSTBITE OF MOUTH & THROAT TISSUES. CHRONIC: NONE SPECIFIED BY MANUFACTURER .
Explanation of Carcinogenicity:NO INGREDIENT OF A CONCENTRATION OF 0.1% OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN.
Effects of Overexposure:INHALED-DIZZINESS, UNCONSCIOUSNESS, DEATH. SKIN-IRRITATION, FROSTBITE. EYES-IRRITATION, FROSTBITE. INGESTED-FROSTBITE OF MOUTH & THROAT
.
Medical Cond Aggravated by Exposure:PRE-EXISTING MEDICAL CONDITIONS OF THE HEART, LUNG, SKIN, EYE.

===== First Aid Measures =====

First Aid:IN ALL CASES GET MEDICAL ATTENTION. EYES-TREAT FOR FROSTBITE THEN FLUSH WITH WATER FOR 15 MINUTES. SKIN-REMOVE CONTAMINATED CLOTHES. TREAT FOR FROSTBITE THEN WASH WITH MILD SOAP & WATER. INHALED-REMOVE TO FRESH AIR. ADMINISTER OXYGEN OR ARTIFICIAL RESPIRATION AS NEEDED. INGESTED-TREAT FOR FROSTBITE & OBTAIN IMMEDIATE MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:NONE
Lower Limits:NONE
Upper Limits:NONE
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, DRY CHEMICAL, ALCOHOL FOAM WHEN EXTINGUISHING FIRES INVOLVING THIS MATERIAL.
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL FIRE FIGHTER'S PROTECTIVE GEAR. USE WATER TO COOL FIRE EXPOSED CONTAINERS.
Unusual Fire/Explosi

on Hazard:NONE SPECIFIED BY MANUFACTURER.

===== Accidental Release Measures =====

Spill Release Procedures:SHUT OFF LEAK IF POSSIBLE & SAFE TO DO SO.
WEAR SELF-CONTAINED BREATHING APPARATUS & APPROPRIATE PERSONAL
PROTECTIVE GEAR. ABSORB SPILL WITH INERT MATERIAL & PLACE IN A
CONTAINER FOR DISPOSAL. DO NOT FLUSH TO SEWER. KEEP OUT OF
WATERWAYS.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====
=====

Handling and Storage Precautions:STORE IN A COOL, DRY PLACE AWAY FROM
HEAT & OPEN FLAMES. KEEP CONTAINER CLOSED WHEN NOT IN USE. DO NOT
STORE IN DIRECT SUNLIGHT.

Other Precautions:KEEP OUT OF REACH OF CHILDREN. AVOID PROLONGED OR
REPEATED CONTACT WITH SKIN, EYES, CLOTHING. WASH HANDS BEFORE
EATING. USE WITH ADEQUATE VENTILATION. AVOID BREATHING VAPOR OR
MIST.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF ENGINEER
ING CONTROLS FAIL OR NON-ROUTINE USE
OR AN EMERGENCY OCCURS; WEAR AN MSHA/NIOSH APPROVED AIR-SUPPLIED
RESPIRATOR OR SCBA, AS REQUIRED. USE IAW 29 CFR 1910.134.

Ventilation:USE GOOD GENERAL VENTILATION OR LOCAL EXHAUST TO MAINTAIN
EXPOSURE BELOW TLV(S).

Protective Gloves:RUBBER OR CHEMICALLY RESISTANT GLOVES.

Eye Protection:SAFETY GLASSES W/FACESHIELD.

Other Protective Equipment:NONE NORMALLY REQUIRED.

Work Hygienic Practices:WASH HANDS AFTER HANDLING AND BEFORE EATING,
DRINKING,

OR SMOKING. LAUNDRER CONTAMINATED CLOTHES BEFORE REUSE.

Supplemental Safety and Health

MSDS IS FOR REFILL CYLINDER FOR SIGNALTONE-NEIMAN PART NUMBER 65800
"BIG HORN".

===== Physical/Chemical Properties =====

HCC:V2

Boiling Pt:B.P. Text:-16F,-27C

Vapor Pres:4241

Vapor Density:3.18

Spec Gravity:1.21

Evaporation Rate & Reference:>1 (N-BUTYL ACETATE=1)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:CLEAR, COLORLESS GAS; SLIGHT ETHEREAL ODOR.

Percent Volatiles

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
DO NOT MIX WITH POWDERED ALKALI & ALKALINE EARTH METALS OR STRONG
OXIDIZING AGENTS.
Stability Condition to Avoid:DO NOT SPRAY NEAR OPEN FLAMES, RED HOT
SURFACES, OR OTHER SOURCES OF IGNITION.
Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY RELEASE
HYDROFLUORIC ACID VAPOR.
Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Di
sposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND
FEDERAL ENVIRONMENTAL REGULATIONS. WATER RUNOFF CAN CAUSE
ENVIRONMENTAL DAMAGE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all lia
bility for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.