

RESIN TECHNOLOGY GROUP INC -- ACTIVATOR A -- 1660-00-325-0283

=====
===== Product Identification =====
=====

Product ID:ACTIVATOR A

MSDS Date:01/11/1995

FSC:1660

NIIN:00-325-0283

Kit Part:Y

MSDS Number: CCMQH

=== Responsible Party ===

Company Name:RESIN TECHNOLOGY GROUP INC

Address:28 NORFOLK AVE

City:SOUTH EASTON

State:MA

ZIP:02375

Country:US

Info Phone Num:508-230-8070 FAX: 508-230-2318

Emergency Phone Num:

800-424-9300 CHEMTREC

CAGE:0JVX9

=== Contractor Identification ===

Company Name:MORTON THIOKOL,INC;ARMSTRONG PRODUCTS COMPANY

Address:407-ARGONNE ROAD

Box:647

City:WARSAW

State:IN

ZIP:46580-3811

Country:US

Phone:219-267-3226

CAGE:98911

Company Name:RESIN TECHNOLOGY GROUP INC

Address:28 NORFOLK AVE

Box:City:S EASTON

State:MA

ZIP:02375

Country:US

Phone:508-230-8070

CAGE:0JVX9

=====
===== Composition/Information on Ingredients =====
=====

Ingred Name:DIETHYLENETRIAMINE

CAS:111-40-0

RTECS #:

IE1225000

Fraction by Wt: 100%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:1 PPM

ACGIH TLV:S, 1 PPM; 9596

=====
===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:CORROSIVE! CONTACT MAY CAUSE SEVERE IRRITATION/BURNS TO SKIN & EYES; MAY CAUSE HYPERSENSITIVITY IN SOME INDIVIDUALS. INHALA

TION MAY CAUSE IRRITATION OF RESPIRATORY SYSTEM; MAY CAUSE HYPERSENSITIVITY I N SOME. INGESTION MAY CAUSE SEVERE IRRITATION/BURNS TO MOUTH/THROAT/GI TRACT. MAY ALSO AFFECT LIVER, KIDNEY, IMMUNE SYS.

Explanation of Carcinogenicity:NO INGREDIENT OF A CONCENTRATION OF 0.1% OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN.

Effects of Overexposure:EYES-SEVERE IRRITATION, BURNS. SKIN-BURNS, TISSUE DAMAGE, HYPERSENSITIVITY. INHALED-IRRITATION OF UPPER RESPIRATORY SYS

TE, COUGHING, SHORTNESS OF BREATH, TIGHTNESS IN CHEST. INGESTED-SEVERE BURNS TO M OUTH/THROAT/DIGESTIVE TRACT, NAUSEA, VOMITING, GI TRACT UPSET.

Medical Cond Aggravated by Exposure:PRE-EXISTING LIVER, KIDNEY, RESPIRATORY, IMMUNE SYSTEM DISORDERS.

=====
===== First Aid Measures =====

First Aid:IN ALL CASES GET MEDICAL ATTENTION. EYES-FLUSH WITH WATER FOR 15 MINUTES. SKIN-REMOVE CONTAMINATED CLOTHES. WASH WITH MILD SOAP & WATER. INHALED-REMOVE

TO FRESH AIR. ADMINISTER OXYGEN OR ARTIFICIAL RE SPIRATION AS NEEDED. INGESTED-CONTACT POISON CONTROL CENTER AND OBTAIN IMMEDIATE MEDICAL ATTENTION. DO NOT INDUCE VOMITING! IF CONSCIOUS, GIVE 2 CUPS WATER. NO CARBONATED BEVERAGES!

=====
===== Fire Fighting Measures =====

Flash Point Method:SCC

Flash Point:>200F,>93C

Extinguishing Media:SMALL FIRES: HALON, WATER FOG, CARBON DIOXIDE, DRY CHEMICAL, FOAM. LARGE FIRES: WATER SPRAY/FOG, ALCOHOL FOAM.

Fire

Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL FIRE FIGHTER'S PROTECTIVE GEAR. WATER MAY CAUSE FROTHING.
Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.

===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE AREA. EVACUATE IF EXPOSURE EXCEEDS TLV. CONTAIN SPILL. IF LARGE AMOUNT SPILLED, USE PUMP OR VACUUM TO PICK-UP. OTHERWISE, ABSORB WITH INERT MATERIAL. SCOOP UP & PLACE IN A CONTAINER FOR LATER DISPOSAL. REPORT SPILL IF REQUIRED BYLAW.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY, WELL-VENTILATED PLACE. DO NOT STORE ABOVE 86F. AVOID CONTACT WITH EYES, SKIN, CLOTHES. USE APPROPRIATE VENTILATION/RESPIRATORS.
Other Precautions:NONE SPECIFIED BY MANUFACTURER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:
IF ENGINEERING CONTROLS FAIL OR NON-ROUTINE USE OR AN EMERGENCY OCCURS; WEAR AN MSHA/NIOSH APPROVED RESPIRATOR WITH ORGANIC VAPOR CARTRIDGE OR AN AIR-SUPPLIED RESPIRATOR OR SCBA, AS REQUIRED. USE IAW 29 CFR 1910.134.
Ventilation:USE ADEQUATE MECHANICAL VENTILATION OR LOCAL EXHAUST TO MAINTAIN EXPOSURE BELOW TLV(S).
Protective Gloves:IMPERVIOUS-RUBBER.
Eye Protection:CHEMICAL SPLASH GOGGLES+FACESHIELD.
Other Protective Equipment:RUBBER APRON. EYE WASH STATION & SAFETY SHOWER.
DO NOT WEAR CONTACT LENSES.
Work Hygienic Practices:WASH HANDS AFTER HANDLING AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOTHES BEFORE REUSE.
Supplemental Safety and Health
KEY1=C4. PART B OF 81 PART KIT. ONLY PNI A, B & C ARE HAZARDOUS-AS BEST AS DLA-HMIS CAN FIGURE OUT.

===== Physical/Chemical Properties =====

HCC:B2
Boiling Pt:=203.3C, 398.F
B.P. Text:398F,203C
Vapor Pres:1
Vapor Density:3.56
Spec Gravity:0.95
Solubility in Water:COMP

LETE

Appearance and Odor:AMBER, VISCOUS LIQUID; AMINE ODOR.

Percent Volatiles by Volume:1.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, ACIDS, WATER, CHEMICALLY ACTIVE METALS; EG
NICKEL, COBALT, COPPER, IRON.

Stability Condition to Avoid:AVOID CONTACT WITH INCOMPATIBLE MATERIALS.

Hazardous Decomposition Products:AMINES, OXIDES OF NITROGEN, SMOKE,
SOOT, CARBON DIOXIDE, CARBON MONOXIDE.

Conditions

to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND
FEDERAL ENVIRONMENTAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
d

isclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.