AGFA DIVISION OF BAYER CORPORATION -- ENCO PLATE CLEANER,60639226 -- 6850-01-019-0667

Product ID: ENCO PLATE CLEANER, 60639226 MSDS Date:08/14/1996 FSC:6850 NIIN:01-019-0667 MSDS Number: CCMRZ === Responsible Party === Company Name: AGFA DIVISION OF BAYER CORPORATION Address:50 MEISTER AVE Box:1271 City:SOMERVILLE State:NJ ZIP:08876 Country:US Info Phone Num:908-231 -5445 Emergency Phone Num:908-231-5445/800-424-9300(CHEMTREC) CAGE:MO568 === Contractor Identification === Company Name: AGFA DIVISION OF BAYER CORPORATION Address:50 MEISTER AVE Box:1271 City:SOMERVILLE State:NJ ZIP:08876 Country:US Phone:908-231-5445 CAGE:MO568 Company Name: HOECHST CELANESE CORP PRINTING PRODUCTS DIV Address:3070 U S HWY 22 W Box:3700 City:SOMERVILLE State:NJ ZIP:08870 Country:US Phone:908-231-3829 CAGE:02687

Ingred Name:STODDARD SOLVENT CAS:8052-41-3 RTECS #:WJ8925000 Fraction by Wt: 19% Other REC Limits:NONE RECOMMENDED OSHA PEL:500 PPM ACGIH TLV:100 PPM; 9596

Ingred Name:NAPHTHA, LIGHT AROMATIC (SOLVENT NAPHTHA)/SUPER HIGH FLASH NAPHTHA CAS:64742-95-6 RTECS #:WF3400000 Other REC Limits:NONE RECOMMENDED OSHA PEL:5 MG/M3 AS OIL MIST ACGIH TLV:5 MG/M3 AS OIL MIST

Ingred Name:NITRIC ACID (SARA 302/313) (CERCLA) CAS:7697-37-2 RTECS #:QU5775000 Fraction by Wt: 4% Other REC Limits:NONE RECOMMENDE D OSHA PEL:2 PPM ACGIH TLV:2 PPM/4 STEL; 9596 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:PHOSPHORIC ACID (SARA 313) (CERCLA) CAS:7664-38-2 RTECS #:TB6300000 Fraction by Wt: 3% Other REC Limits:NONE RECOMMENDED OSHA PEL:1 MG/M3 ACGIH TLV:1 MG/M3/3 STEL; 9596 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:WATER CAS:7732-18-5 RTECS #:ZC0110000 Other REC Limits:NONE RECOMMENDED OSHA PEL:NOT RELEVANT ACGIH TLV:NOT RELEVANT

===========

LD50 LC50 Mixture:LD50 (ORAL, RAT) IS NOT KNOWN. Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: TARGET ORGANS: EYES, SKIN, CNS, **RESPIRATORY & GI TRACTS. ACUTE- INHALE: HIGH VAPOR CONCENTRATIONS** MAY CAUSE CNS DEPRESSION. EYE:CAUSES IRRITATION. SKIN: PROLONGED/REPEATED CONTACT MAY CAUSE DRYING. CRACK ING. ORAL:HARMFUL. MAY CAUSE GI TRACT IRRITATION. ASPIRATION INTO LUNGS MAY CAUSE DAMAGE/DEATH. CHRONIC- DERMATITIS. Explanation of Carcinogenicity:NONE Effects of Overexposure: IRRITATION, COUGHING, CHOKING, CHEST PAIN, DIFFICULTY IN BREATHING, ABDOMINAL PAIN, NAUSEA, VOMITING, DIARRHEA, COLLAPSE, UNCONSCIOUSNESS, DEATH, DIZZINESS, HEADACHES, DRYING AND CRACKING OF SKIN, DER MATITIS Medical Cond Aggravated by Exposure: PERSONS WITH PRE-EXISTING SKIN DISORDERS, EYE PROBLEMS OR IMPAIRED CNS, RESPIRATORY FUNCTION SUCH AS ASTHMA, BRONCHITIS, EMPHYSEMA MA Y BE MORE SUSCEPTIBLE TO THE

EFFECTS OF THIS PRODUCT.

First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED:REMOVE TO FRESH AIR. PROVIDE CPR/OXYGEN IF NEEDED. EYES:FLUSH WITH WATER FOR 15 MINUTES, HOLDING EYELIDS OPEN. CALL PHYSICIAN. SKIN:WASH WITH SOAP & WATER . ORAL:DO NOT INDUCE VOMITING. IF CONSCIOUS, RINSE MOUTH OUT WITH WATER. GET MEDICAL ATTENTION IMMEDIATELY. NEVER GIVE ANYTIHING BY MOUTH TO AN UNCONSCIOUS PERSON.

Flash Point Method:CC
Flash Point:112F,44C
Extinguishing Media:USE WATER SPRAY, CARBON DIOXIDE (CO2), FOAM OR DRY CHEMICAL. USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS.
Fire Fighting Procedures:WEAR FULL PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE OPERATED IN THE POSITIVE PRESSURE MODE.
Unusual Fire/Explosion Hazard:VAPOR IS HEAVIER THAN

AIR AND CAN TRAVEL CONSIDERABLE DISTANCE TO A SOURCE OF IGNITION AND FLASH BACK. CONTAINERS MAY RUPTURE DUE TO VAPOR PRESSURE BUILDUP.

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENT. VENTILATE AREA. REMOVE IGNITION SOURCES. REMOVE SPILLS WITH INERT ABSORBENT MATERIAL SUCH AS SAND OR VERMICULITE. PLACE MATERIAL INTO CONTAINER FOR DISPOSAL. WASH SPILL AREA . KEEP SPILL AND WASH WATER FROM ENTERING SE

WERS.

Neutralizing Agent:SODA ASH (SODIUM CARBONATE), LIME (CALCIUM HYDROXIDE), LIMESTONE (CA CARBONATE)

Handling and Storage Precautions:STORE IN COOL, WELL VENTILATED PLACE, AWAY FROM ALKALINE MATERIALS. KEEP CONTAINERS TIGHTLY CLOSED. KEEP OUT OF REACH OF CHILDREN.

Other Precautions:WARNING! FLAMMABLE AND CORROSIVE. DO NOT GET IN EYES, ON SKIN OR CLOTHING. AVOID BREATHING VAPORS. USE WITH ADEQUATE VENTIL

ATION. PROTECT CONTAINERS AGAINST PHYSICAL DAMAGE. KEEP AWAY FROM FOOD AND FE ED. WASH THROUGHLY AFTER HANDLING.

Respiratory Protection:NONE SHOULD BE NEEDED. IF TLV IS EXCEEDED OR FOR SYMPTOMS OF OVER EXPOSURE, WEAR NIOSH-APPROVED ORGANIC VAPOR RESPIRATOR OR POSITIVE-PRESSURE SELF-CONTAINED BREATHING APPARATUS. Ventilation:MECHANICAL (GENERAL AND/OR LOCAL EXHAUST, EXPLOSION-PROOF) VENTILATION TO MAINTAIN EXPOS URE BELOW TLV(S). Protective Gloves:NATURAL RUBBER OR NEOPRENE Eye Protection:SAFETY GLASSES/CHEMICAL SPLASH GOGGLES Other Protective Equipment:USE RUBBER SPLASH APRON AND RUBBER BOOTS. EYEWASH AND SAFETY SHOWER SHOULD BE LOCATED NEARBY. Work Hygienic Practices:OBSERVE GOOD INDUSTRIAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. WASH THOROUGHLY BEFORE EATING, DRINKING/SMOKING.

Supplemental Safety and Health

HCC:F

6 NRC/State Lic Num:NOT RELEVANT Boiling Pt:>100.C, 212.F Vapor Density:>1 Spec Gravity:0.97 pH:0.56 VOC Grams/Liter:1.53 Evaporation Rate & amp; Reference: