View NSN Online: https://aerobasegroup.kr/nsn/4210-01-287-4181

UNION CARBIDE CHEMICALS AND PLASTICS CO INC -- NITROGEN -- 4210-01-287-4181

======== Product Identification ============

Product ID:NITROGEN MSDS Date:08/01/1985

FSC:4210

NIIN:01-287-4181

Kit Part:Y

MSDS Number: CCMTR === Responsible Party ===

Company Name: UNION CARBIDE CHEMICALS AND PLASTICS CO INC

Address:39 OLD RIDGEBURY RD

City: DANBURY

State:CT

ZIP:06817-0001

Country:US

Info Phone Num:304-744-3487

Emerg

ency Phone Num:304-744-3487

CAGE:0TAZ2

=== Contractor Identification === Company Name:ALL-SAFE INC Address:4767 LANGTON RD

Box:116

City:HIILIARD

State:OH ZIP:43026 Country:US

Phone:614-876-4041

CAGE:2X264

Company Name: UNION CARBIDE CORPORATION

Address:39 OLD RIDGEBURY RD

Box:City:DANBURY

State:CT

ZIP:06817-0001 Country:US

Phone:1-800-568-4000 / 732-563-5522

CAGE:0TAZ2

====== Composition/Information on Ingredients ========

Ingred Name:NITROGEN

CAS:7727-37-9

RTECS #:QW9700000

Fract

ion by Wt: 100% Other REC Limits:NONE RECOMMENDED ACGIH TLV:ASPHYXIANT; 9596
======================================
LD50 LC50 Mixture:CLASSIFIED AS SIMPLE ASPHYXIANT Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:INGEST:UNLIKELY ROUTE OF EXPOSURE;THIS IS A GAS.SKIN:LIQUID MAY CAUSE FROSTBITE.EYES:NO HARMFUL EFFECT EXPECTED.INHAL:ASPHYXIANT. Explanation of Carcino
genicity:THERE ARE NO INGREDIENTS ABOVE 0.1% WHICH ARE IDENTIFIED AS CARCINOGENS BY NTP,IARC OR OSHA. Effects of Overexposure:SKIN:LIQUID MAY CAUSE FROSTBITE.INHAL:DROWSINESS,DIZZINESS,EXCITATION,EXCESS SALIVATION,VOMITING,UNCONSCIOUSNESS. Medical Cond Aggravated by Exposure:UNLIKELY TO AGGRIVATE EXISTING MEDICAL CONDITIONS UNDER NORMAL CONDITIONS OF USE.
======================================
First Aid:EYES:FLUSH WITH WATER.CONSULT AN OPTHAMOLOGIS T.SKIN:TREAT FOR FROSTBITE WITH WATER NO WARMER THAN 105F.CALL PHYSICIAN FOR MASSIVE EXPOSURE.INHAL:REMOVE TO FRESH AIR.GIVE OXYGEN OR ARTIFICIAL RESPIRATI ON IF NEEDED.CALL PHYSICIAN.INGEST:UNLIKELY ROUTE OF EXPOSURE.
======================================
Flash Point:NONE Extinguishing Media:**NON-FLAMMABLE** USE MEDIA APPROPRIATE FOR SURROUNDING FIRE. Fire Fighting Procedures:USE A SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE E QUIPMENT.COOL FIRE EXPOSED CONTAINERS WITH WATER FOG. Unusual Fire/Explosion Hazard:CONTAINERS MAY BURST AT ELEVATED TEMPERATURES.
========== Accidental Release Measures ==========
Spill Release Procedures:EVACUATE AREA.USE SCBA WHERE NEEDED.VENTILATE AREA.TEST FOR ADEQUATE OXYGEN LEVELS BEFORE REENTERING AREA. Neutralizing Agent:NOT APPLICABLE.
========== Handling and Storage ============
Handling and Storage Precautions:STORE IN A COOL,D

PLACE.KEEP CONTAINER CLOSED WHEN NOT IN USE. Other Precautions: FOLLOW LABEL DIRECTIONS. ===== Exposure Controls/Personal Protection ======== Respiratory Protection: WHERE ENVIRONMENTAL CONTROLS ARE LACKING OR IN ENCLOSED SPACES USE A SELF-CONTAINED BREATHING APPARATUS. Ventilation:LOCAL VENTILATION AT THE WORKSITE;MECHANICAL(GENERAL) VENTILATION TO MAINTAIN TLV/PEL. Protective Gloves: COTTON FOR HANDLING CYLINDERS. **Eve Protection:SAFETY GLASSES** Other Protective Equipment:NONE Work Hygienic Practices: USE REASONABLE CARE IN HANDLING THIS PRODUCT. Supplemental Safety and Health KEY1;G3.REFER TO SAME NSN WITH CAGE 21481 AND PNIND B.THIS ITEM IS A DRY CHEMICAL FIRE EXTINGUISHER MADE BY WALTER KIDDE, MODEL 486573.EXTINGUISHER IS PRESSURIZED TO 360PSI;INTERNAL VOLUME OF EXTINGUIS HER IS 750IN*3(RE:KEVIN RICHARDS,508-881-2000). ========= Physical/Chemical Properties =========== HCC:G3 Boiling Pt:B.P. Text:-319F,-195C Melt/Freeze Pt:M.P/F.P Text:-346F,-210C Vapor Pres:SUPPL Vapor Density: 0.967 Solubility in Water: NEGLIGIBLE Appearance and Odor: COLORLESS, ODORLESS GAS. Percent Volatiles by Volume:100 ======== Stability and Reactivity Data =========== Stability Indicator/Materials to Avoid:YES LITHIUM, NEODYMIUM, TITANIUM, OZONE. Stability Condition to Avoid: TEMPERATURE ABOVE 52C/125F. Hazardous Decomposition Products: MANUFACTURER STATES NONE. ===== Disposal Considerations =====

RY, WELL-VENTILATED

==========

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL,STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.