

VAN WATERS AND ROGERS INC -- CHLOROTHENE SM SOLVENT, CHEMCO SAF-T-SOLV --
6850-01-424-8532

===== Product Identification =====

Product ID:CHLOROTHENE SM SOLVENT, CHEMCO SAF-T-SOLV

MSDS Date:12/19/1995

FSC:6850

NIIN:01-424-8532

MSDS Number: CCMZH

=== Responsible Party ===

Company Name:VAN WATERS AND ROGERS INC

Address:6100 CARILLON POINT

City:KIRKLAND

State:WA

ZIP:98033

Country:US

Info Phone Num:206

-889-3400

Emergency Phone Num:206-889-3400

CAGE:0STM5

=== Contractor Identification ===

Company Name:CHEMICAL COMMODITIES AGENCY, INC.

Address:27447 PACIFIC STREET

Box:City:HIGHLAND

State:CA

ZIP:92346-2640

Country:US

Phone:909-864-2310

CAGE:60777

Company Name:VOPAK USA INC

Address:6100 CARILLON POINT

Box:City:KIRKLAND

State:WA

ZIP:98033-7357

Country:US

Phone:425-889-3400/425-889-3617

CAGE:0STM5

===== Composition/Information on Ingredients =====

Ingred Name:METHYL CHLOROFORM (

1,1,1-TRICHLOROETHANE) (SARA 313)
(CERCLA)

CAS:71-55-6

RTECS #:KJ2975000

Fraction by Wt: 96.5%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:350 PPM

ACGIH TLV:350 PPM/450STEL;9596

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ozone Depleting Chemical:1

Ingred Name:1,4-DIOXANE (DIETHYLENE DIOXIDE) (SARA 313) (CERCLA)

CAS:123-91-1

RTECS #:JG8225000

Fraction by Wt: 2.5%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:S, 100 PPM

ACGIH TLV:S, 25 PPM; 9596

EPA Rpt Qty:100 LBS

DOT Rpt Qty:100 LBS

Ingred Name:

1,2-BUTYLENE OXIDE (SARA 313) (CERCLA)

CAS:106-88-7

RTECS #:EK3675000

Fraction by Wt: 0.47%

Other REC Limits:NONE RECOMMENDED

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:NITROMETHANE

CAS:75-52-5

RTECS #:PA9800000

Fraction by Wt: 0.34%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:20 PPM; 9596

=====
===== Hazards Identification =====

LD50 LC50 Mixture:LD50 ORAL, RAT: >10,000 MG/KG;

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of

Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYE: PAIN. SLIGHT TRANSIENT IRRITATION WITH SLIGHT TRANSIENT CORNEAL INJURY. IRRITATION. SKIN: PROLONGED OR REPEATED MAY CAUSE IRRITATION, DRYING, FLAKING. INGESTION: ASPIRATED PRODUCT MAY RESULT IN I NJURY TO OTHER BODY SYSTEMS. INHALATION: HIGH CONCENTRATIONS (10000): UNCONSCIOUSNESS, DEATH. CARDIAC ARTHYTHMIAS.

Explanation of Carcinogenicity:THIS COMPOUND CONTAINS NO INGREDIENTS AT CONCENTRATION

S OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT CARCINOGENS.

Effects of Overexposure:EYE PAIN, TRANSIEN IRRITATION, SKIN IRRITATION, DRYING, FLAKING, CHEMICAL PNEUMONIA, UNCONSCIOUSNESS, CARDIAC ARTHYTHMIAS, DEATH.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH WATER FOR 15 MINUTES WHILE HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING.

WASH WITH SOAP AND WATER. IF IRRITATION PERSIST, GET MEDICAL ATTENTION. INH ALATION: REMOVE TO FRESH AIR. RESTORE BREATHING. GET MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITING. IF OCCURS, KEEP HEAD BELOW HIPS. GET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:NONE

Lower Limits:7.5

Upper Limits:12.5

Extinguishing Media:WATER FOG

Fire Fighting Procedures:WEAR POSITIVE PRESSURE SELF CONTAINED

BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:VAPORS OF THIS SOLVENT MAY DEVELOP & FLAMMABLE ATMOSPHERE IN CONFINED OR POORLY-VENTILATED AREAS.

===== Accidental Release Measures =====

Spill Release Procedures:MINIMIZE AREA EFFECTED BY SPILL. BLOCK ANY POTENTIAL ROUTES TO WATER SYSTEMS. NOTIFY PROPER AUTHORITIES. USE ABSORBENT TO RECOVER SPILLED MATERIAL. KEEP OUT OF WATER SUPPLIES.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====

===== **Handling and Storage**=====

Handling and Storage Precautions:HANDLE W/REASONABLE CARE. AVOID BREATHING VAPORS. STORE IN COOL, DRY PLACE. CONCENTATED VAPORS HEAVIER THAN AIR, MAY COLLECT IN LOW/CONFINED AREAS.

Other Precautions:DON'T ENTER LOW OR CONFINED AREA WITHOUT SPECIAL BREATHING APPARATUS & OBSERVER PRESENT. DON'T PACKAGE IN ALUMINUM AEROSOL CAN W/FINELY DIVIDED ALUMINUM OR ALLOY IN AREOSOL CAN. ALUMINUM NOT ACCEPTABL E MAT'L FOR PUMPS, MIXERS, FITTINGS.

===== **Exposure Controls/Personal Protection**=====

Respiratory Protection:MAINTAIN ATMOSPHERIC LEVELS TLV/PEL,USE POSITIVE PRESSURE SCBA. IN CONFINED/POORLY VENTED AREA,USE POSTIVE PRESSURE SCBA.

Ventilation:CONTROL AIRBORNE CONCENTRATION