Product ID:95/5 SOLID WIRE SOLDER, 22004 MSDS Date:01/01/1996 FSC:3439 NIIN:01-324-0891 **MSDS Number: CCPJH** === Responsible Party === Company Name:OATEY CO Address:4700 WEST 160TH ST Box:35096 City:CLEVELAND State:OH ZIP:44135 Country:US Info Phone Num:216-267-7100 Emergency Phone Num:303-623-5716 CAGE: 53472 === Contractor Identification === Company Name: OATEY CO Address:4700 WEST 160TH STREET Box:35906 City:CLEVELAND State:OH ZIP:44135 Country:US Phone:216-267-7100/303-623-5716 CAGE:53472

Ingred Name:TIN CAS:7440-31-5 RTECS #:XP7320000 Fraction by Wt: 95% OSHA PEL:2 MG/M3 ACGIH TLV:2 MG/M3

Ingred Name:ANTIMONY (SARA 313) (CERCLA) CAS:7440-36-0 RTECS #:CC4025000 Fraction by Wt: 5% OSHA PEL:0.5 MG/M3 ACGIH TLV:0.5 MG/M3 (SB LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:INHALATION: IF HEATED, FUMES MAY PRODUCE RESPIRATORY IRRITATION, FEVER, CHILLS, MUSCULAR PAIN, VOMITING AND SWEATING. SKIN: FUMES MAY CAUSE IRRITATION. EYES: FUMES MAY CAUSE IRRITA TION. INGESTION: MAY CAUSE ABDOMINAL PAIN, GASTROINTESTINITIS, INTERNAL CUTS OR OBSTRUCTIONS. TARGET ORGANS: LUNG, SKIN, (EFTS OF OVEREXP) Explanation of Carcinogenicity:NOT RELEVANT Effects of Overexposure:HLTH HAZ: EYE, IRRITANT BY HEATED FUMES. Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

First Aid:SKIN: IF IRRIT ARISES, WASH THOROUGHLY W/SOAP & WATER. SEEK MED ATTN IF IRRIT PERSISTS. EYE

S: IF FUMES CAUSE IRRIT, MOVE TO FRESH AIR & IRRIGATE EYES W/WATER FOR AT LEAST 15 MIN. IF IRRIT PERSISTS, SE EK MED ATTN. IF EYE IS STRUCK W/WIRE, SEEK MED ATTN. INHAL: MOVE TO FRESH AIR. IF BRTHG IS DFCLT, GIVE OXYGEN. IF NOT BRTHG, GIVE ARTF RESP. KEEP VICTIM QUIET & WARM. CALL POIS CTL CTR OR MD (SUPDAT)

Extinguishing Media:SM FIRES: USE DRY CHEM, CARBON DIOIXDE, WATER OR FOAM EXTING. LG FIRES: EVA

CUATE AREA & CALL FIRE DEPARTMENT IMMED.

Fire Fighting Procedures: USE NIOSH APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT .

Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.

Spill Release Procedures: PLACE MATERIAL IN A CLOSED CONTAINER. Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Handling and Storage Precautions: PRACTICE GOOD PERSONAL HY

GIENE AND

HOUSEKEEPING.

Other Precautions:NONE SPECIFIED BY MANUFACTURER.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection: NIOSH APPROVED RESPIRATOR FOR TOXIC DUST/FUMES. Ventilation: GENERAL MECHANICAL: NECESSARY IF SOLDERING IN NON-VENTILATED AREA, LOCAL EXHAUST: OPEN DOORS & WINDOWS TO REMOVE FUMES. Protective Gloves: RUBBER GLOVES. Eve Protection: ANSI APPRVD CHEM WORKERS GOGGLES . Other Protective Equipment: ANSI APPROVED EYE WASH & DELUGE SHOWER . Work Hygienic Practices: PRACTICE GOOD PERSONAL HYGIENE AND HOUSEKEEPING. Supplemental Safety and Health FIRST AID PROC: IMMED. INGEST: DRINK WATER & CALL POIS CTL CTR OR MD IMMED. AVOID ALCOHOLIC BEVERAGES. NEVER GIVE ANYTHING BY MOUTH TO AN UNCON PERSON. Melt/Freeze Pt:M.P/F.P Text:>450F,>232C Spec Gravity:9-11 Solubility in Water: INSOLUBLE Appearance and Odor:SILVER-GRAY WIRE METAL; NO ODOR. ======== Stability Indicator/Materials to Avoid:YES STRONG OXIDIZERS. Stability Condition to Avoid:NOT APPLICABLE. Hazardous Decomposition Products: LEAD FUMES ABOVE MELTING POINT. Waste Disposal Methods: ACCORDING TO LOCAL, STATE AND FEDERAL

Waste Disposal Methods:ACCORDING TO LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by eleme

nts of the Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.