

SCOT LABORATORIES -- HOSE ASSEMBLY LUBRICANT, 222070 -- 9150-01-359-6563

=====
Product Identification
=====

Product ID:HOSE ASSEMBLY LUBRICANT, 222070

MSDS Date:01/27/1992

FSC:9150

NIIN:01-359-6563

MSDS Number: CCPJJ

=== Responsible Party ===

Company Name:SCOT LABORATORIES

Address:16841 PARK CIRCLE DR

City:CHAGRIN FALLS

State:OH

ZIP:44022

Country:US

Info Phone Num:215-543-3033

Emergency Phone Num

:215-543-3033

CAGE:SCTLA

=== Contractor Identification ===

Company Name:SCOT LABORATORIES

Address:16841 PARK CIRCLE DR

Box:City:CHAGRIN FALLS

State:OH

ZIP:44022

Country:US

Phone:216-543-3033

CAGE:SCTLA

=====
Composition/Information on Ingredients
=====

Ingred Name:PETROLEUM DISTILLATES

CAS:68551-15-5

OSHA PEL:N/K

ACGIH TLV:400 PPM (MFR)

=====
Hazards Identification
=====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: In

halation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:SKIN CONTACT:PROLONGED CONTACT MAY
CAUSE DERMATITIS. EYE CONTACT:POSSIBLE IRRITATION.
INGESTION:HARMFUL IF SWALLOWED.
Explanation of Carcinogenicity:NOT RELEVANT
Effects of Overexposure:SKIN CONTACT:PROLONGED CONTACT MAY CAUSE
DERMATITIS. EYE CONTACT:POSSIBLE IRRITANT. INGESTION:NAUSEA,
DIARRHEA.
Medical Cond Aggravated by Exposure:RESPIRATORY CONDITIONS.

==

===== First Aid Measures =====

First Aid:INHAL:REMOVE TO FRESH AIR. SUPPORT BREATHING (GIVE O₂/ARTF
RESP) . EYES:FLUSH W/WATER FOR AT LEAST 15 MINUTES. IF IRRITATION
PERSISTS, CONSULT MD IMMEDIATELY. SKIN:WASH W/SOAP & WATER. CHANGE
S OAKEN CLOTHING. INGEST:DO NOT INDUCE VOMITING. CONTAINS PETROLEUM
DISTILLATES. CONSULT MD.

===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:380F,193C
Exti
nguishing Media:TREAT AS CLASS B FIRE. USE CARBON DIOXIDE, FOAM OR
POWDER.
Fire Fighting Procedures:USE NIOSH APPROVED SCBA & FULL PROTECTIVE
EQUIPMENT .
Unusual Fire/Explosion Hazard:DO NOT USE HOT SURFACES & NEAR SOURCES OF
IGNITION SUCH AS FIRE, SPARKS OR WELDING EQUIPMENT.

===== Accidental Release Measures =====

Spill Release Procedures:MOP UP, WET VACUUM OR USE AN ABSORBENT
MATERIAL (SAND, EARTH, CLAY OR SAWDUST). RINSE AREA W/WATER &
DETERG
ENT TO COMPLETELY REMOVE PRODUCT.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:HANDLE IN VENTILATED AREA. DO NOT
STORE NEAR OPEN FIRE OR DIRECT HEAT. VENT LARGE TANKS TO OUTSIDE.
Other Precautions:NONE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH APPROVED RESPIRATOR APPROPRIATE FOR
EXPOSURE OF CONCERN . NONE NORMALLY NEEDED.

V

entilation:LOCAL EXHAUST:NORMALLY ADEQUATE. MECHANICAL(GENERAL): IF TLV'S ARE EXCEEDED USE MECH VENT OF MIN VELOCITY OF 60 FPM.

Protective Gloves:IMPERVIOUS GLOVES .

Eye Protection:ANSI APPROVED CHEM WORKERS GOGGS .

Other Protective Equipment:EYE WASH FOUNTAIN & DELUGE SHOWER WHICH MEET ANSI DESIGN CRITERIA . NONE NEEDED FOR NORMAL USE.

Work Hygienic Practices:FOLLOW GOOD MANUFACTURING & HOUSEKEEPING PRACTICES.

Supplemental Safety and Health
NONE SPECIFIED BY MANUFACTURER.

=====

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:>378F,>192C

Vapor Pres:NEGLIGIBLE

Vapor Density:>1

Spec Gravity:0.89 (H*2O=1)

Evaporation Rate & Reference: