View NSN Online: https://aerobasegroup.kr/nsn/8030-00-458-5666

## CONAP INC. -- CONATHANE CE-1155 PART B CURATIVE -- 8030-00-458-5666

============= Product Identification ========================

Product ID:CONATHANE CE-1155 PART B CURATIVE

MSDS Date:08/10/1993

FSC:8030

NIIN:00-458-5666

Kit Part:Y

MSDS Number: CCSSY
=== Responsible Party ===
Company Name: CONAP INC.
Address: 1405 BUFFALO STREET

City:OLEAN State:NY ZIP:14760 Country:US

Info Phone Num:716-372-9650 Emergency Phone Num:716-372-

9650

Preparer's Name: MARVIN A. FRIEDMAN

CAGE:16245

=== Contractor Identification ===

Company Name: CONAP INC., WHOLLY OWNED SUBSIDIARY OF CYTEC INDUSTRIES

INC.

Address:1405 BUFFALO STREET

Box:City:OLEAN

State:NY ZIP:14760 Country:US

Phone:716-372-9650

CAGE:16245

======= Composition/Information on Ingredients ========

Ingred Name: TOLUENE (SARA 313) (CERCLA) LD50: (ORAL, RAT) 2.5 G/KG

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 5,000 MG/KG

Routes of Entry: Inhalation:YES Ski

n:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:DIRECT CONTACT WITH THIS MATERIAL MAY
CAUSE MODERATE EYE AND MILD SKIN IRRITATION. INHALATION
OVEREXPOSURE MAY CAUSE IRRITATION OF THE RESPIRATORY TRACT.
CHRONIC: TOLUENE APPEARS ON THE NAVY LISTING O F OCCUPATIONAL
CHEMICAL REPRODUCTIVE HAZARDS. SEEK CONSULTATION FROM APPROPRIATE
HEALTH PROFESSIONALS (EFTS OF OVEREXP)
Explanation of Carcinogenicity:NOT RELEVANT
Effects o f Overexposure:HLTH HAZ: CONCERNING LATEST HAZARD LIST INFO
AND SAFE HANDLING AND EXPOSURE INFO.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.
Medical Colid Aggravated by Exposure. NOINE SPECIFIED BY MANOPACTORER.
======================================
First Aid:INGEST: CALL MD IMMEDIATELY . INHAL: REMOVE TO FRESH AIR.
SUPPORT BREATHING (GIVE OXYGEN/ARTIFICIAL RESPIRATION) . SKIN: WASH
AFFECTED AREAS OF SKIN WITH SOAP AND WATER, EYES: IMMEDIATELY
IRRIGATE WITH PLENTY OF WATER FOR AT LEAST 15 MI
NUTES. OBTAIN
MEDICAL ATTENTION IF IRRITATION PERSISTS.
WESTONE AT TEITHOUT INTO THE ENGINE OF
======================================
Flash Point Method:TCC
Flash Point Method:TCC
Flash Point Method:TCC Flash Point:55.0F,12.8C
Flash Point Method:TCC Flash Point:55.0F,12.8C Extinguishing Media:USE WATER SPRAY, ALCOHOL FOAM, CARBON DIOXIDE OR
Flash Point Method:TCC Flash Point:55.0F,12.8C Extinguishing Media:USE WATER SPRAY, ALCOHOL FOAM, CARBON DIOXIDE OR DRY CHEMICAL TO EXTINGUISH FIRES. WATER STREAM MAY BE INEFFECTIVE.
Flash Point Method:TCC Flash Point:55.0F,12.8C Extinguishing Media:USE WATER SPRAY, ALCOHOL FOAM, CARBON DIOXIDE OR DRY CHEMICAL TO EXTINGUISH FIRES. WATER STREAM MAY BE INEFFECTIVE. Fire Fighting Procedures:USE NIOSH APPROVED SCBA AND FULL PROTECTIVE
Flash Point Method:TCC Flash Point:55.0F,12.8C Extinguishing Media:USE WATER SPRAY, ALCOHOL FOAM, CARBON DIOXIDE OR DRY CHEMICAL TO EXTINGUISH FIRES. WATER STREAM MAY BE INEFFECTIVE. Fire Fighting Procedures:USE NIOSH APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT. USE WATER TO KEEP CONTAINERS COOL. Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.
Flash Point Method:TCC Flash Point:55.0F,12.8C Extinguishing Media:USE WATER SPRAY, ALCOHOL FOAM, CARBON DIOXIDE OR DRY CHEMICAL TO EXTINGUISH FIRES. WATER STREAM MAY BE INEFFECTIVE. Fire Fighting Procedures:USE NIOSH APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT. USE WATER TO KEEP CONTAINERS COOL.
Flash Point Method:TCC Flash Point:55.0F,12.8C Extinguishing Media:USE WATER SPRAY, ALCOHOL FOAM, CARBON DIOXIDE OR DRY CHEMICAL TO EXTINGUISH FIRES. WATER STREAM MAY BE INEFFECTIVE. Fire Fighting Procedures:USE NIOSH APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT. USE WATER TO KEEP CONTAINERS COOL. Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.
Flash Point Method:TCC Flash Point:55.0F,12.8C Extinguishing Media:USE WATER SPRAY, ALCOHOL FOAM, CARBON DIOXIDE OR DRY CHEMICAL TO EXTINGUISH FIRES. WATER STREAM MAY BE INEFFECTIVE. Fire Fighting Procedures:USE NIOSH APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT. USE WATER TO KEEP CONTAINERS COOL. Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.  ==================================
Flash Point Method:TCC Flash Point:55.0F,12.8C Extinguishing Media:USE WATER SPRAY, ALCOHOL FOAM, CARBON DIOXIDE OR DRY CHEMICAL TO EXTINGUISH FIRES. WATER STREAM MAY BE INEFFECTIVE. Fire Fighting Procedures:USE NIOSH APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT. USE WATER TO KEEP CONTAINERS COOL. Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.  ==================================
Flash Point Method:TCC Flash Point:55.0F,12.8C Extinguishing Media:USE WATER SPRAY, ALCOHOL FOAM, CARBON DIOXIDE OR DRY CHEMICAL TO EXTINGUISH FIRES. WATER STREAM MAY BE INEFFECTIVE. Fire Fighting Procedures:USE NIOSH APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT. USE WATER TO KEEP CONTAINERS COOL. Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.  ==================================
Flash Point Method:TCC Flash Point:55.0F,12.8C  Extinguishing Media:USE WATER SPRAY, ALCOHOL FOAM, CARBON DIOXIDE OR DRY CHEMICAL TO EXTINGUISH FIRES. WATER STREAM MAY BE INEFFECTIVE.  Fire Fighting Procedures:USE NIOSH APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT. USE WATER TO KEEP CONTAINERS COOL.  Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.  ==================================

ecautions:KEEP AWAY FROM HEAT, SPARKS & FLAME.

AVOID CONTACT W/EYES, SKIN & CLOTHING. KEEP CONTAINER CLOSED. USE W/ADEQ VENT. WASH THOROUGHLY AFTER HANDLING.

Other Precautions:AREAS CONTIANING THIS MATERIAL SHOULD HAVE FIRE-SAFE PRACTICES AND ELECTRICAL EQUIPMENT IN ACCORDANCE WITH ELECTRIAL AND FIRE PROTECTION CODES (NFPA-30) GOVERNING CLASS I FLAMMABLE LIQUIDS.

===== Exposure Controls/Personal Protection ========

Respiratory Protection: WHERE EXPOS ARE BELOW

THE PERMISSIBLE EXPOSURE

LIMIT (PEL), NO RESPIRATORY PROT IS REQD. WHERE EXPOS EXCEED THE PEL, USE RESPIRATOR APPRVD BY NIOSH FOR MATERIAL & LEVEL OF EXPOS. SEE "GUIDE TO INDUSTR IAL RESPIRATORY PROTECTION" (NIOSH).

Ventilation:WHERE THIS MATL IS NOT USED IN A CLOSED SYSTEM, GOOD ENCLOSURE & LOC EXHST VENT SHOULD BE PROVIDED TO CONTROL EXPOSURE. Protective Gloves:IMPERVIOUS GLOVES.

Eye Protection: ANSI APPRVD CHEM WORKERS GOGGLES.

Other Protective Equipment: ANSI APPROVED EYE WAS

H & DELUGE SHOWER.

APRON, WORKPANTS, LONG SLEEVE WORK SHIRT OR DISPOSABLE COVERALLS RECOMD.

Work Hygienic Practices: FOOD, BEVERAGES & TOBACCO PRODS SHOULD NOT BE CARRED, STORED OR CONSUMED WHERE THIS MATL IS IN USE. BEFORE (SUPDAT)

Supplemental Safety and Health

SPILL PROC: BOOTS. COVER SPILLS/WSOME INTER ABSORB MATL; SWEEP UP & PLACE IN WASTE DISP CNTNR. FLUSH AREA W/WATER. HYGIENE PRACT: EATING, DRINKING OR SMOKING, WASH FACE & HANDS W/SOAP & WATER. AVOID S KIN CON

TACT.

======== Physical/Chemical Properties ==========

HCC:F2

Spec Gravity:0.95

Evaporation Rate & Deference: