

FLAMEMASTER CORP -- CS 3100 PART B -- 8030-00-631-8013

===== Product Identification =====

Product ID:CS 3100 PART B

MSDS Date:02/05/1996

FSC:8030

NIIN:00-631-8013

Kit Part:Y

MSDS Number: CCXPK

=== Responsible Party ===

Company Name:FLAMEMASTER CORP

Address:11120 SHERMAN WAY

City:SUN VALLEY

State:CA

ZIP:91352

Country:US

Info Phone Num:800-424-9300 CHEMTREC

Emergency Phone Num:818-982-1650

Preparer

's Name:HERBERT MOORE

CAGE:14439

=== Contractor Identification ===

Company Name:FLAMEMASTER CORP THE CHEM SEAL DIV

Address:11120 SHERMAN WAY

Box:City:SUN VALLEY

State:CA

ZIP:91352-4949

Country:US

Phone:818-982-1650

CAGE:14439

===== Composition/Information on Ingredients =====

Ingred Name:LEAD DIOXIDE

CAS:1309-60-0

RTECS #:OG0700000

Fraction by Wt: 64.0%

Other REC Limits:NONE SPECIFIED

OSHA PEL:0.05 MG/M3

ACGIH TLV:0.15 MG/M3

Ingred Name:LEAD OXIDE

CAS:1317-36-8

RTECS #:OG175

0000  
Fraction by Wt: 6.0%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:0.05 MG/M3  
ACGIH TLV:0.15 MG/M3

=====  
Hazards Identification  
=====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE: WEAKNESS, STUPOR. CHRONIC:  
KIDNEY DAMAGE, ANEMIA, REPRODUCTIVE DEFECTS.  
Effects of Overexposure:HEADACHE, MUSCLE AND JOINT PAIN, NEUROMUSCULAR  
DYSFUNCTION.  
Medical Cond Aggra  
vated by Exposure:ANEMIA, KIDNEY DISEASE, PREGNANCY.

=====  
First Aid Measures  
=====

First Aid:INGESTION: INDUCE VOMITING, CONSULT A PHYSICIAN AT ONCE. EYE  
CONTACT: FLUSH WITH LARGE AMOUNT OF WATER AND CONTACT PHYSICIAN.

=====  
Fire Fighting Measures  
=====

Flash Point Method:TCC  
Flash Point:>200F,>93C  
Autoignition Temp:Autoignition Temp Text:NA  
Lower Limits:NA  
Upper Limits:NA  
Extinguishing Media:FOAM, DRY CHEMICAL, CO2  
, WATER.  
Fire Fighting Procedures:USE A SELF-CONTAINED BREATHING APPARATUS WITH  
FULL FACEPIECE, IN CONFINED AREAS.  
Unusual Fire/Explosion Hazard:FIRE HAZARD EXISTS IF CONTACT WITH  
OXIDIZABLE MATERIALS AT HIGH TEMPERATURES OCCURS.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:SCOOP UP AND TRANSFER TO A SAFETY CONTAINER.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:STORE IN COOL DRY A

REA. KEEP  
CONTAINERS CLOSED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF SOOT IS FORMED, USE NIOSH APPROVED  
RESPIRATOR.

Ventilation:LOCAL EXHAUST: AIR HOOD; MECHANICAL: FAN.

Protective Gloves:RUBBER GLOVES.

Eye Protection:SAFETY GLASSES.

Other Protective Equipment:APPROPRIATE TO AVOID PROLONGED CONTACT.

Work Hygienic Practices:WASH HAND BEFORE EATING, DRINKING OR S

Supplemental Safety and Health

NK

===== Physical/Chemical

Properties =====

Boiling Pt:B.P. Text:644F,340C

Melt/Freeze Pt:M.P/F.P Text:LIQ@RM TEMP

Vapor Pres:NIL

Vapor Density:NA

Spec Gravity:3.00 (WATER=1)

VOC Pounds/Gallon:1

pH:6.8

Viscosity:NA

Evaporation Rate & Reference:NIL

Solubility in Water:NEGLIGIBLE

Appearance and Odor:BROWN PASTE; OILY ODOR

Percent Volatiles by Volume:3.0

Corrosion Rate:NA

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZABLE MATERIALS.

Stability Condition to Avoid:HIGH HEAT.

Hazardous Decomposition Products:LEAD OXIDE DUST AND ORGANICS.

===== Disposal Considerations =====

Waste Disposal Methods:RETURN TO SMELTER FOR RECLAMATION OR REACT WITH  
BASE AND DISPOSE ACCORDING TO FEDERAL, STATE & LOCAL REGULATIONS.

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by e

lements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.