

DEL PAINT CORP -- 9970 BLACK WRINKLE FINISH -- 8010-00-530-8380

===== Product Identification =====

Product ID:9970 BLACK WRINKLE FINISH

MSDS Date:11/05/1996

FSC:8010

NIIN:00-530-8380

MSDS Number: CDCJC

=== Responsible Party ===

Company Name:DEL PAINT CORP

Address:3105 E RENO AVE

City:OKLAHOMA CITY

State:OK

ZIP:73106-6699

Country:US

Info Phone Num:405-672-1431/800-866-6823

Emergency Phone Num:405-6

92-7269/405-672-1431

CAGE:EO523

=== Contractor Identification ===

Company Name:DEL PAINT CORP

Address:3105 E RENO AVE

City:OKLAHOMA CITY

State:OK

ZIP:73117-6699

Country:US

Phone:405-672-1431/800-866-6823

CAGE:EO523

Company Name:DEL PAINT MFG

Address:3105 EAST RENO

Box:City:OKLAHOMA CITY

State:OK

ZIP:73117

Country:US

Phone:405-672-1431

CAGE:39934

===== Composition/Information on Ingredients =====

Ingred Name:STODDARD SOLVENT (PETROLEUM DISTILLATE), MINERAL SPIRITS

*96

-4*
CAS:8052-41-3
RTECS #:WJ8925000
Fraction by Wt: 20-30%
Other REC Limits:525 MG/CUM
OSHA PEL:100 PPM
ACGIH TLV:100 PPM

Ingred Name:LIGHT ALIPHATIC NAPHTHA, VM & P NAPHTHA, LACOLENE *96-4*
CAS:64742-89-8
Fraction by Wt: 10-20%
OSHA PEL:300 PPM
ACGIH TLV:300 PPM

Ingred Name:HEXONE, METHYL ISOBUTYL KETONE (MIBK), 4-METHYL-2-PENTANONE
96-4
CAS:108-10-1
RTECS #:SA9275000
Fraction by Wt: 2.3%
Other REC Limits:50 PPM
OSHA PEL:50 PPM
ACGIH TLV:50 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000
LBS

Ingred Name:VOLATILE ORGANIC CONTENT: COATING & MATERIAL 3.33 LBS/GAL
RTECS #:9999999VO

===== Hazards Identification =====

LD50 LC50 Mixture:ORAL LD50(RAT): 25 ML/KG MINERAL SPIRITS
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION: NOSE & THROAT IRRITATION,
CNS DEPRESSION. SKIN: IRRITATION, DERMATITIS & LIQUID CAN BE
ABSORBED. EYES: IRRITATION.
INGESTION: MOUTH, THROAT, ESOPHAGUS &
STOMACH IRRITATION. REPEATED/PROLONGED OCCUPATIONAL OVEREXPOSURE
TO SOLVENTS MAY CAUSE PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:IRRITATION, DIZZINESS, BREATHING DIFFICULTY,
HEADACHES, LOSS OF COORDINATION, DEFATTING, TEARING, DISCOMFORT,
REDNESS, BLURRED VISION, NAUSEA, VOMITING, DIARRHEA.
Medical Cond Aggravated by Exposure:PRE-EXISTING EYE, SKIN &
RESPIRATORY DISORDERS.

=====

===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. EYES: IMMEDIATELY FLUSH
W/LARGE AMOUNTS OF WATER FOR 15 MINS. SKIN: THOROUGHLY WASH W/SOAP
& WATER. INGESTION: DON'T INDUCE VOMITING. OBTAIN MEDICAL ATTENTION
IN ALL C ASES.

===== Fire Fighting Measures =====

Flash Point:A FEW INCHES & GROUND
CONTAINER WHEN POURING. USE NON-SPARKING UTENSILS WHEN HANDLING.
HANDLE AS IGNITABLE LIQUID.
DON'T TAKE INTERNALLY. EMPTIED
CONTAINERS MAY RETAIN HAZAR DOUS RESIDUE & EXPLOSIVE VAPORS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR AN APPROPRIATE, PROPERLY FITTED NIOSH/MSHA
APPROVED RESPIRATOR DURING THE USE OF THIS PRODUCT UNTIL VAPOR &
MISTS LEVELS ARE