View NSN Online: https://aerobasegroup.kr/nsn/6750-01-341-6134

EASTMAN KODAK COMPANY -- 103 8660 PRE-BLEACH & REPLENISH,PROCESS E-6 AR,CONCENTRATE -- 6750-01-341-6134

Product ID:103 8660 PRE-BLEACH & REPLENISH, PROCESS E-6 AR, CONCENTRATE

MSDS Date:07/31/1996

FSC:6750

NIIN:01-341-6134

MSDS Number: CDJTT === Responsible Party ===

Company Name: EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY ZIP:14650 Count ry:US

Info Phone Num:716-477-3194 MSDS:800-242-2424

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST Box:City:ROCHESTER

State:NY

ZIP:14650-1115 Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name: EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD Box:City:ROCHESTER

State:NY

ZIP:14650-3129 Country:US

Phone:800-828-6203

CAGE:5K871

====== Com

## position/Information on Ingredients =======

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000 Fraction by Wt: 80 - 85%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:NOT RELEVANT ACGIH TLV:NOT RELEVANT

Ingred Name:STABILIZING AGENT

Fraction by Wt: 10 - 15%

Other REC Limits: NONE RECOMMENDED

Ingred Name: POTASSIUM SULFITE

CAS:10117-38-1 RTECS #:WT3530000 Fraction by Wt: 1 - 5%

Other REC Limits: NONE RECOMMENDED

Ingred Name: ETHYLENEDIAMINE-TETRAACETIC ACID (EDTA) (CERCLA)

CAS:60-00-4 RTECS #:A H4025000

Fraction by Wt: 1 - 5%

Other REC Limits: NONE RECOMMENDED

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name: METHYL ALCOHOL (METHANOL) (SARA 313) (CERCLA)

CAS:67-56-1

RTECS #:PC1400000 Fraction by Wt: 2%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:S, 200 PPM

ACGIH TLV:S,200PPM/250STEL; 96

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:1-THIOGLYCEROL

CAS:96-27-5

RTECS #:TY8140000

Fraction by Wt: 212F,>100C

Vapor Pres:18 @ 68F Vapor Density:0.6 Spec Gravity:1.20

pH:6.1 Solubilit y in Water:COMPLETE Appearance and Odor:COLORLESS LIQUID - ODORLESS Percent Volatiles by Volume:80- 85

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS, STRONG ACIDS, STRONG BASES
Stability Condition to Avoid:NONE
Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE,
SULFUR DIOXIDE, FORMALDEHYDE

======= Disposal Considerations ============

Waste Disposal Methods:DISCHA RGE, TREATMENT OR DISPOSAL MAY BE SUBJECT TO FEDERAL, STATE OR LOCAL LAWS. FLUSH TO SEWER WITH LARGE AMOUNT OF WATER.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competen t professional advice to verify and assume responsibility for the suitability of this information to their particular situation.