

PERFORMANCE CHEMICALS LTD -- VACTAN (5 LITER BOTTLE) -- 6850-01-432-8277

=====
Product Identification
=====

Product ID:VACTAN (5 LITER BOTTLE)

MSDS Date:12/21/1995

FSC:6850

NIIN:01-432-8277

MSDS Number: CDMKR

=== Responsible Party ===

Company Name:PERFORMANCE CHEMICALS LTD

Address:60 VERNEY ROAD

City:LONDON

Country:UK

Info Phone Num:757-481-0373

Emergency Phone Num:757-481-0373

CAGE:PERF0

=== Cont

ractor Identification ===

Company Name:PERFORMANCE CHEMICALS

Address:60 VERNEY ROAD

Box:UNKNOW

City:LONDON SE 163DH

Country:UK

Phone:02072313737

CAGE:U6889

Company Name:PERFORMANCE CHEMICALS LTD

Address:60 VERNEY ROAD

Box:City:LONDON, ENGLAND

Phone:804-858-2851

CAGE:PERF0

Company Name:RAYCO SERVICES INC

Address:5360 ROBIN HOOD RD

Box:City:NORFOLK

State:VA

ZIP:23513

Country:US

Phone:804-858-2885

CAGE:0PZ83

=====
Composition/Information on Ingredients
=====

Ingred Name:ETHANOL,

2-BUTOXY-; (2-BUTOXYETHANOL)

CAS:111-76-2

RTECS #:KJ8575000

Fraction by Wt: 1-5%

OSHA PEL:50 PPM, S

ACGIH TLV:25 PPM, S

Ingred Name:TANNIC ACID (CONTAINING ING 3)

CAS:1401-55-4

RTECS #:LW7800000

OSHA PEL:N/K

ACGIH TLV:N/K

Ingred Name:VINYL ACRYLIC COPOLYMERS

CAS:25586-24-7

OSHA PEL:N/K

ACGIH TLV:N/K

Ingred Name:SUPP DATA:ABSORBENT MATERIAL & TRANSFERRED TO CONTAINERS
FOR DISPOSAL. FINALLY WASH DOWN AREA W/WATER. SMALL (ING 5)

RTECS #:9999999ZZ

Ingred Name:ING 4:SPILL:TREAT AS PER RE

SIDUES DESCRIBED IN LARGE SPILL.

RTECS #:9999999ZZ

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES:CONTACT MAY LEAD TO SOME

IRRITATION. SKIN:INCIDENTAL SPLASHES MAY CAUSE NO EFFECTS IF WASHED
OFF. REPEATED AND/OR PROLONGED CONTACT MAY CAUSE IRRITATION.

INGESTION:INCIDE

NTAL SWALLOWING OF SMALL QUANTITIES DURING USE OF

THIS PRODUCT MAY LEAD TO NO SYMPTOMS OR MINOR IRRITATION. INGESTION
OF LARGE (EFTS OF OVEREXP)

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:HLTH HAZ:DOSES (UNLIKELY TO BE ACCIDENTAL) MAY
CAUSE NAUSEA, VOMITING, DIZZINESS. INHALATION:INHALATION OF VAPORS
FROM THIS PRODUCT IN SMALL DOSES NOT LIKELY TO PRODUCE ANY
SYMPTOMS. ANIMAL STUDIES CL EARLY DEMONSTRATED DOSE-RELATED
ADVERSEEFFECTS ON THE CNS, HE

MATOPOIETIC TISSUES, BLOOD, KIDNEYS
AND LIVER, (SUPP DATA)

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:EYES:IRRIGATE WITH EYEWASH SOLUTION OR CLEAN WATER FOR AT
LEAST 15 MINUTES, HOLDING EYELIDS APART. OBTAIN MEDICAL ATTENTION.
SKIN:WASH WITH WATER. IF ANY SYMPTOMS DEVELOP SEEK MEDICAL
ATTENTION. REMOVE ANY CONTAMINATED CLOTHING & WASH BEFORE RE-USE.
INGEST:WASH OUT MOUTH
WITH WATER. OBTAIN MEDICAL ATTENTION IF ILL
EFFECTS OCCUR. INHAL:REMOVE PATIENT FROM EXPOSURE, KEEP WARM & AT
REST.

===== Fire Fighting Measures =====

Extinguishing Media:WATER SPRAY, FOAM, DRY POWDER OR CO*2.
Fire Fighting Procedures:USE NIOSH APPROVED SCBA & FULL PROTECTIVE
EQUIPMENT .
Unusual Fire/Explosion Hazard:VACTAN IS NOT CONSIDERED A FIRE OR
EXPLOSION HAZARD.

===== Accidental Release Measures =====

Spill
Release Procedures:EXTING ANY NAKED FLAMES/HEATING ELEMENTS IN
VICIN OF SPILLAGE. AVOID PROD ENTERING SEWERS/OTHER WATERCOURSES.
IF PROD HAS ENTERED THESE INFORM LOC GOVT AGENCY/WATER AUTH. LG
SPILL:CONTAIN W/SAND, EART H/ANY OTHER SUITABLE ABSORB MATL.
TRANSFER(SUPDAT)
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID CONTACT W/SKIN & EYES. WEAR
APPROPRIATE PERSONAL
PROTECTIVE EQUIPMENT. ALWAYS USE PRODUCT IN
ADEQUATELY VENTILIATED AREAS.
Other Precautions:PROTECT FROM FREEZING. KEEP AT TEMPERATURES NOT
EXCEEDING 86C. KEEP IN TIGHTLY SEALED CONTAINERS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH APPROVED RESPIRATOR APPROPRIATE FOR
EXPOSURE OF CONCERN . NO SPECIAL EQUIPMENT REQUIRED. ENSURE
ADEQUATE VENTILATION FOR AREA OF PRODUCT USE.
Ventilation:NO SPECIAL MEASURES REQUIRED IF STORED A

PPROPRIATELY.

ALWAYS USE PRODUCT IN ADEQUATELY VENTILATED AREAS.

Protective Gloves:RUBBER OR PLASTIC GLOVES.

Eye Protection:ANSI APPROVED CHEM WORKERS GOGGS .

Other Protective Equipment:ANSI APPROVED EYE WASH FOUNTAIN & DELUGE SHOWER . IF HNDLG LG QTYS OR SPLASHES POSS WEAR PROT OVERALLS & BOOTS.

Work Hygienic Practices:ALWAYS FOLLOW PRINCIPLES OF GOOD OCCUPATIONAL HYGIENE TO CONTROL PERSONAL EXPOSURE.

Supplemental Safety and Health

NOTE:AFTER COATING & DRYING VACTAN CAN W/STAND

MAX SURF TEMP OF 140F

BEFORE PROD BEGINS TO BREAK DOWN (MFR). EFTS OF OVEREXP:ASSOC W/ADMIN OF ETHYLENE GLYCOL MONOBUTYL ETHER (EGBE). (EXTRACTED FROM DH HS (NIOSH) PUBLICATION NO.90-118) . SPILL PROC:LIQ TO SALVAGE CNTNRS. ANY RESIDUES SHOULD BE ABSORBED ONTO (ING 4)

===== Physical/Chemical Properties =====

Melt/Freeze Pt:M.P/F.P Text:>25F,>-4C

Spec Gravity:1.23

pH:85F.

Hazardous Decomposition Products:NONE KNOWN.

===== Disposal Con
siderations =====

Waste Disposal Methods:DISPOSAL MUST BE I/A/W FEDERAL, STATE & LOCAL REGULATIONS . VIA APPROVED WASTE DISPOSAL CONTRACTOR TO AN APPROVED DISPOSAL SITE FOR DISPOSAL BY APPROVED METHOD. OBSERVE ALL LOCAL & NATIONAL REGU LATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or i
mplied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.