

BTR VALVE SEALANTS INC -- BTR 950 SEALANT (STICK GRADE)

=====
MSDS Safety Information
=====

FSC: 9150
NIIN: 00-261-8289
MSDS Date: 05/01/1995
MSDS Num: CDQLK
Product ID: BTR 950 SEALANT (STICK GRADE)
MFN: 01
Responsible Party
Cage: 14262
Name: BTR VALVE SEALANTS INC
Address: 140 THOMAS ROAD
City: SULPHUR SPRI
NGS TX 75482
Info Phone Number: 903-439-6465
Emergency Phone Number: 903-439-6465
Proprietary Ind: Y
Review Ind: Y
Published: Y

=====
Contractor Summary
=====

Cage: 80318
Name: BTR VALVE SEALANTS INC
Address: 140 THOMAS RD
City: SULPHUR SPRINGS TX 75482
Phone: 903-439-6465
Cage: 9K140
Name: BTR VALVE SEALANTS INC
Address: REPLACED BY CAGE CODE 80318
Box: UNKNOW
City: UNKNOWN NK 00000
Phone: UNKNOW
WN
Cage: 14262
Name: BTR VALVE SEALANTS, INC.
Address: 430 NORTH LEXINGTON AVE
City: PITTSBURGH PA 15208
Phone: 412-244-5251

=====
Item Description Information
=====

Item Manager: S9G
Item Name: GREASE,PLUG VALVE
Specification Number: MIL-G-6032
Type/Grade/Class: B CLASS,TYPE II
Unit of Issue: BX
Quantitative Expression: 00000000024EA
UI Container Qty: G
Type of Container: STICKS
=====

=====
Ingredients
=====

Name: *** PROPRIETARY ***

=====

Health Hazards Data
=====

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER.

Route Of Entry Inds - Inhalation: NO

Skin: YES

Ingestion: NO

Carcinogenicity Inds - NTP: NO

IARC: YES

OSHA: NO

Effects of Exposure: INHAL:NONE EXPECTE

D. INGEST:MAY BE MILDLY IRRIT TO

GASTROINTESTINAL TRACT. SKIN:PROLONGED/REPEATED SKIN CONTACT MAY PRODUCE MILD IRRIT. EYE:MATERIAL CONTACTING EYES MAY PRODUCE IRRITATION.

Explanation Of Carcinogenicity: PER MSDS:IARC-LIM EVIDENCE FOR CARCI TO HUMANS FOR ORGANOPHILIC CLAY(ENCAPSULATED)(CONTAINS 0-4% TOT CRYSTALLINE SILICA)

Signs And Symptions Of Overexposure: MILDLY GI TRACT IRRIT, MILD SKIN IRRIT UPON PROL/REP CONTACT, EYE IRRIT.

Medical Cond Aggravated By Exposure: NONE SPECIFIED BY MANUFACTURER.

First Aid: EYE:FLUSH EYES FOR 15MINS WITH CLEAR WATER.CONTACT

PHYSICIAN.SKIN:WASH THOROUGHLY W/SOAP/WATER.INHAL:VAPOR PRESSURE IS VERY LOW.VAPOR INHAL IS NOT CONSIDERED A PROBLEM UNDER NORMAL USAGE CONDITIONS.IN GEST:IF SWALLOWED CONSULT PHYSICIAN.

=====
Handling and Disposal
=====

Spill Release Procedures: RECOVER FREE MATERIAL. ADD SUITABLE ABSORBANT TO SPILLS AREA. CLEAN SPILL AREA W/DETERGENT SOLUTION.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Waste Disposal Methods: INCINERATE IN FURNACE OR OTHERWISE DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE LOCAL, STATE AND FEDERAL REQUUMTS & REGS.

Handling And Storage Precautions: STORE IN SEALED CONTIANERS TO AVOID CONTAMINATION W/FOREIGN PARTICLES.

Other Precautions: ORGANOPHILIC CLAY CONTAINS <4% TOTAL CRYSTALLINE SILICA WHICH IS ENCAPSULATED IN FORMULATION.NO INUURY FROM AIRBORNE DUSTS SHOULD RESULT

UNDER NORMAL USAGE CONDITONS.

=====
Fire and Explosion Hazard Information
=====

Flash Point Method: COC

Flash Point Text: 320F,160C

Lower Limits: NA

Upper Limits: NA

Extinguishing Media: DRY CHEMICAL POWDER, CARBON DIOXIDE, CHEMICAL FOAM.

Fire Fighting Procedures: WEAR SELF-CONTAINED BREATHING APPARATUS WHEN FIGHTING
FIRE IN CONFINED AREAS.TREAT AS BURNING OIL.

Unusual Fire/Explosion Hazard: N
ONE KNOWN.

=====
Control Measures
=====

Respiratory Protection: RESPIRATORY PROTECTION NOT NEEDED UNDER NORMAL USAGE
CONDITIONS.

Ventilation: ADEQUATE VENTIALTION IN ACCORDANCE WITH GOOD ENGINEERING PRACTICE
IS SUFFICIENT.

Protective Gloves: RESISTANT GLOVES AS NEEDED TO MIN CONTACT

Eye Protection: SAF GLASSES ADVISED AS STD SAF PROTECTIN

Other Protective Equipment: NONE NORMALLY NEEDED.

Work

Hygienic Practices: NONE SPECIFIED BY MANUFACTURER.

=====
Physical/Chemical Properties
=====

HCC: V6

B.P. Text: NA

Vapor Pres: NIL

Vapor Density: NA

Spec Gravity: 1.17 @75F

Evaporation Rate & Reference: NIL.

Solubility in Water: NEGIGIBLE.

Appearance and Odor: TAN GREASE IN STICK FORM. SLIGHT FATTY ODOR.

Percent Volatiles by Volume: NIL

=====
Reactivity Data
=====

Stability Indicator: YES

Stability Condition To Avoid: NONE SPECIFIED BY MANUFACTURER.

Materials To Avoid: AVOID CONTACT W/STRONG OXIDIZERS.

Hazardous Decomposition Products: INCOMPLETE COMBUSTION MAYPRODUCE CARBON
MONOXIDE, CARBON DIOXIDE & ASPHYXIANTS.

Hazardous Polymerization Indicator: NO

=====
Toxicological Information
=====

=====

Ecological Information

MSDS Transport Information

Regulatory Information

Other Information

Transportation Information

Responsible Party Cage: 14262
 Trans ID NO: 62333
 Product ID: BTR 950 SEALANT (STICK GRADE)
 MSDS Prepared Date: 05/01/1995
 Review Date: 05/13/1997
 MFN: 1
 Net Unit Weight: UNKNOWN
 Multiple KIT Number: 0
 Review IND: Y
 Unit Of Issue: BX
 Container QTY: G
 Type Of Container: STICKS
 Additional Data: PER MSDS:DOT CAL
 SSIFICATION:NOT REGULATED, DOT PROPER SHIPPING
 NAME/ID #/HAZARD CLASS:NOT APPLICABLE

Detail DOT Information

DOT PSN Code: ZZZ
 DOT Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

Detail IMO Information

IMO PSN Code: ZZZ
 IMO Proper Shipping Name: NOT REGU

LATED FOR THIS MODE OF TRANSPORTATION

=====
Detail IATA Information
=====

IATA PSN Code: ZZZ

IATA Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

=====
Detail AFI Information
=====

AFI PSN Code: ZZZ

AFI Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

=====
HAZCOM Label
=====

Product ID: BTR 950 SEALANT (STICK GRADE)

Cage: 14262

Company Name: BTR VALVE SEALANTS, INC.

Street: 430 NORTH LEXINGTON AVE

City: PITTSBURGH PA

Zipcode: 15208

Health Emergency Phone: 903-439-6465

Date Of Label Review: 05/13/1997

Status Code: C

Label Date: 05/13/1997

Year Procured: 1997

Origination Code: F

Eye Protection IND: YES

Skin Protection IND: YES

Signal Word: CAUTION

Health

h Hazard: None

Contact Hazard: Slight

Fire Hazard: None

Reactivity Hazard: None

Hazard And Precautions: INHAL:NONE EXPECTED. INGEST:MAY BE MILDLY IRRIT TO GASTROINTESTINAL TRACT. SKIN:PROLONGED/REPEATED SKIN CONTACT MAY PRODUCE MILD IRRIT. EYE:MATERIAL CONTACTING EYES MAY PRODUCE IRRITATION. STORE IN SEALED CONTAINERS TO AVOID CONTAMINATION W/FOREIGN PARTICLES. FIRST AID: EYE:FLUSH EYES FOR 15MINS WITH CLEAR WATER.CONTACT PHYSICIAN.SKIN:WASH THOROUGHLY W/SOAP/WATER.INHAL:VAPOR PRESSUR

E IS VERY LOW.V APOR INHAL IS NOT CONSIDERED

A PROBLEM UNDER NORMAL USAGE CONDITIONS.INGEST:IF SWALLOWED CONSULT
PHYSICIAN. TARGET ORAGAS:SKIN.

=====
Disclaimer (provided with this information by the compiling agencies): This
information is formulated for use by elements of the Department of Defense.
The United States of America in no manner whatsoever expressly or implied
warrants, states, or intends said information to have any applic
ation, use or
viability by or to any person or persons outside the Department of Defense
nor any person or persons contracting with any instrumentality of the United
States of America and disclaims all liability for such use. Any person
utilizing this instruction who is not a military or civilian employee of the
United States of America should seek competent professional advice to verify
and assume responsibility for the suitability of this information to their
particular situation
regardless of similarity to a corresponding Department
of Defense or other government situation.