

SHELL OIL COMPANY -- SHELL SPIRAX(R) HEAVY DUTY 80W/90, 59210 -- 9150-01-035-5393

=====
Product Identification
=====

Product ID:SHELL SPIRAX(R) HEAVY DUTY 80W/90, 59210

MSDS Date:10/14/1992

FSC:9150

NIIN:01-035-5393

MSDS Number: CDQMN

=== Responsible Party ===

Company Name:SHELL OIL COMPANY

Address:HEALTH, SAFETY AND ENVIRONMENT

Box:4320

City:HOUSTON

State:TX

ZIP:77210

Country:US

Info Phone Num:7

13-241-4819/4141/2252 FAX -6511

Emergency Phone Num:713-473-9461/800-424-9300(CHEMTREC)

CAGE:54527

=== Contractor Identification ===

Company Name:EQUILON ENTERPRISES LLC PRODUCT STEWARDSHIP

Address:1111 BAGBY RD RM 4325D

Box:674414

City:HOUSTON

State:TX

ZIP:77267-4414

Country:US

Phone:877-276-7285

CAGE:3N254

Company Name:SHELL OIL (800-535-2104)

Address:309 JEFFERSON HWY

Box:UNKNOW

City:NEW ORLEANS

State:LA

ZIP:70121

Country:US

Phone:800-535-2104

CAGE:4Y429

Company Name:SHELL OIL COMPANY

Address

:Box:2463
City:HOUSTON
State:TX
ZIP:77210
Country:US
Phone:800-231-6950
CAGE:54527

=====
=====
===== Composition/Information on Ingredients =====
=====

Ingred Name:RESIDUAL OILS, HYDROTREATED
CAS:64742-57-0
Fraction by Wt: 0-65%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:5 MG/M3 (OIL MIST)
ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name:SOLVENT, DEWAXED RESIDUAL OIL (PETROLEUM)
CAS:64742-62-7
Fraction by Wt: 0-65%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:5 MG/M3 AS OIL MIST
ACGIH TLV:5 MG/M3 AS OI
L MIST

Ingred Name:MINERAL OIL, PETROLEUM DISTILLATE, SOLVENT DEWAXED
(SEVERE), HEAVY PARAFFINIC
CAS:64742-65-0
RTECS #:PY8038501
Fraction by Wt: 0-35%
Other REC Limits:NONE RECOMMENDED

Ingred Name:HYDROTREATED MIDDLE PETROLEUM DISTILLATE
CAS:64742-46-7
RTECS #:JN9379645
Fraction by Wt: 0-20%
Other REC Limits:NONE RECOMMENDED

Ingred Name:MINERAL OIL
CAS:64742-53-6
RTECS #:PY8036000
Fraction by Wt: 0-20%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:5 MG/M3 (OIL MIST)
ACGIH TLV:5 MG/M3 (OIL M

IST)

Ingred Name: DISTILLATES, ACID-TREATED HEAVY NAPHTHENIC

CAS: 64742-18-3

RTECS #: PY8032000

Fraction by Wt: 0-15%

Other REC Limits: NONE RECOMMENDED

OSHA PEL: 300 PPM

ACGIH TLV: 300 PPM

Ingred Name: MINERAL OIL, HYDROTREATED (SEVERE), HEAVY NAPHTHENIC
DISTILLATE

CAS: 64742-52-5

RTECS #: PY8035001

Fraction by Wt: 0-15%

Other REC Limits: NONE RECOMMENDED

Ingred Name: ADDITIVES PACKAGE

Fraction by Wt: